

ETSI TS 132 643 V8.1.0 (2011-01)

Technical Specification

**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Configuration Management (CM);
UTRAN network resources Integration Reference Point (IRP);
Common Object Request Broker Architecture (CORBA)
Solution Set (SS)
(3GPP TS 32.643 version 8.1.0 Release 8)**



Reference

RTS/TSGS-0532643v810

Keywords

LTE, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Foreword..... | 4 |
| Introduction | 4 |
| 1 Scope | 5 |
| 2 References | 5 |
| 3 Definitions and abbreviations..... | 6 |
| 3.1 Definitions | 6 |
| 3.2 Abbreviations | 6 |
| 4 Architectural features | 6 |
| 4.1 Notifications | 6 |
| 5 Mapping | 7 |
| 5.1 General mappings..... | 7 |
| 5.2 UTRAN NRM Information Object Class (IOC) mapping..... | 7 |
| 5.2.1 IOC RncFunction..... | 7 |
| 5.2.2 IOC UtranGenericCell | 8 |
| 5.2.3 IOC NodeBFunction | 9 |
| 5.2.4 IOC IubLink..... | 9 |
| 5.2.6 IOC ExternalUtranGenericCell..... | 10 |
| 5.2.7 IOC AntennaFunction..... | 11 |
| 5.2.8 IOC ExternalRncFunction | 11 |
| 5.2.9 UtranCellFDD..... | 12 |
| 5.2.10 UtranCellTDD | 12 |
| 5.2.11 UtranCellTDDLcr..... | 13 |
| 5.2.12 UtranCellTDDHcr | 13 |
| 5.2.13 ExternalUtranCellFDD | 14 |
| 5.2.14 ExternalUtranCellTDD..... | 14 |
| 5.2.15 ExternalUtranCellTDDHcr | 15 |
| 5.2.16 ExternalUtranCellTDDLcr | 15 |
| 5.2.17 IOC TmaFunction | 16 |
| 6 Rules for management information model extensions | 17 |
| 6.1 Allowed extensions | 17 |
| 6.2 Extensions not allowed..... | 17 |
| Annex A (normative): CORBA IDL, NRM definitions | 18 |
| A.1 IDL specification (file name "UtranNetworkResourcesNRMDefs.idl")..... | 18 |
| Annex B (informative): Change history | 25 |
| History | 26 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 32.641: "Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP); Requirements".
- 32.642: "Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP); Network Resource Model (NRM)".
- 32.643: "Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set (SS)".**
- 32.645: "Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP); Bulk CM eXtensible Markup Language (XML) file format definition".

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G-network as it evolves. CM actions have the objective to control and monitor the actual configuration on the NEs and NRs, and they may be initiated by the operator or functions in the OSs or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as a single action on a Network Element (NE) of the 3G-network or as part of a complex procedure involving actions on many NEs.

The Itf-N interface for Configuration Management is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2]. For CM, a number of IRPs (and the Name Convention) are defined herein, used by this as well as other technical specifications for telecom management produced by 3GPP.

1 Scope

The purpose of this UTRAN Network Resources IRP: CORBA Solution Set is to define the mapping of the IRP information model (see TS 32.642 [4]) to the protocol specific details necessary for implementation of this IRP in a CORBA/IDL environment.

This Solution Set specification is related to 3GPP TS 32.642 V8.0.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 32.642: "Telecommunication management; Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] OMG Notification Service, Version 1.0.
- [7] OMG CORBA services: Common Object Services Specification, Update: November 22, 1996.
- [8] The Common Object Request Broker: Architecture and Specification (for specification of valid version, see [1]).
- [9] 3GPP TS 32.303: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
- [10] 3GPP TS 32.111-3: "Telecommunication management; Fault Management; Part 3: Alarm Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".

3 Definitions and abbreviations

3.1 Definitions

For terms and definitions please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and TS 32.642 [4].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|---|
| CORBA | Common Object Request Broker Architecture |
| DN | Distinguished Name |
| IS | Information Service |
| IDL | Interface Definition Language (OMG) |
| IOC | Information Object Class |
| IRP | Integration Reference Point |
| MO | Managed Object |
| MOC | Managed Object Class |
| NRM | Network Resource Model |
| OMG | Object Management Group |
| SS | Solution Set |

4 Architectural features

The overall architectural feature of UTRAN Network Resources IRP is specified in TS 32.642 [4]. This clause specifies features that are specific to the CORBA SS.

4.1 Notifications

Notifications are sent according to the Notification IRP: CORBA SS (see 3GPP TS 32.303 [9]).

5 Mapping

5.1 General mappings

Attributes modelling associations as defined in the NRM (here also called 'reference attributes') are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

5.2 UTRAN NRM Information Object Class (IOC) mapping

5.2.1 IOC RncFunction

Mapping from NRM IOC RncFunction attributes to SS equivalent MOC RncFunction attributes

| NRM Attributes of IOC RncFunction in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|---|---------------|---------|-------------------|------|-------|
| rncFunctionId | rncFunctionId | string | M | M | - |
| mcc | mcc | long | M | M | M |
| mnc | mnc | long | M | M | M |
| rncId | rncId | long | M | M | M |

5.2.2 IOC UtranGenericCell

Mapping from NRM IOC UtranGenericCell attributes and associations to SS equivalent MOC UtranGenericCell attributes

| NRM Associations/Attributes of IOC UtranGenericCell in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|-------------------------------|---|-------------------|------|-------|
| id | id | string | M | M | - |
| cId | cId | long | M | M | M |
| localCellId | localCellId | long | M | M | M |
| retAntennaFunctionList | retAntennaFunctionList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | O | M | M |
| maximumTransmissionPower | maximumTransmissionPower | short | M | M | M |
| lac | lac | long | M | M | M |
| pichPower | pichPower | float | O | M | O |
| pchPower | pchPower | float | O | M | O |
| fachPower | fachPower | float | O | M | O |
| rac | rac | long | O | M | M |
| sac | sac | long | M | M | M |
| uraList | uraList | GenericNetworkResourcesIRPSystem::AttributeTypes::LongSet | O | M | M |
| AssociatedWith/ utranCell-IubLink | utranCellIubLink | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | - |
| cellMode | cellMode | GenericNRMAAttributeTypes:: CellModeEnumType | M | M | - |
| operationalState | operationalState | StateManagementIRPOptConstDefs::OperationalStateTypeOpt | O | M | - |
| hsFlag | hsFlag | short | O | M | - |
| hsEnable | hsEnable | short | O | M | - |
| numOfHspdschs | numOfHspdschs | short | O | M | - |
| numOfHsscchs | numOfHsscchs | short | O | M | - |
| frameOffset | frameOffset | short | CO | M | - |
| cellIndividualOffset | cellIndividualOffset | short | CO | M | - |
| hcsPrio | hcsPrio | short | CO | M | - |
| maximumAllowedULTxPower | maximumAllowedULTxPower | short | CO | M | - |
| snaInformation | snaInformation | GenericNetworkResourceMAttributeTypes:: snaInformationType | CO | M | - |
| qrxlevMin | qrxlevMin | short | CO | M | - |
| deltaQrxlevmin | deltaQrxlevmin | short | CO | M | - |
| qhcs | qhcs | short | CO | M | - |
| penaltyTime | penaltyTime | short | CO | M | - |
| referenceTimeDifferenceToCell | referenceTimeDifferenceToCell | short | CO | M | - |
| readSFNIndicator | readSFNIndicator | boolean | CO | M | - |
| restrictionStateIndicator | restrictionStateIndicator | GenericNetworkResourceMAttributeTypes:: restrictionStateEnumType | CO | M | - |
| dpcModeChangeSupportIndicator | dpcModeChangeSupportIndicator | GenericNetworkResourceMAttributeTypes:: dpcModeChangeSupportEnumType | CO | M | - |
| tmaFunctionList | tmaFunctionList | GenericNetworkResourceIRPSystem::AttributeTypes::MOReferenceSet | O | M | - |

NOTE 1: For all support qualifiers with the value 'O', see attribute constraints in TS 32.642 [4].

NOTE 2: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4].

5.2.3 IOC NodeBFunction

Mapping from NRM IOC NodeBFunction attributes and associations to SS equivalent MOC NodeBFunction attributes

| NRM Attributes of IOC NodeBFunction in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|----------------------|---|-------------------|------|-------|
| nodeBFunctionId | nodeBFunctionId | string | M | M | - |
| ConnectedTo/ nodeBFunction-IubLink | nodeBFunctionIubLink | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | - |

5.2.4 IOC IubLink

Mapping from NRM IOC IubLink attributes and associations to SS equivalent MOC IubLink attributes

| NRM Attributes of IOC IubLink in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|-----------------------------------|--|-------------------|------|-------|
| iubLinkId | iubLinkId | string | M | M | - |
| AssociatedWith/ iubLink-UtranCell | iubLinkUtranCell | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | M | M | M |
| ConnectedTo/ iubLink-NodeBFunction | iubLinkNodeBFunction | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | - |
| AssociatedWith1/ iubLink-ATMChannelTerminationPoint | iubLinkATMChannelTerminationPoint | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | - |

5.2.6 IOC ExternalUtranGenericCell

Mapping from NRM IOC ExternalUtranGenericCell attributes and associations to SS equivalent MOC ExternalUtranGenericCell attributes

| NRM Attributes of IOC ExternalUtranGenericCell in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|-------------------------------|---|-------------------|------|-------|
| id | id | string | M | M | - |
| cId | cId | long | M | M | M |
| mcc | mcc | short | M | M | M |
| mnc | mnc | short | M | M | M |
| rncId | rncId | long | M | M | M |
| cellMode | cellMode | GenericNRMAAttributeTypes::CellModeEnumType | M | M | - |
| lac | lac | long | M | M | M |
| rac | rac | long | O | M | M |
| controllingRnc | controllingRnc | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | O | M | - |
| hsFlag | hsFlag | short | O | M | - |
| frameOffset | frameOffset | short | CO | M | - |
| cellIndividualOffset | cellIndividualOffset | short | CO | M | - |
| hcsPrio | hcsPrio | short | CO | M | - |
| maximumAllowedULTxPower | maximumAllowedULTxPower | short | CO | M | - |
| qrxlevMin | qrxlevMin | short | CO | M | - |
| deltaQrxlevmin | deltaQrxlevmin | short | CO | M | - |
| qhcs | qhcs | short | CO | M | - |
| penaltyTime | penaltyTime | short | CO | M | - |
| referenceTimeDifferenceToCell | referenceTimeDifferenceToCell | short | CO | M | - |
| readSFNIndicator | readSFNIndicator | boolean | CO | M | - |
| restrictionStateIndicator | restrictionStateIndicator | GenericNetworkResourceMAttributeTypes::restrictionStateEnumType | CO | M | - |
| dpcModeChangeSupportIndicator | dpcModeChangeSupportIndicator | GenericNetworkResourceMAttributeTypes::dpcModeChangeSupportEnumType | CO | M | - |
| snaInformation | snaInformation | GenericNetworkResourceMAttributeTypes::snaInformationType | CO | M | - |
| NOTE 1: For all support qualifiers with the value 'O', see attribute constraints in TS 32.642 [4]. | | | | | |
| NOTE 2: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4]. | | | | | |

5.2.7 IOC AntennaFunction

| NRM Attributes of IOC antennaFunction in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|------------------|--|-------------------|------|-------|
| antennaFunctionId | antennaId | string | M | M | - |
| retUtranCellList | retUtranCellList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | O | M | M |
| retTiltValue | retTiltValue | short | O | M | M |
| bearing | bearing | short | O | M | M |
| maxTiltValue | maxTiltValue | short | O | M | M |
| minTiltValue | minTiltValue | short | O | M | M |
| mechanicalOffset | mechanicalOffset | short | O | M | M |
| retGroupName | retGroupName | string | O | M | M |
| height | height | short | O | M | M |
| baseElevation | baseElevation | short | O | M | O |
| latitude | latitude | long | O | M | O |
| longitude | longitude | long | O | M | O |
| maxAzimuthValue | maxAzimuthValue | short | O | M | M |
| minAzimuthValue | minAzimuthValue | short | O | M | M |
| horizBeamwidth | horizBeamwidth | short | O | M | M |
| vertBeamwidth | vertBeamwidth | short | O | M | M |
| patternLabel | patternLabel | string | O | M | O |

NOTE: For all support qualifiers with the value 'O', see attribute constraints in TS 32.642 [4].

5.2.8 IOC ExternalRncFunction

Mapping from NRM IOC ExternalRncFunction attributes and associations to SS equivalent MOC ExternalRncFunction attributes

| NRM Attributes of IOC ExternalRncFunction in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|-----------------------|--|-------------------|------|-------|
| externalRncFunctionId | externalRncFunctionId | string | M | M | - |
| mcc | mcc | long | M | M | M |
| mnc | mnc | long | M | M | M |
| rncId | rncId | long | M | M | M |
| controlledCellList | controlledCellList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | O | M | - |

NOTE: For all support qualifiers with the value 'O', see attribute constraints in TS 32.642 [4].

5.2.9 UtranCellFDD

Mapping from NRM IOC UtranCellFDD attributes and associations to SS equivalent MOC UtranCellFDD attributes

| NRM Attributes of IOC UtranCellFDD in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|---------------------------------|---|-------------------|------|-------|
| uarfcnUl | uarfcnUl | short | O | M | M |
| uarfcnDl | uarfcnDl | short | O | M | M |
| primaryScramblingCode | primaryScramblingCode | short | O | M | M |
| primaryCpichPower | primaryCpichPower | float | O | M | M |
| primarySchPower | primarySchPower | float | O | M | M |
| secondarySchPower | secondarySchPower | float | O | M | M |
| bchPower | bchPower | float | O | M | M |
| aichPower | aichPower | float | O | M | - |
| qqualMin | qqualMin | float | CO | M | - |
| cellCapabilityContainerFDD | cellCapabilityContainerFDD | FDDNetworkResourceMAttributeTypes:: CellCapabilityContainerFDDType | CO | M | - |
| txDiversityIndicator | txDiversityIndicator | FDDNetworkResourceMAttributeTypes:: txDiversityIndicatorEnumType | CO | M | - |
| temporaryOffset1 | temporaryOffset1 | short | CO | M | - |
| temporaryOffset2 | temporaryOffset2 | short | CO | M | - |
| sttdSupportIndicator | sttdSupportIndicator | FDDNetworkResourceMAttributeTypes:: sttdSupportEnumType | CO | M | - |
| closedLoopMode1SupportIndicator | closedLoopMode1SupportIndicator | FDDNetworkResourceMAttributeTypes:: closedLoopMode1EnumType | CO | M | - |
| NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4]. | | | | | |

5.2.10 UtranCellTDD

Mapping from NRM IOC UtranCellTDD attributes and associations to SS equivalent MOC UtranCellTDD attributes

| NRM Attributes of IOC UtranCellTDD in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|----------------------------|---|-------------------|------|-------|
| uarfcn | uarfcn | short | O | M | M |
| cellParameterId | cellParameterId | long | O | M | M |
| primaryCcpchPower | primaryCcpchPower | float | O | M | M |
| cellCapabilityContainerTDD | cellCapabilityContainerTDD | TDDNetworkResourceMAttributeTypes:: CellCapabilityContainerTDDType | CO | M | - |
| sctdIndicator | sctdIndicator | TDDNetworkResourceMAttributeTypes:: sctdSupportEnumType | CO | M | - |
| dpchConstantValue | dpchConstantValue | long | CO | M | - |
| NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4]. | | | | | |

5.2.11 UtranCellTDDLcr

Mapping from NRM IOC UtranCellTDDLcr attributes and associations to SS equivalent MOC UtranCellTDDLcr attributes

| NRM Attributes of IOC UtranCellTDDLcr in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|-----------------|--|-------------------|------|-------|
| uarfcnLCRList | uarfcnLCRList | TDDNRMAAttributeTypes:: UarfcnLCRListConfigStructType | O | M | M |
| dwPchPower | dwPchPower | float | O | M | M |
| fpachPower | fpachPower | float | O | M | O |
| tstdIndicator | tstdIndicator | TDDNRMAAttributeTypes:: tstdIndicatorEnumType | CO | M | - |
| timeSlotLCRList | timeSlotLCRList | TDDNRMAAttributeTypes:: TimeSlotListConfigStructType | O | M | M |

NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4].

5.2.12 UtranCellTDDHcr

Mapping from NRM IOC UtranCellTDDHcr attributes and associations to SS equivalent MOC UtranCellTDDHcr attributes

| NRM Attributes of IOC UtranCellTDDHcr in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|------------------|---|-------------------|------|-------|
| schPower | schPower | float | O | M | M |
| temporaryOffset1 | temporaryOffset1 | short | CO | M | - |
| syncCase | syncCase | short | CO | M | - |
| timeSlotForSch | timeSlotForSch | short | CO | M | - |
| schTimeSlot | schTimeSlot | short | CO | M | - |
| timeSlotHCRList | timeSlotHCRList | TDDNRMAAttributeTypes:: TimeSlotListConfigStructType | O | M | M |

NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4].

5.2.13 ExternalUtranCellFDD

Mapping from NRM IOC ExternalUtranCellFDD attributes and associations to SS equivalent MOC ExternalUtranCellFDD attributes

| NRM Attributes of IOC UtranCellTDDHcr in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|----------------------------|---|-------------------|------|-------|
| uarfcnUl | uarfcnUl | short | O | M | M |
| uarfcnDl | uarfcnDl | short | O | M | M |
| primaryScramblingCode | primaryScramblingCode | short | O | M | M |
| primaryCpichPower | primaryCpichPower | float | O | M | M |
| qqualMin | qqualMin | long | CO | M | - |
| cellCapabilityContainerFDD | cellCapabilityContainerFDD | FDDNetworkResourceMAttributeTypes:: CellCapabilityContainerFDDType | CO | M | - |
| txDiversityIndicator | txDiversityIndicator | FDDNetworkResourceMAttributeTypes:: txDiversityIndicatorEnumType | CO | | - |
| temporaryOffset1 | temporaryOffset1 | short | CO | M | - |
| temporaryOffset2 | temporaryOffset2 | short | CO | M | - |
| sttdSupportIndicator | sttdSupportIndicator | FDDNetworkResourceMAttributeTypes:: sttdSupportEnumType | CO | M | - |

NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4].

5.2.14 ExternalUtranCellTDD

Mapping from NRM IOC ExternalUtranCellTDD attributes and associations to SS equivalent MOC ExternalUtranCellTDD attributes

| NRM Attributes of IOC UtranCellTDDHcr in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|----------------------------|---|-------------------|------|-------|
| uarfcn | uarfcn | short | O | M | M |
| cellParameterId | cellParameterId | long | O | M | - |
| primaryCcpchPower | primaryCcpchPower | float | O | M | - |
| cellCapabilityContainerTDD | cellCapabilityContainerTDD | TDDNetworkResourceMAttributeTypes:: CellCapabilityContainerFDDType | CO | M | - |
| sctdIndicator | sctdIndicator | TDDNetworkResourceMAttributeTypes:: sctdSupportEnumType | CO | M | - |
| dpchConstantValue | dpchConstantValue | long | CO | M | - |

NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4].

5.2.15 ExternalUtranCellTDDHcr

Mapping from NRM IOC ExternalUtranCellTDDHcr attributes and associations to SS equivalent MOC ExternalUtranCellTDDHcr attributes

| NRM Attributes of IOC UtranCellTDDLcr in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|------------------|---|-------------------|------|-------|
| temporaryOffset1 | temporaryOffset1 | short | CO | M | - |
| syncCase | syncCase | short | CO | M | - |
| timeSlotForSch | timeSlotForSch | short | CO | M | - |
| schTimeSlot | schTimeSlot | short | CO | M | - |
| timeSlotHCRLList | timeSlotHCRLList | TDDNRMAAttributeTypes:: TimeSlotListConfigStructType | O | M | - |

NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4].

5.2.16 ExternalUtranCellTDDLcr

Mapping from NRM IOC ExternalUtranCellTDDLcr attributes and associations to SS equivalent MOC ExternalUtranCellTDDLcr attributes

| NRM Attributes of IOC UtranCellTDDLcr in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|------------------|---|-------------------|------|-------|
| tstdIndicator | tstdIndicator | TDDNRMAAttributeTypes:: tstdIndicatorEnumType | CO | M | - |
| timeSlotLCRLList | timeSlotLCRLList | TDDNRMAAttributeTypes:: TimeSlotListConfigStructType | O | M | - |

NOTE: For all support qualifiers with the value 'CO' see attribute constraints in TS 32.642 [4].

5.2.17 IOC TmaFunction

Mapping from NRM IOC TmaFunction attributes and associations to SS equivalent MOC TmaFunction attributes

| NRM Attributes of IOC tmaFunction in TS 32.642 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|--------------------------------------|---|-------------------|------|-------|
| tmaFunctionId | tmaFunctionId | string | M | M | - |
| tmaSubunitNumber | tmaSubunitNumber | unsigned short | M | M | M |
| tmaStateFlag | tmaStateFlag | unsigned short | M | M | O |
| tmaFunctionFlag | tmaFunctionFlag | unsigned short | M | M | M |
| tmaMinGain | tmaMinGain | unsigned short | M | M | - |
| tmaMaxGain | tmaMaxGain | unsigned short | M | M | - |
| tmaResolution | tmaResolution | unsigned short | M | M | - |
| tmaGainFigure | tmaGainFigure | unsigned short | M | M | O |
| tmaNumberOfSubunits | tmaNumberOfSubunits | unsigned short | M | M | - |
| tmaNumberOfNonLinearGainValues | tmaNumberOfNonLinearGainValues | unsigned short | M | M | - |
| tmaNonLinearGainValue | tmaNonLinearGainValue | sequence of unsigned short | M | M | M |
| tmaUtranCellList | tmaUtranCellList | GenericNetworkResourcesIRPSSystem::AttributeTypes::MOReferenceSet | M | M | M |
| tmaAdditionalDataFieldNumber | tmaAdditionalDataFieldNumber | unsigned short | CO | M | CO |
| tmaAntennaModelNumber | tmaAntennaModelNumber | string | CO | M | CO |
| tmaAntennaSerialNumber | tmaAntennaSerialNumber | string | CO | M | CO |
| tmaAntennaOperatingBands | tmaAntennaOperatingBands | unsigned short | CO | M | CO |
| tmaBeamwidthForEachOpBandInBandOrder | tmaBeamwidthForEachOpBandInBandOrder | sequence of unsigned short | CO | M | CO |
| tmaGainForEachOpBandInBandOrder | tmaGainForEachOpBandInBandOrder | sequence of unsigned short | CO | M | CO |
| tmaInstallationDate | tmaInstallationDate | string | CO | M | CO |
| tmaInstallersId | tmaInstallersId | string | CO | M | CO |
| tmaBaseStationId | tmaBaseStationId | string | CO | M | CO |
| tmaSectorId | tmaSectorId | string | CO | M | CO |
| tmaAntennaBearing | tmaAntennaBearing | unsigned short | CO | M | CO |
| tmaInstalledMechanicalTilt | tmaInstalledMechanicalTilt | short | CO | M | CO |
| tmaSubunitType | tmaSubunitType | unsigned short | CO | M | CO |
| tmaSubunitRxFrequencyBand | tmaSubunitRxFrequencyBand | sequence of unsigned short | CO | M | CO |
| tmaSubunitTxFrequencyBand | tmaSubunitTxFrequencyBand | sequence of unsigned short | CO | M | CO |
| tmaMaxSupportedGain | tmaMaxSupportedGain | unsigned short | CO | M | CO |
| tmaMinSupportedGain | tmaMinSupportedGain | unsigned short | CO | M | CO |
| tmaGainResolution | tmaGainResolution | unsigned short | CO | M | CO |

6 Rules for management information model extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation while still remaining compliant with 3GPP SA5's specifications.

6.1 Allowed extensions

Vendor-specific IOCs may be supported. The vendor-specific IOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific IOCs and vendor-specific attributes. New IOCs shall be distinguishable from 3GPP SA5 IOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific IOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM IOCs may be subclassed. Subclassed IOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed IOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM IOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, `ManagementNode` (or its subclasses) shall be contained under `SubNetwork` (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the IOCs be represented in IDL. 3GPP SA5's NRM IOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study.

6.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not IOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

Annex A (normative): CORBA IDL, NRM definitions

A.1 IDL specification (file name "UtranNetworkResourcesNRMDefs.idl")

```
//File:UtranNetworkResourcesNRMDefs.idl
#ifndef _UTRANNETWORKRESOURCESNRMDEFS_IDL_
#define _UTRANNETWORKRESOURCESNRMDEFS_IDL_
#include "GenericNetworkResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module UtranNetworkResourcesNRMDefs
{

    /**
     * Definitions for MO class RncFunction
     */
    interface RncFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "RncFunction";
        // Attribute Names
        //
        const string rncFunctionId = "rncFunctionId";
        const string mcc= "mcc";
        const string mnc= "mnc";
        const string rncId= "rncId";
    };
    /**
     * Definitions for MO class UtranGenericCell
     */
    interface UtranGenericCell : GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "UtranGenericCell";
        // Attribute Names
        //
        const string id = "id";
        const string utranCellIubLink = "utranCellIubLink";
        const string cId= "cId";
        const string localCellId= "localCellId";

        const string maximumTransmissionPower= "maximumTransmissionPower";
        const string retAntennaFunctionList= "retAntennaFunctionList";
        const string primarySchPower= "primarySchPower";
        const string secondarySchPower= "secondarySchPower";
        const string bchPower= "bchPower";

        const string fpachPower= "fpachPower";
        const string pichPower= "pichPower";
        const string pchPower= "pchPower";
        const string fachPower= "fachPower";
        const string cellMode = "cellMode";

        const string lac= "lac";
        const string rac= "rac";
        const string sac= "sac";
        const string uraList= "uraList";
        const string operationalState = "operationalState";
        const string tmaFunctionList = "tmaFunctionList";
        const string hsFlag = "hsFlag";
        const string hsEnable = "hsEnable";
        const string numOfHspdschs = "numOfHspdschs";
        const string numOfHsscchs = "numOfHsscchs";
        const string snaInformation = "snaInformation";
        const string frameOffset = "frameOffset";
    };
};

```

```

const string cellIndividualOffset = "cellIndividualOffset";
const string hcsPrio = "hcsPrio";
const string maximumAllowedULTxPower = "maximumAllowedULTxPower";
const string qrxlevMin = "qrxlevMin";
const string deltaQrxlevmin = "deltaQrxlevmin";
const string qhcs = "qhcs";
const string penaltyTime = "penaltyTime";
const string referenceTimeDifferenceToCell = "referenceTimeDifferenceToCell";
const string readSFNIndicator = "readSFNIndicator";
const string restrictionStateIndicator = "restrictionStateIndicator";
const string dpcModeChangeSupportIndicator = "dpcModeChangeSupportIndicator";
};

interface AntennaFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS= "AntennaFunction";
    // Attribute Names
    //
    const string antennaId= "antennaFunctionId";
    const string retUtranCellList= "retUtranCellList";
    const string retTiltValue= "retTiltValue";
    const string bearing= "bearing";
    const string maxTiltValue= "maxTiltValue";
    const string minTiltValue= "minTiltValue";
    const string mechanicalOffset= "mechanicalOffset";
    const string retGroupName= "retGroupName";
    const string height= "height";
    const string baseElevation= "baseElevation";
    const string latitude= "latitude";
    const string longitude= "longitude";
    const string maxAzimuthValue= "maxAzimuthValue";
    const string minAzimuthValue= "minAzimuthValue";
    const string horizBeamwidth= "horizBeamwidth";
    const string vertBeamwidth= "vertBeamwidth";
    const string patternLabel= "patternLabel";
};

/**
 * Definitions for MO class TmaFunction
 */
interface TmaFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS= "TmaFunction";
    // Attribute Names
    //
    const string tmaFunctionId= "tmaFunctionId";
    const string tmaSubunitNumber= "tmaSubunitNumber";
    const string tmaStateFlag= "tmaStateFlag";
    const string tmaFunctionFlag= "tmaFunctionFlag";
    const string tmaMinGain= "tmaMinGain";
    const string tmaMaxGain= "tmaMaxGain";
    const string tmaResolution= "tmaResolution";
    const string tmaGainFigure= "tmaGainFigure";
    const string tmaNumberOfSubunits= "tmaNumberOfSubunits";
    const string tmaNumberOfNonLinearGainValues= "tmaNumberOfNonLinearGainValues";
    const string tmaNonLinearGainValue= "tmaNonLinearGainValue";
    const string tmaUtranCellList= "tmaUtranCellList";
    const string tmaAdditionalDataFieldNumber= "tmaAdditionalDataFieldNumber";
    const string tmaAntennaModelNumber= "tmaAntennaModelNumber";
    const string tmaAntennaSerialNumber= "tmaAntennaSerialNumber";
    const string tmaAntennaOperatingBands= "tmaAntennaOperatingBands";
    const string tmaBeamwidthForEachOpBandInBandOrder= "tmaBeamwidthForEachOpBandInBandOrder";
    const string tmaGainForEachOpBandInBandOrder= "tmaGainForEachOpBandInBandOrder";
    const string tmaInstallationDate= "tmaInstallationDate";
    const string tmaInstallersId= "tmaInstallersId";
    const string tmaBaseStationId= "tmaBaseStationId";
    const string tmaSectorId= "tmaSectorId";
    const string tmaAntennaBearing= "tmaAntennaBearing";
    const string tmaInstalledMechanicalTilt= "tmaInstalledMechanicalTilt";
    const string tmaSubunitType= "tmaSubunitType";
    const string tmaSubunitRxFrequencyBand= "tmaSubunitRxFrequencyBand";
    const string tmaSubunitTxFrequencyBand= "tmaSubunitTxFrequencyBand";
    const string tmaMaxSupportedGain= "tmaMaxSupportedGain";
    const string tmaMinSupportedGain= "tmaMinSupportedGain";
    const string tmaGainResolution= "tmaGainResolution";
};

```

```

/**
 * Definitions for MO class NodeBFunction
 */
interface NodeBFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "NodeBFunction";
    // Attribute Names
    //
    const string nodeBFunctionId = "nodeBFunctionId";
    const string nodeBFunctionIubLink = "nodeBFunctionIubLink";
};

/**
 * Definitions for MO class IubLink
 */
interface IubLink : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "IubLink";
    // Attribute Names
    //
    const string iubLinkId = "iubLinkId";
    const string iubLinkNodeBFunction = "iubLinkNodeBFunction";
    const string iubLinkUtranCell = "iubLinkUtranCell";
    const string iubLinkATMChannelTerminationPoint = "iubLinkATMChannelTerminationPoint";
};

};

/**
 * Definitions for MO class UtranRelation
 */
interface UtranRelation : GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "UtranRelation";
    // Attribute Names
    //
    const string utranRelationId = "utranRelationId";
    const string adjacentCell = "adjacentCell";
};

};

/**
 * Definitions for MO class ExternalUtranGenericCell
 */
interface ExternalUtranGenericCell : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "ExternalUtranGenericCell";
    // Attribute Names
    //
    const string id = "id";
    const string cId = "cId";
    const string mcc = "mcc";
    const string mnc = "mnc";
    const string rncId = "rncId";

    const string cellMode = "cellMode";
    const string uarfcn = "uarfcn";
    const string cellParameterId = "cellParameterId";

    const string lac = "lac";
    const string rac = "rac";
    const string controllingRnc = "controllingRnc";
    const string hsFlag = "hsFlag";
    const string frameOffset = "frameOffset";
    const string cellIndividualOffset = "cellIndividualOffset";
    const string hcsPrio = "hcsPrio";
    const string maximumAllowedULTxPower = "maximumAllowedULTxPower";
    const string qrxlevMin = "qrxlevMin";
    const string deltaQrxlevmin = "deltaQrxlevmin";
    const string qhcs = "qhcs";
    const string penaltyTime = "penaltyTime";
    const string referenceTimeDifferenceToCell = "referenceTimeDifferenceToCell";
    const string readSFNIndicator = "readSFNIndicator";
    const string restrictionStateIndicator = "restrictionStateIndicator";
    const string dpcModeChangeSupportIndicator = "dpcModeChangeSupportIndicator";
};

/**
 * Definitions for MO class ExternalRncFunction
 */

```

```

interface ExternalRncFunction :
  GenericNetworkResourcesNRMDefs::ManagedFunction
{
  const string CLASS = "ExternalRncFunction";
  // Attribute Names
  //
  const string externalRncFunctionId = "externalRncFunctionId";
  const string mcc = "mcc";
  const string mnc = "mnc";
  const string rncId = "rncId";
  const string controlledCellList = "controlledCellList";
};

/**
 * Definitions for MO class UtranCellFDD
 */
interface UtranCellFDD : UtranGenericCell
{
  const string CLASS = "UtranCellFDD";
  // Attribute Names
  //
  const string uarfcnUl = "uarfcnUl";
  const string uarfcnDl = "uarfcnDl";
  const string primaryScramblingCode = "primaryScramblingCode";
  const string primaryCpichPower = "primaryCpichPower";
  const string primarySchPower = "primarySchPower";
  const string secondarySchPower = "secondarySchPower";
  const string bchPower = "bchPower";
  const string aichPower = "aichPower";
  const string qqualMin = "qqualMin";
  const string cellCapabilityContainerFDD = "cellCapabilityContainerFDD";
  const string txDiversityIndicator = "txDiversityIndicator";
  const string temporaryOffset1 = "temporaryOffset1";
  const string temporaryOffset2 = "temporaryOffset2";
  const string sttdSupportIndicator = "sttdSupportIndicator";
  const string closedLoopModelSupportIndicator = "closedLoopModelSupportIndicator";
};

/**
 * Definitions for MO class UtranCellTDD
 */
interface UtranCellTDD : UtranGenericCell
{
  const string CLASS = "UtranCellTDD";
  // Attribute Names
  //
  const string uarfcn = "uarfcn";
  const string cellParameterId = "cellParameterId";
  const string primaryCpichPower = "primaryCpichPower";
  const string cellCapabilityContainerTDD = "cellCapabilityContainerTDD";
  const string sctdIndicator = "sctdIndicator";
  const string dpchConstantValue = "dpchConstantValue";
};

/**
 * Definitions for MO class UtranCellTDDLcr
 */
interface UtranCellTDDLcr : UtranCellTDD
{
  const string CLASS = "UtranCellTDDLcr";
  // Attribute Names
  //
  const string uarfcnLCRList = "uarfcnLCRList";
  const string fpachPower = "fpachPower";
  const string dwPchPower = "dwPchPower";
  const string tstdIndicator = "tstdIndicator";
  const string timeSlotLCRList = "timeSlotLCRList";
};

/**
 * Definitions for MO class UtranCellTDDHcr
 */
interface UtranCellTDDHcr : UtranCellTDD
{
  const string CLASS = "UtranCellTDDHcr";
  // Attribute Names
  //
  const string schPower = "schPower";
  const string temporaryOffset1 = "temporaryOffset1";
};

```

```

    const string syncCase = "syncCase";
    const string timeSlotForSch = "timeSlotForSch";
    const string schTimeSlot = "schTimeSlot";
    const string timeSlotHCRLList = "timeSlotHCRLList";
};
/**
 * Definitions for MO class ExternalUtranCellFDD
 */
interface ExternalUtranCellFDD : ExternalUtranGenericCell
{
    const string CLASS = "ExternalUtranCellFDD";
    // Attribute Names
    //
    const string uarfcnUl = "uarfcnUl";
    const string uarfcnDl = "uarfcnDl";
    const string primaryScramblingCode = "primaryScramblingCode";
    const string primaryCpichPower = "primaryCpichPower";
    const string qqualMin = "qqualMin";
    const string cellCapabilityContainerFDD = "cellCapabilityContainerFDD";
    const string txDiversityIndicator = "txDiversityIndicator";
    const string temporaryOffset1 = "temporaryOffset1";
    const string temporaryOffset2 = "temporaryOffset2";
    const string sttdSupportIndicator = "sttdSupportIndicator";
    const string closedLoopModelSupportIndicator = "closedLoopModelSupportIndicator";
};
/**
 * Definitions for MO class ExternalUtranCellTDD
 */
interface ExternalUtranCellTDD : ExternalUtranGenericCell
{
    const string CLASS = "ExternalUtranCellTDD";
    // Attribute Names
    //
    const string uarfcn = "uarfcn";
    const string cellParameterId = "cellParameterId";
    const string primaryCpichPower = "primaryCpichPower";
    const string cellCapabilityContainerTDD = "cellCapabilityContainerTDD";
    const string sctdIndicator = "sctdIndicator";
    const string dpchConstantValue = "dpchConstantValue";
};
/**
 * Definitions for MO class ExternalUtranCellTDDHcr
 */
interface ExternalUtranCellTDDHcr : ExternalUtranCellTDD
{
    const string CLASS = "ExternalUtranCellTDDHcr";
    // Attribute Names
    //
    const string temporaryOffset1 = "temporaryOffset1";
    const string syncCase = "syncCase";
    const string timeSlotForSch = "timeSlotForSch";
    const string schTimeSlot = "schTimeSlot";
    const string timeSlotHCRLList = "timeSlotHCRLList";
};
/**
 * Definitions for MO class ExternalUtranCellTDDLcr
 */
interface ExternalUtranCellTDDLcr : ExternalUtranCellTDD
{
    const string CLASS = "ExternalUtranCellTDDLcr";
    // Attribute Names
    //
    const string tstdIndicator = "tstdIndicator";
    const string timeSlotLCRLList = "timeSlotLCRLList";
};

/**
 * This module adds datatype definitions for both FDD and TDD mode
 * attributes used in the NRM which are not the basic datatypes
 * already defined in CORBA.
 */
module GenericNRMAAttributeTypes
{
    enum CellModeEnumType
    {
        FDDMode,
        TDDMode_1_28Mcps,
    }
};

```

```

        TDDMode_3_84Mcps
    };
    enum RestrictionStateEnumType
    {
        cellReservedForOperatorUse,
        cellAccessible
    };
    enum DpcModeChangeEnumType
    {
        dpcModeChange_supported,
        dpcModeChange_not_supported
    };
    typedef long SNAC;
    struct snaInformationType
    {
        long mcc;
        long mnc;
        sequence<SNAC> snaList;
    };
};

/**
 * This module adds datatype definitions for FDD mode attributes
 * used in the NRM which are not the basic datatypes already defined
 * in CORBA.
 */
module FDDNRMAAttributeTypes
{
    enum SttdSupportEnumType
    {
        active,
        inactive
    };

    enum txDiversityIndicatorEnumType
    {
        none,
        primaryCpichBroadcastFrom2Antennas,
        sttdAppliedToPrimaryCCPCH,
        tstdAppliedToPrimarySchAndSecondarySch
    };
    enum ClosedLoopModelEnumType
    {
        closedLoopModel_supported,
        closedLoopModel_not_supported
    };

    typedef octet CellCapabilityContainerFDDBit;
    //CellCapabilityContainerFDDBits:
    const unsigned long Flexible_Hard_Split_Support_Indicator = 0;
    const unsigned long Delayed_Activation_Support_Indicator = 1;
    const unsigned long HS_DSCH_Support_Indicator = 2;
    const unsigned long DSCH_Support_Indicator = 3;
    const unsigned long F_DPCH_Support_Indicator = 4;
    const unsigned long E_DCH_Support_Indicator = 5;
    const unsigned long E_DCH_TTI2ms_Support_Indicator = 6;
    const unsigned long E_DCH_2sf2and2sf4_and_all_inferior_SF_Support_Indicator = 7;
    const unsigned long E_DCH_2sf2_and_all_inferior_SF_Support_Indicator = 8;
    const unsigned long E_DCH_2sf4_and_all_inferior_SF_Support_Indicator = 9;
    const unsigned long E_DCH_sf4_and_all_inferior_SF_Support_Indicator = 10;
    const unsigned long E_DCH_sf8_and_all_inferior_SF_Support_Indicator = 11;
    const unsigned long E_DCH_HARQ_IR_Combining_Support_Indicator = 12;
    const unsigned long E_DCH_HARQ_Chase_Combining_Support_Indicator = 13;
    typedef sequence <CellCapabilityContainerFDDBit> CellCapabilityContainerFDDType;

};

/**
 * This module adds datatype definitions for TDD mode attributes
 * used in the NRM which are not the basic datatypes already defined
 * in CORBA.
 */
module TDDNRMAAttributeTypes
{
    enum ActivityStatusType
    {
        active,
        inactive
    };
    typedef ActivityStatusType TstdIndicatorEnumType;

```



```
typedef ActivityStatusType SctdSupportEnumType;
typedef ActivityStatusType TimeSlotStatusType;

typedef octet CellCapabilityContainerTDDBit;
const unsigned long Delayed_Activation_Support_Indicator = 0;
const unsigned long HS_DSCH_Support_Indicator = 1;
const unsigned long DSCH_Support_Indicator = 2;
typedef sequence <CellCapabilityContainerTDDBit> CellCapabilityContainerTDDType;

enum TimeSlotDirectionType
{
    UL,
    DL
};

struct TimeSlotConfigStructType
{
    short timeSlotId;
    TimeSlotDirectionType timeSlotDirection;
    TimeSlotStatusType timeSlotStatus;
};
typedef sequence<TimeSlotConfigStructType> TimeSlotListConfigStructType;

struct UarfcnLCRConfigStructType
{
    short uarfcn;
    TimeSlotListConfigStructType timeSlotLCRList;
};
typedef sequence<UarfcnLCRConfigStructType> UarfcnLCRListConfigStructType;
};
#endif // _UTRANNETWORKRESOURCESNRMDEFS_IDL_
```

Annex B (informative): Change history

| Change history | | | | | | | | |
|----------------|-------|-----------|------|----|--|-----|-------|-------|
| Date | TSG # | TSG Doc. | CR | R | Subject/Comment | Cat | Old | New |
| Jun 2006 | SP-32 | SP-060259 | 0026 | -- | Add configuration parameters for radio channel power - Align with 32.642 | B | 6.6.0 | 7.0.0 |
| Sep 2006 | SP-33 | SP-060623 | 0028 | -- | Correct the IOC AntennaFunction data types of latitude and longitude from "short" to "long" to avoid overflow | A | 7.0.0 | 7.1.0 |
| Mar 2007 | -- | -- | -- | -- | Delete reference to the 32.644 CMIP SS. Reason: SA#35 endorsed the SA5 decision to not propagate the CMIP Solution Sets to Rel-7 (TS 32.3x4, TS 32.4x4, TS 32.6x4) | -- | 7.1.0 | 7.1.1 |
| Jun 2007 | SP-36 | SP-070282 | 0029 | -- | Add control and configuration of Tower Mounted Amplifiers - Align with RAN3 25.466 | B | 7.1.1 | 7.2.0 |
| Jun 2007 | SP-36 | SP-070276 | 0030 | -- | Add missing monitoring of cell neighbourhood relations over ltf-p2p - Align with 32.642 | F | 7.1.1 | 7.2.0 |
| Dec 2007 | SP-38 | SP-070730 | 0032 | 1 | R7 CR 32.643-720 Correct CORBA Solution Set Tables | A | 7.2.0 | 7.3.0 |
| Dec 2007 | SP-38 | SP-070733 | 0033 | 1 | Add write support for TMA Additional Data and correct CORBA IDL syntax errors. | F | 7.2.0 | 7.3.0 |
| Mar 2008 | SP-39 | SP-080058 | 0034 | - | Add missing multi-frequency attributes for 1.28Mcps TDD - Align with 32.642 | F | 7.3.0 | 7.4.0 |
| Apr 2008 | -- | -- | -- | -- | Updated the Change history | -- | 7.4.0 | 7.4.1 |
| Jun 2008 | SP-40 | SP-080328 | 0035 | -- | Correction of UTRAN Cell attributes - Align with 32.642 | F | 7.4.1 | 7.5.0 |
| Dec 2008 | SA_42 | -- | -- | -- | Upgrade to Release 8 | -- | 7.5.0 | 8.0.0 |
| Dec 2010 | SA_50 | SP-100831 | 0037 | -- | Correcting the inconsistent support qualifier of userLabel - Align with 32.642 IS | F | 8.0.0 | 8.1.0 |

History

| Document history | | |
|-------------------------|--------------|-------------|
| V8.0.0 | January 2009 | Publication |
| V8.1.0 | January 2011 | Publication |
| | | |
| | | |
| | | |