

# ETSI TS 132 653 V5.0.1 (2002-12)

---

*Technical Specification*

**Digital cellular telecommunications system (Phase 2+);  
Telecommunication management;  
Configuration Management (CM);  
GERAN network resources Integration Reference Point (IRP):  
CORBA solution set  
(3GPP TS 32.653 version 5.0.1 Release 5)**

---



---

Reference

RTS/TSGS-0532653v501

---

Keywords

GSM

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

[editor@etsi.org](mailto:editor@etsi.org)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.  
All rights reserved.

**DECT™**, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON™** and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

All published ETSI deliverables shall include information which directs the reader to the above source of information.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Foreword.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	5
3 Definitions and abbreviations.....	5
3.1 Definitions .....	5
3.2 Abbreviations .....	5
4 Architectural features .....	6
4.1 Notifications .....	6
5 Mapping .....	6
5.1 General mappings.....	6
5.2 GERAN NRM Information Object Class (IOC) mapping.....	6
5.2.1 IOC BssFunction .....	6
5.2.2 IOC BtsSiteMgr .....	6
5.2.3 IOC GsmCell .....	7
5.2.4 IOC GsmRelation .....	7
5.2.5 IOC ExternalGsmCell.....	7
6 Rules for management information model extensions .....	8
6.1 Allowed extensions .....	8
6.2 Extensions not allowed.....	8
<b>Annex A (normative): CORBA IDL, NRM Definitions.....</b>	<b>9</b>
<b>Annex B (informative): Change history .....</b>	<b>11</b>
History .....	12

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G-network as it evolves. CM actions have the objective to control and monitor the actual configuration on the NEs and NRs, and they may be initiated by the operator or functions in the OSs or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service. The CM actions are initiated either as a single action on a Network Element (NE) of the 3G-network or as part of a complex procedure involving actions on many NEs.

The Itf-N interface for Configuration Management is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2]. For CM, a number of IRPs (and the Name Convention) are defined herein, used by this as well as other technical specifications for telecom management produced by 3GPP.

---

# 1 Scope

The purpose of this *GERAN Network Resources IRP: CORBA Solution Set* is to define the mapping of the IRP information model (see 3GPP TS 32.652 [4]) to the protocol specific details necessary for implementation of this IRP in a CORBA/IDL environment.

This Solution Set specification is related to 3GPP TS 32.652 V5.0.X.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "3G Telecom Management principles and high level requirements".
- [2] 3GPP TS 32.102: "3G Telecom Management architecture".
- [3] 3GPP TS 32.600: "Configuration Management (CM); Concept and main requirements".
- [4] 3GPP TS 32.652: "Configuration Management (CM); GERAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] 3GPP TS 32.303: "Configuration Management (CM); Notification Integration Reference Point (IRP); CORBA solution set".
- [6] 3GPP TS 32.111-3: "Fault Management; Part 3: Alarm Integration Reference Point (IRP): CORBA solution set".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For terms and definitions refer to TS 32.101 [1], TS 32.102 [2], TS 32.600 [3] and TS 32.652 [4].

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CORBA	Common Object Request Broker Architecture
DN	Distinguished Name
IS	Information Service
IDL	Interface Definition Language
IOC	Information Object Class
IRP	Integration Reference Point
MO	Managed Object
MOC	Managed Object Class
NRM	Network Resource Model

SS

Solution Set

## 4 Architectural features

The overall architectural feature of GERAN Network Resources IRP is specified in TS 32.652[4]. This clause specifies features that are specific to the CORBA SS.

### 4.1 Notifications

Notifications are sent according to the Notification IRP: CORBA SS (see TS 32.303 [5]).

## 5 Mapping

### 5.1 General mappings

The IS parameter name `managedObjectInstance` is mapped into DN.

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an `MOReference`. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type `MOReferenceSet`, which contains a sequence of MO references.

If a reference attribute is changed, an `AttributeValueChange` notification is emitted.

### 5.2 GERAN NRM Information Object Class (IOC) mapping

#### 5.2.1 IOC BssFunction

**Table 2: Mapping from NRM IOC BssFunction attributes to SS equivalent MOC BssFunction attributes**

NRM Attributes of IOC BssFunction in TS 32.652 [4]	SS Attributes	SS Type	Support Qualifier	Read	Write
<code>bssFunctionId</code>	<code>bssFunctionId</code>	string	M	M	-
<code>userLabel</code>	<code>userLabel</code>	string	M	M	M

#### 5.2.2 IOC BtsSiteMgr

**Table 3: Mapping from NRM IOC BtsSiteMgr attributes to SS equivalent MOC BtsSiteMgr attributes**

NRM Attributes of IOC BtsSiteMgr in TS 32.652 [4]	SS Attributes	SS Type	Support Qualifier	Read	Write
<code>btsSiteMgrId</code>	<code>btsSiteMgrId</code>	string	M	M	-
<code>userLabel</code>	<code>userLabel</code>	string	M	M	M
<code>latitude</code>	<code>latitude</code>	long	O	M	M
<code>longitude</code>	<code>longitude</code>	long	O	M	M

### 5.2.3 IOC GsmCell

**Table 4: Mapping from NRM IOC GsmCell attributes to SS equivalent MOC GsmCell attributes**

NRM Attributes of IOC GsmCell in TS 32.652 [4]	SS Attributes	SS Type	Support Qualifier	Read	Write
gsmCellId	gsmCellId	string	M	M	-
userLabel	userLabel	string	M	M	M
cellIdentity	cellIdentity	long	M	M	M
cellAllocation	cellAllocation	GenericNRIRPSys::AttributesTypes::LongSet	M	M	M
ncc	ncc	long	M	M	M
bcc	bcc	long	M	M	M
lac	lac	long	M	M	M
mcc	mcc	long	M	M	M
mnc	mnc	long	M	M	M
rac	rac	long	O	M	M
racc	racc	long	O	M	M
tsc	tsc	long	M	M	M
rxLevAccessMin	rxLevAccessMin	long	M	M	M
msTxPwrMaxCCH	msTxPwrMaxCCH	long	M	M	M
hoppingSequenceNumber	hoppingSequenceNumber	long	M	M	M
plmnPermitted	plmnPermitted	long	M	M	M

### 5.2.4 IOC GsmRelation

**Table 5: Mapping from NRM IOC GsmRelation attributes to SS equivalent MOC GsmRelation attributes**

NRM Attributes of IOC GsmRelation in TS 32.652 [4]	SS Attributes	SS Type	Support Qualifier	Read	Write
gsmRelationId	gsmRelationId	string	M	M	-
relationType	relationType	string	M	M	M
adjacentCell	adjacentCell	string	M	M	M
bcchFrequency	bcchFrequency	long	O	M	-
ncc	ncc	long	O	M	-
bcc	bcc	long	O	M	-
lac	lac	long	O	M	-

### 5.2.5 IOC ExternalGsmCell

**Table 6: Mapping from NRM IOC ExternalGsmCell attributes to SS equivalent MOC ExternalGsmCell attributes**

NRM Attributes of IOC ExternalGSMCell in TS 32.652 [4]	SS Attributes	SS Type	Support Qualifier	Read	Write
externalGsmCellId	externalGsmCellId	string	M	M	-
userLabel	userLabel	string	M	M	M
cellIdentity	cellIdentity	long	M	M	M
bcchFrequency	bcchFrequency	long	M	M	M
ncc	ncc	long	M	M	M
bcc	bcc	long	M	M	M
lac	lac	long	M	M	M
mcc	mcc	long	M	M	M
mnc	mnc	long	M	M	M
rac	rac	long	O	M	M
racc	racc	long	O	M	M



---

## 6 Rules for management information model extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications.

### 6.1 Allowed extensions

Vendor-specific IOCs may be supported. The vendor-specific IOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific IOCs and vendor-specific attributes. New MOCs shall be distinguishable from 3GPP SA5 IOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific IOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM IOCs may be subclassed. Subclassed IOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed IOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM IOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, ManagementNode (or its subclasses) shall be contained under SubNetwork (or its subclasses). Also, in Rel-4, there may only be 0 or 1 ManagementNode (or its subclasses) contained under SubNetwork (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the MOCs be represented in IDL. 3GPP SA5's NRM IOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study in 3GPP's Releases 5.

### 6.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not IOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

---

## Annex A (normative): CORBA IDL, NRM Definitions

```
#ifndef GeranNetworkResourcesNRMDefs_idl
#define GeranNetworkResourcesNRMDefs_idl

#pragma prefix "3gppsa5.org"

/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module GeranNetworkResourcesNRMDefs
{

    /**
     * Definitions for MO class BssFunction
     */
    interface BssFunction
    {
        const string CLASS = "BssFunction";

        // Attribute Names
        //
        const string bssFunctionId = "bssFunctionId";
        const string userLabel = "userLabel";
    };

    /**
     * Definitions for MO class BtsSiteMgr
     */
    interface BtsSiteMgr
    {
        const string CLASS = "BtsSiteMgr";

        // Attribute Names
        //
        const string btsSiteMgrId = "btsSiteMgrId";
        const string userLabel = "userLabel";
        const string latitude = "latitude";
        const string longitude = "longitude";
    };

    /**
     * Definitions for MO class GsmCell
     */
    interface GsmCell
    {
        const string CLASS = "GsmCell";

        // Attribute Names
        //
        const string gsmCellId = "gsmCellId";
        const string userLabel = "userLabel";
        const string cellIdentity = "cellIdentity";
        const string cellAllocation = "cellAllocation";
        const string ncc = "ncc";
    };
};
```

```
    const string bcc = "bcc";
    const string lac = "lac";
    const string mcc = "mcc";
    const string mnc = "mnc";
    const string rac = "rac";
    const string racc = "racc";
    const string tsc = "tsc";
    const string rxLevAccessMin = "rxLevAccessMin";
    const string msTxPwrMaxCCH = "msTxPwrMaxCCH";
    const string hoppingSequenceNumber = "hoppingSequenceNumber";
    const string plmnPermitted = "plmnPermitted";

};

/**
 * Definitions for MO class GsmRelation
 */
interface GsmRelation
{
    const string CLASS = "GsmRelation";

    // Attribute Names
    //
    const string gsmRelationId = "gsmRelationId";
    const string relationType = "relationType";
    const string adjacentCell = "adjacentCell";
    const string bcchFrequency = "bcchFrequency";
    const string ncc = "ncc";
    const string bcc = "bcc";
    const string lac = "lac";
};

/**
 * Definitions for MO class ExternalGsmCell
 */
interface ExternalGsmCell
{
    const string CLASS = "ExternalGsmCell";

    // Attribute Names
    //
    const string externalGsmCellId = "externalGsmCellId";
    const string userLabel = "userLabel";
    const string cellIdentity = "cellIdentity";
    const string bcchFrequency = "bcchFrequency";
    const string ncc = "ncc";
    const string bcc = "bcc";
    const string lac = "lac";
    const string mcc = "mcc";
    const string mnc = "mnc";
    const string rac = "rac";
    const string racc = "racc";
};

};

#endif
```

---

## Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Dec 2001	S_14	SP-010651	001	--	Addition of MCC and MNC in the object model	4.0.0	4.1.0
Dec 2001	S_14	SP-010646	002	--	Change type "integer" to "long" in the GERAN Network Resources IRP: CORBA SS	4.0.0	4.1.0
Sep 2002	S_17	SP-020497	003	--	Upgrade to Rel-5	4.1.0	5.0.0
Dec 2002	--	--	--	--	Cosmetics	5.0.0	5.0.1

---

## History

<b>Document history</b>		
V5.0.0	September 2002	Publication (Withdrawn)
V5.0.1	December 2002	Publication