

# ETSI TS 132 763 V8.4.0 (2010-10)

---

*Technical Specification*

**Digital cellular telecommunications system (Phase 2+);  
Universal Mobile Telecommunications System (UMTS);  
LTE;  
Telecommunication management;  
Evolved Universal Terrestrial Radio Access Network (E-UTRAN)  
Network Resource Model (NRM)  
Integration Reference Point (IRP):  
Common Object Request Broker Architecture (CORBA) Solution Set (SS)  
(3GPP TS 32.763 version 8.4.0 Release 8)**

---



---

**Reference**

RTS/TSGS-0532763v840

---

**Keywords**

GSM, LTE, UMTS

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup>, **UMTS**<sup>TM</sup>, **TIPHON**<sup>TM</sup>, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE**<sup>TM</sup> is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM**<sup>®</sup> and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Foreword.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	5
3 Definitions, symbols and abbreviations .....	5
3.1 Abbreviations .....	5
4 Architectural Features .....	6
5 Mapping .....	6
5.1 General .....	6
5.2 Information Object Class (IOC) mapping .....	6
5.2.1 IOC ENBFunction .....	6
5.2.2 IOC EUTranGenericCell.....	7
5.2.3 IOC ExternalEUTranGenericCell .....	7
5.2.4. IOC EUTranCellFDD .....	7
5.2.5 IOC ExternalEUTranCellFDD .....	8
5.2.6 IOC EUTranRelation .....	8
5.2.7 IOC Link_ENB_ENB .....	8
5.2.8 IOC Cdma2000Relation .....	8
5.2.9 IOC EP_RP_EPS .....	8
5.2.10 IOC SectorEquipmentFunction.....	9
5.2.11 IOC ExternalENBFunction.....	9
6 Rules for management information model extensions .....	10
<b>Annex A (normative): CORBA IDL, NRM definitions .....</b>	<b>11</b>
<b>Annex B (informative): Change history .....</b>	<b>15</b>
History .....	16

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- |               |                                                                                                                                                    |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| 32.761        | E-UTRAN Network Resource Model (NRM) Integration Reference Point (IRP): Requirements                                                               |
| 32.762        | E-UTRAN Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS)                                                   |
| <b>32.763</b> | <b>E-UTRAN Network Resource Model (NRM) Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)</b> |
| 32.765        | E-UTRAN Network Resource Model (NRM) Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition            |

---

# 1 Scope

The present document is part of an Integration Reference Point (IRP) named E-UTRAN Network Resource Model (NRM) IRP, through which an IRPAgent can communicate configuration management information to one or several IRPManagers concerning E-UTRAN resources. The E-UTRAN NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set(s).

The present document specifies the E-UTRAN Network Resources IRP: CORBA Solution Set, which defines the mapping of the IRP information model (see TS 32.762 [2]) to the protocol specific details necessary for implementation of this IRP in a CORBA/IDL environment.

This Solution Set is related to 3GPP TS 32.762 v8.4.X.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 21.905: 'Vocabulary for 3GPP Specifications'.
- [2] 3GPP TS 32.762: " Telecommunications management; Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS)".
- [3] 3GPP TS 32.643: 'Telecommunication management; Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)'.
- [4] 3GPP TS 32.153: 'Telecommunication management; Integration Reference Point (IRP) technology specific templates, rules and guidelines'.

---

# 3 Definitions, symbols and abbreviations

## 3.1 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

CORBA	Common Object Request Broker Architecture
DN	Distinguished Name
IS	Information Service
IDL	Interface Definition Language (OMG)
IOC	Information Object Class
IRP	Integration Reference Point

MO	Managed Object
MOC	Managed Object Class
NRM	Network Resource Model
OMG	Object Management Group
SS	Solution Set

## 4 Architectural Features

The overall architectural feature of 32.763 is specified in 3GPP TS 32.762 [2]. This clause specifies features that are specific to the CORBA SS.

## 5 Mapping

### 5.1 General

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

### 5.2 Information Object Class (IOC) mapping

#### 5.2.1 IOC ENBFunction

Attribute of IOC ENBFunction in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
x2BlackList	x2BlackList	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet	CM	M	M
x2WhiteList	x2WhiteList	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet	CM	M	M
x2HOBlackList	x2HOBlackList	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet	CM	M	M
x2IpAddressList	x2IpAddressList	genericEUTRANNRMAttributeTypes::ipAddressListType	O	M	-
Note: For all conditional qualifiers, see attribute constraints in 32.762 [2]					

## 5.2.2 IOC EUTRANGenericCell

Attribute of IOC EUTRANGenericCell in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier
id	id	string	M	M
cellIdentity	cellIdentity	long	M	M
cellSize	cellSize	genericEUTRANRRMAAttributeTypes::cellSizeEnumType	M	M
plmnIdList	plmnIdList	genericEUTRANRRMAAttributeTypes::plmnIdListType	M	M
tac	tac	long	M	M
pci	pci	short	M	M
pciList	pciList	genericEUTRANRRMAAttributeTypes::pciListType	CM	M
maximumTransmissionPower	maximumTransmissionPower	short	M	M
referenceSignalPower	referenceSignalPower	short	O	M
pb	pb	short	O	M
partOfSectorPower	partOfSectorPower	short	CM	M
operationalState	operationalState	StateManagementIRPOptConstDefs::OperationalStateTypeOpt	O	M
administrativeState	administrativeState	StateManagementIRPOptConstDefs::AdministrativeStateTypeOpt	O	M
availabilityStatus	availabilityStatus	StateManagementIRPOptConstDefs::AvailabilityStatusTypeOpt	O	M

Note: For all conditional qualifiers, see attribute constraints in 32.762 [2]

## 5.2.3 IOC ExternalEUTRANGenericCell

Attribute of IOC ExternalEUTRANGenericCell in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
pci	pci	short	M	M	M
plmnIdList	plmnIdList	genericEUTRANRRMAAttributeTypes::plmnIdListType	O	M	M
cellIdentity	cellIdentity	long	M	M	M

## 5.2.4 IOC EUTRANCellFDD

Attribute of IOC EUTRANCellFDD in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
earfcnDl	earfcnDl	short	M	M	M
earfcnUl	earfcnUl	short	M	M	M



## 5.2.5 IOC ExternalEUTranCellFDD

Attribute of IOC ExternalEUTranCellFDD in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
earfcnDl	earfcnDl	short	M	M	M
earfcnUl	earfcnUl	short	M	M	M

## 5.2.6 IOC EUTranRelation

Attribute of IOC EUTranRelation in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
tCI	tCI	long	M	M	M
isRemoveAllowed	isRemoveAllowed	boolean	CM	M	M
isHOAllowed	isHOAllowed	boolean	CM	M	M
adjacentCell	adjacentCell	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference	M	M	-

Note: For all conditional qualifiers, see attribute constraints in 32.762 [2]

## 5.2.7 IOC Link\_ENB\_ENB

Attribute of IOC Link_ENB_ENB in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier

## 5.2.8 IOC Cdma2000Relation

Attribute of IOC Cdma2000Relation in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
adjacentSector	adjacentSector	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference	M	M	-

## 5.2.9 IOC EP\_RP\_EPS

Attribute of IOC EP_RP_EPS in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
farEndNeIpAddress	farEndNeIpAddress	string	O	M	O

### 5.2.10 IOC SectorEquipmentFunction

Attribute of IOC SectorEquipmentFunction in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
fqBand	fqBand	short	M	M	-
confOutputPower	confOutputPower	short	M	M	M

### 5.2.11 IOC ExternalENBFunction

Attribute of IOC ExternalENBFunction in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-

---

## 6 Rules for management information model extensions

For rules on how the models and IDL definitions provided in the present document can be extended for a particular implementation while still remaining compliant with 3GPP SA5's specifications, see annex B of TS 32.153 [4].

## Annex A (normative): CORBA IDL, NRM definitions

```

//File:EUtranNetworkResourcesNRMDefs.idl
#ifndef _EUTRANNETWORKRESOURCESNRMDDFS_IDL_
#define _EUTRANNETWORKRESOURCESNRMDDFS_IDL_
#include "GenericNetworkResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module EUtranNetworkResourcesNRMDefs
{

    /*
    * Definitions for MO class ENBFunction
    */
    interface ENBFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "ENBFunction";
        // Attribute Names
        //
        const string id= "id";
        const string x2BlackList= "x2BlackList";
        const string x2WhiteList= "x2WhiteList";
        const string x2HOBlackList= "x2HOBlackList";
        const string x2IpAddressList= "x2IpAddressList";
    };

    /*
    * Definitions for MO class EUtranGenericCell
    */
    interface EUtranGenericCell: GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "EUtranGenericCell";
        // Attribute Names
        //
        const string id = "id";
        const string cellIdentity = "cellIdentity";
        const string cellSize = "cellSize";
        const string plmnIdList = "plmnIdList";
        const string tac = "tac";
        const string pci = "pci";
        const string pciList = "pciList";
        const string operationalState = "operationalState";
        const string administrativeState = "administrativeState";
        const string availabilityStatus = "availabilityStatus";
        const string maximumTransmissionPower = "maximumTransmissionPower";
        const string referenceSignalPower = "referenceSignalPower";
        const string pb = "pb";
        const string partOfSectorPower = "partOfSectorPower";
    };

    /*
    * Definitions for MO class ExternaleUtranGenericCell
    */
    interface ExternaleUtranGenericCell: GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "ExternaleUtranGenericCell";
        // Attribute Names
        //
        const string id= "id";
        const string pci= "pci";
        const string plmnIdList = "plmnIdList";
        const string cellIdentity = "cellIdentity";
    };
}

```

```
/*
 * Definitions for MO class EUTranCellFDD
 */
interface EUTranCellFDD: EUTranGenericCell
{
    const string CLASS = "EUTranCellFDD";
    // Attribute Names
    //
    const string earfcnDl = "earfcnDl";
    const string earfcnUl = "earfcnUl";
};

/*
 * Definitions for MO class ExternaleUTranCellFDD
 */
interface ExternaleUTranCellFDD: ExternaleUTranGenericCell
{
    const string CLASS = "ExternaleUTranCellFDD";
    // Attribute Names
    //
    const string earfcnDl = "earfcnDl";
    const string earfcnUl = "earfcnUl";
};

/*
 * Definitions for MO class EUTranCellTDD
 */
interface EUTranCellTDD: EUTranGenericCell
{
    const string CLASS = "EUTranCellTDD";
    // Attribute Names
    //
};

/*
 * Definitions for MO class ExternaleUTranCellTDD
 */
interface ExternaleUTranCellTDD: ExternaleUTranGenericCell
{
    const string CLASS = "ExternaleUTranCellTDD";
    // Attribute Names
    //
};

/*
 * Definitions for MO class EUTranRelation
 */
interface EUTranRelation: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "EUTranRelation";
    // Attribute Names
    //
    const string id= "id";
    const string tCI = "tCI";
    const string isRemoveAllowed = "isRemoveAllowed";
    const string isHOAllowed = "isHOAllowed";
    const string adjacentCell = "adjacentCell";
};

/*
 * Definitions for MO class Link_ENB_ENB
 */
interface Link_ENB_ENB: GenericNetworkResourcesNRMDefs::Link
{
    const string CLASS = "Link_ENB_ENB";
    // Attribute Names
    //
};
```

```

/*
 * Definitions for MO class Cdma2000Relation
 */
interface Cdma2000Relation:GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "Cdma2000Relation";
    // Attribute Names
    //
    const string id= "id";
    const string adjacentSector = "adjacentSector";
};

/*
 * Definitions for MO class EP_RP_EPS
 */
interface EP_RP_EPS: GenericNetworkResourcesNRMDefs::EP_RP
{
    const string CLASS = "EP_RP_EPS";
    // Attribute Names
    //
    const string farEndNeIpAddr = "farEndNeIpAddr";
};

/*
 * Definitions for MO class ExternalENBFunction
 */
interface ExternalENBFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "ExternalENBFunction";
    // Attribute Names
    //
    const string id = "id";
};

*
 * Definitions for MO class SectorEquipmentFunction
 */
interface SectorEquipmentFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "SectorEquipmentFunction";
    // Attribute Names
    //
    const string id= "id";
    const string fqBand= "fqBand";
    const string confOutputPower= "confOutputPower";
};

};

module genericEUTRANNRMAAttributeTypes
{
    enum cellSizeEnumType
    {
        verysmall,
        small,
        medium,
        large
    };

    struct PlmnIdType
    {
        short mcc;
        short mnc;
    };
    const short PLMNID_LIST_LENGTH = 6
    typedef sequence<PlmnIdType > plmnIdListType;
};

```

```
const short NO_OF_PCIS = 504;
typedef sequence<short,NO_OF_PCIS> pciListType;

typedef sequence<string> ipAddressListType;

};

};
#endif // _EUTRANNETWORKRESOURCESNRMDEFS_IDL_
```

## Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Mar 2009	SP-43	SP-090075	--	--	Presentation to SA for information and approval	1.0.0	8.0.0
Jun 2009	SP-44	SP-090408	001	--	Add the missing cellSize attribute in EUTRANGenericCell - align with 36.423	8.0.0	8.1.0
Jun 2009	SP-44	SP-090408	003	--	Add the missing downlink power related attributes for EUTRAN Cell - align with 36.213 and 36.331	8.0.0	8.1.0
Sep 2009	SP-45	SP-090542	005	-	Align with the IS in 32.762 - Add and remove attributes for IOC Relations	8.1.0	8.2.0
Sep 2009	SP-45	SP-090542	007	-	Add missing attribute "id" and remove old "<Classname>Id" attributes.	8.1.0	8.2.0
Sep 2009	SP-45	SP-090542	008	-	Align with the IS in 32.762 - Add ExternalENBFunction	8.1.0	8.2.0
Sep 2009	SP-45	SP-090542	012	-	Add plmnIdList to ExternalEutranGenericCell	8.1.0	8.2.0
Mar 2010	SP-47	SP-100037	017	-	Align inheritance with IS	8.2.0	8.3.0
Sep 2010	SP-49	SP-100487	025	--	Align with IS - Remove cellType	8.3.0	8.4.0



---

## History

<b>Document history</b>		
V8.0.0	April 2009	Publication
V8.1.0	July 2009	Publication
V8.2.0	October 2009	Publication
V8.3.0	April 2010	Publication
V8.4.0	October 2010	Publication