

ETSI TS 132 766 V10.5.0 (2011-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Evolved Universal Terrestrial Radio Access
Network (E-UTRAN) Network Resource Model (NRM)
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 32.766 version 10.5.0 Release 10)**



Reference

RTS/TSGS-0532766va50

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Foreword..... | 5 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 3 Definitions and abbreviations..... | 7 |
| 3.1 Definitions | 7 |
| 3.2 Abbreviations | 8 |
| 4 Solution Set Definitions | 8 |
| Annex A (normative): CORBA Solution Set | 9 |
| A.1 Architectural features | 9 |
| A.1.1 Syntax for Distinguished Names | 9 |
| A.1.2 Rules for NRM extensions | 9 |
| A.1.2.1 Allowed extensions..... | 9 |
| A.1.2.2 Extensions not allowed | 9 |
| A.2 Mapping | 10 |
| A.2.1 General mapping | 10 |
| A.2.2 Information Object Class (IOC) mapping | 10 |
| A.2.2.1 IOC ENBFunction | 10 |
| A.2.2.2 IOC EUTRANGenericCell..... | 11 |
| A.2.2.3 IOC ExternalEUTRANGenericCell | 12 |
| A.2.2.4 IOC EUTRANCellFDD | 12 |
| A.2.2.5 IOC ExternalEUTRANCellFDD | 12 |
| A.2.2.6 IOC EUTRANRelation | 13 |
| A.2.2.7 IOC Link_ENB_ENB | 14 |
| A.2.2.8 IOC Cdma2000Relation | 14 |
| A.2.2.9 Void | 14 |
| A.2.2.10 IOC ExternalENBFunction..... | 14 |
| A.2.2.11 IOC EUTRANCellTDD..... | 14 |
| A.2.2.12 IOC ExternalEUTRANCellTDD..... | 14 |
| A.2.2.13 IOC MCEFunction..... | 15 |
| A.2.2.14 IOC MBSFNArea | 15 |
| A.2.2.15 IOC RNFunction..... | 15 |
| A.2.2.16 IOC DeNBCapability..... | 15 |
| A.2.2.17 IOC ExternalRNFunction | 15 |
| A.2.2.18 Void | 16 |
| A.2.2.19 IOC QciDscpMapping | 16 |
| A.2.2.20 IOC EnergySavingProperties..... | 17 |
| A.2.2.21 IOC CellOutageCompensationInformation | 17 |
| A.2.2.22 IOC EUTRANCellNMCentralizedSON..... | 18 |
| A.3 Solution Set definitions | 22 |
| A.3.1 IDL definition structure | 22 |
| A.3.2 IDL specification "EUTRANNetworkResourcesNRMDefs.idl" | 22 |
| Annex B (normative): XML Definitions | 31 |
| B.1 Architectural features | 31 |
| B.1.1 Syntax for Distinguished Names | 31 |
| B.2 Mapping | 31 |

| | | |
|-------------------------------|--|-----------|
| B.2.1 | General mapping | 31 |
| B.2.2 | Information Object Class (IOC) mapping | 31 |
| B.3 | Solution Set definitions | 32 |
| B.3.1 | XML definition structure | 32 |
| B.3.2 | Graphical Representation | 32 |
| B.3.3 | XML schema "eutranNrm.xsd" | 33 |
| Annex C (informative): | Change history | 48 |
| History | | 49 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

| | |
|------------------|---|
| TS 32.761 | Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP): Requirements |
| TS 32.762 | Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS) |
| TS 32.766 | Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions |

1 Scope

The present document is part of an Integration Reference Point (IRP) named E-UTRAN Network Resource Model (NRM) IRP, through which an `IRPAgent` can communicate configuration management information to one or several `IRPManagers` concerning E-UTRAN resources. The E-UTRAN NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set(s).

The present document specifies the Solution Sets for the E-UTRAN NRM IRP.

This Solution Set specification is related to 3GPP TS 32.762 V10.5.X [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 32.153: "Telecommunication management; Integration Reference Point (IRP) technology specific templates, rules and guidelines".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 32.762: " Telecommunications management; Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] 3GPP TS 32.606: "Telecommunication management; Configuration Management (CM); Basic CM Integration Reference Point (IRP); Solution Set (SS) definitions".
- [7] 3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Solution Set (SS) definitions".
- [8] W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)".
- [9] W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer".
- [10] W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures".
- [11] W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes".
- [12] W3C REC-xml-names-19990114: "Namespaces in XML".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1], TS 32.600 [3] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

XML file: file containing an XML document

XML document: composed of the succession of an optional XML declaration followed by a root XML element

NOTE: See [8]; in the scope of the present document.

XML declaration: it specifies the version of XML being used

NOTE: See [8].

XML element: has a type, is identified by a name, may have a set of XML attribute specifications and is either composed of the succession of an XML start-tag followed by the XML content of the XML element followed by an XML end-tag, or composed simply of an XML empty-element tag; each XML element may contain other XML elements

NOTE: See [8].

empty XML element: having an empty XML content; an empty XML element still possibly has a set of XML attribute specifications; an empty XML element is either composed of the succession of an XML start-tag directly followed by an XML end-tag, or composed simply of an XML empty-element tag

NOTE: See [8].

XML content (of an XML element): empty if the XML element is simply composed of an XML empty-element tag; otherwise the part, possibly empty, of the XML element between its XML start-tag and its XML end-tag

XML start-tag: the beginning of a non-empty XML element is marked by an XML start-tag containing the name and the set of XML attribute specifications of the XML element

NOTE: See [8].

XML end-tag: the end of a non-empty XML element is marked by an XML end-tag containing the name of the XML element

NOTE: See [8].

XML empty-element tag: composed simply of an empty-element tag containing the name and the set of XML attribute specifications of the XML element.

NOTE: See [8].

XML attribute specification: has a name and a value

NOTE: See [8].

DTD: defines structure and content constraints to be respected by an XML document to be valid with regard to this DTD

NOTE: See [8].

XML schema: more powerful than a DTD, an XML schema defines structure and content constraints to be respected by an XML document to conform with this XML schema; through the use of XML namespaces several XML schemas can be used together by a single XML document; an XML schema is itself also an XML document that shall conform with the XML schema for XML schemas

NOTE: See [9], [10] and [11].

XML namespace: enables qualifying element and attribute names used in XML documents by associating them with namespaces identified by different XML schemas

NOTE: See [12], in the scope of the present document.

XML complex type: defined in an XML schema; cannot be directly used in an XML document; can be the concrete type or the derivation base type for an XML element type or for another XML complex type; ultimately defines constraints for an XML element on its XML attribute specifications and/or its XML content

NOTE: See [9], [10] and [11].

XML element type: declared by an XML schema; can be directly used in an XML document; as the concrete type of an XML element, directly or indirectly defines constraints on its XML attribute specifications and/or its XML content; can also be the concrete type or the derivation base type for another XML element type

NOTE: See [9], [10] and [11].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1], TS 32.600 [3], and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

| | |
|-------|--|
| CM | Configuration Management |
| CORBA | Common Object Request Broker Architecture |
| DN | Distinguished Name |
| DTD | Document Type Definition |
| EDGE | Enhanced Data for GSM Evolution |
| GERAN | GSM/EDGE Radio Access Network |
| GSM | Global System for Mobile communication |
| IS | Information Service |
| IDL | Interface Definition Language (OMG) |
| IOC | Information Object Class |
| IRP | Integration Reference Point |
| IS | Information Service |
| MO | Managed Object |
| MOC | Managed Object Class |
| NRM | Network Resource Model |
| OMG | Object Management Group |
| SS | Solution Set |
| UMTS | Universal Mobile Telecommunications System |
| UTRAN | Universal Terrestrial Radio Access Network |
| XML | eXtensible Markup Language |
| XSD | XML Schema Definition |

4 Solution Set Definitions

This specification defines the following 3GPP E-UTRAN NRM IRP Solution Set Definitions:

- 3GPP E-UTRAN NRM IRP CORBA SS (Annex A)
- 3GPP E-UTRAN NRM IRP XML Definitions (Annex B)

Annex A (normative): CORBA Solution Set

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in E-UTRAN NRM IRP: Information Service (TS 32.762 [4]).

A.1 Architectural features

The overall architectural feature of E-UTRAN Network Resources IRP is specified in 3GPP TS 32.762 [4]. This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

A.1.2 Rules for NRM extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications (see also Annex B of TS 32.153 [2]).

A.1.2.1 Allowed extensions

Vendor-specific MOCs may be supported. The vendor-specific MOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific MOCs and vendor-specific attributes. New MOCs shall be distinguishable from 3GPP SA5 MOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific MOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM MOCs may be subclassed. Subclassed MOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed MOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM MOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, ManagementNode (or its subclasses) shall be contained under SubNetwork (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the MOCs be represented in IDL. 3GPP SA5's NRM MOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study.

A.1.2.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not MOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

A.2 Mapping

A.2.1 General mapping

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

A.2.2 Information Object Class (IOC) mapping

This Solution Set supports reference attributes for relations other than containment relations between objects. Reference attributes are therefore introduced in each MOC where needed.

A.2.2.1 IOC ENBFunction

Mapping from NRM IOC ENBFunction attributes and associations to SS equivalent MOC ENBFunction attributes

| Attribute of IOC ENBFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|----------------------|--|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| eNBId | eNBId | unsignedLong | M | M | - |
| x2BlackList | x2BlackList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | CM | M | M |
| x2WhiteList | x2WhiteList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | CM | M | M |
| x2HOBlackList | x2HOBlackList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | CM | M | M |
| x2IpAddressList | x2IpAddressList | genericEUTRANNRMAAttributeTypes::ipAddressListType | O | M | - |
| tceIDMappingInfoList | tceIDMappingInfoList | genericEUTRANNRMAAttributeTypes::TceIDMappingInfoListType | CM | M | M |

Note: For all conditional qualifiers, see attribute constraints in 32.762 [4]

A.2.2.2 IOC EUTRANGenericCell

Mapping from NRM IOC EUTRANGenericCell attributes and associations to SS equivalent MOC EUTRANGenericCell attributes

| Attribute of IOC EUTRANGenericCell in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--|--|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| cellLocalId | cellLocalId | unsignedShort | M | M | M |
| cellSize | cellSize | genericEUTRANRRMAAttributeTypes::cellSizeEnumType | M | M | M |
| plmnIdList | plmnIdList Note: the first plmnId in the SS attribute plmnIdList is the primary PLMN id | genericEUTRANRRMAAttributeTypes::plmnIdListType | M | M | M |
| tac | tac | long | M | M | M |
| pci | pci | short | M | M | CM |
| pciList | pciList | genericEUTRANRRMAAttributeTypes::pciListType | CM | M | M |
| maximumTransmissionPower | maximumTransmissionPower | short | M | M | CM |
| referenceSignalPower | referenceSignalPower | short | M | M | M |
| pb | pb | short | M | M | M |
| partOfSectorPower | partOfSectorPower | short | CM | M | M |
| relatedTmaList | relatedTmaList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | CO | M | - |
| relatedAntennaList | relatedAntennaList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | CO | M | - |
| relatedSector | relatedSector | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | CM | M | - |
| operationalState | operationalState | StateManagementIRPOptConstDefs::OperationalStateTypeOpt | O | M | - |
| administrativeState | administrativeState | StateManagementIRPOptConstDefs::AdministrativeStateTypeOpt | O | M | M |
| availabilityStatus | availabilityStatus | StateManagementIRPOptConstDefs::AvailabilityStatusTypeOpt | O | M | - |
| cellResvInfo | cellResvInfo | genericEUTRANRRMAAttributeTypes::cellResvInfoType | CM | M | M |
| allowedAccessClasses | allowedAccessClasses | genericEUTRANRRMAAttributeTypes::allowedAccessEnumClassesType | M | M | M |
| isChangeForEnergySavingAllowed | isChangeForEnergySavingAllowed | GenericNetworkResourcesIRPSystem::AttributeTypes::yesNoType | CM | M | M |

Note: For all conditional qualifiers, see attribute constraints in 32.762 [4]

A.2.2.3 IOC ExternalEUTranGenericCell

Mapping from NRM IOC ExternalEUTranGenericCell attributes and associations to SS equivalent MOC ExternalEUTranGenericCell attributes

| Attribute of IOC ExternalEUTranGenericCell in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--|---|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| pci | pci | short | M | M | M |
| plmnIdList | plmnIdList Note: the first plmnId in the SS attribute plmnIdList is the primary PLMN id | genericEUTRANRRMAAttributeTypes::plmnIdListType | M | M | M |
| cellLocalId | cellLocalId | unsignedShort | M | M | M |
| eNBId | eNBId | unsignedLong | CM | M | M |

A.2.2.4 IOC EUTranCellFDD

Mapping from NRM IOC EUTranCellFDD attributes and associations to SS equivalent MOC EUTranCellFDD attributes

| Attribute of IOC EUTranCellFDD in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--------------|---------|-------------------|----------------|-----------------|
| earfcnDl | earfcnDl | short | M | M | M |
| earfcnUl | earfcnUl | short | M | M | M |

A.2.2.5 IOC ExternalEUTranCellFDD

Mapping from NRM IOC ExternalEUTranCellFDD attributes and associations to SS equivalent MOC ExternalEUTranCellFDD attributes

| Attribute of IOC ExternalEUTranCellFDD in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--------------|---------|-------------------|----------------|-----------------|
| earfcnDl | earfcnDl | short | M | M | M |
| earfcnUl | earfcnUl | short | M | M | M |

A.2.2.6 IOC EUTranRelation

Mapping from NRM IOC EUTranRelation attributes and associations to SS equivalent MOC EUTranRelation attributes

| Attribute of IOC EUTranRelation in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | V Qu |
|---|------------------------------|---|-------------------|----------------|------|
| id | id | string | M | M | |
| tCI | tCI | long | O | M | |
| isRemoveAllowed | isRemoveAllowed | boolean | CM | M | |
| isHOAllowed | isHOAllowed | boolean | CM | M | |
| adjacentCell | adjacentCell | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | |
| isICICInformationSendAllowed | isICICInformationSendAllowed | boolean | CM | M | |
| isLBAllowed | isLBAllowed | boolean | CM | M | |
| isESCoveredBy | isESCoveredBy | genericEUTRANNRMAttributeTypes::IsEsCoveredByEnumType | CM | M | |
| cellIndividualOffset | cellIndividualOffset | genericEUTRANNRMAttributeTypes::qOffsetEnumType | CM | M | |
| qOffset | qOffset | genericEUTRANNRMAttributeTypes::qOffsetEnumType | CM | M | |

NOTE: For all conditional qualifiers, see attribute constraints in 32.762 [4]

A.2.2.7 IOC Link_ENB_ENB

Mapping from NRM IOC Link_ENB_ENB attributes and associations to SS equivalent MOC Link_ENB_ENB attributes

| Attribute of IOC Link_ENB_ENB in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|--------------|---------|-------------------|----------------|-----------------|
| | | | | | |

A.2.2.8 IOC Cdma2000Relation

Mapping from NRM IOC Cdma2000Relation attributes and associations to SS equivalent MOC Cdma2000Relation attributes

| Attribute of IOC Cdma2000Relation in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|----------------|---|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| adjacentSector | adjacentSector | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | - |

A.2.2.9 Void

A.2.2.10 IOC ExternalENBFunction

Mapping from NRM IOC ExternalENBFunction attributes and associations to SS equivalent MOC ExternalENBFunction attributes

| Attribute of IOC ExternalENBFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--------------|--------------|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| eNBId | eNBId | unsignedLong | M | M | - |

A.2.2.11 IOC EUTRANCellTDD

Mapping from NRM IOC EUTRANCellTDD attributes and associations to SS equivalent MOC EUTRANCellTDD attributes

| Attribute of IOC EUTRANCellTDD in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|-------------------|---------|-------------------|----------------|-----------------|
| earfcn | earfcn | short | M | M | M |
| sfAssignment | sfAssignment | short | M | M | M |
| specialSfPatterns | specialSfPatterns | short | M | M | M |

A.2.2.12 IOC ExternalEUTRANCellTDD

Mapping from NRM IOC ExternalEUTRANCellTDD attributes and associations to SS equivalent MOC ExternalEUTRANCellTDD attributes

| Attribute of IOC ExternalEUTRANCellTDD in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--------------|---------|-------------------|----------------|-----------------|
| earfcn | earfcn | short | M | M | M |

A.2.2.13 IOC MCEFunction

| Attribute of IOC MCEFunction in 3GPP TS 32.762 [2] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--------------|---------|-------------------|----------------|-----------------|
| id | id | string | M | M | - |

A.2.2.14 IOC MBSFNArea

| Attribute of IOC MBSFNArea in 3GPP TS 32.762 [2] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|--------------|--|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| mbsfnAreaId | mbsfnAreaId | short | M | M | M |
| cellIdList | cellIdList | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | M | M | M |

A.2.2.15 IOC RNFunction

Mapping from NRM IOC RNFunction attributes and associations to SS equivalent MOC RNFunction attributes

| Attribute of IOC RNFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|--------------------|---|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| servingCell | servingCell | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | M |
| candidateDeNBCells | candidateDeNBCells | genericEUTRANNRMAttributeTypes::EcgiListType | M | M | M |

Editor's note: the need of attribute candidateDeNBCells is for FFS.

A.2.2.16 IOC DeNBCapability

Mapping from NRM IOC DeNBCapability attributes and associations to SS equivalent MOC DeNBCapability attributes

| Attribute of IOC DeNBCapability in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|-----------------|--|-------------------|----------------|-----------------|
| id | id | string | M | M | - |
| servedRN | servedRN | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | M | M | M |
| maxNbrRNAllowed | maxNbrRNAllowed | unsignedShort | M | M | M |

A.2.2.17 IOC ExternalRNFunction

Mapping from NRM IOC ExternalRNFunction attributes and associations to SS equivalent MOC ExternalRNFunction attributes

| Attribute of IOC RNFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|--------------|---------|-------------------|----------------|-----------------|
| id | id | string | M | M | - |

A.2.2.18 Void

A.2.2.19 IOC QciDscpMapping

**Mapping from NRM IOC QciDscpMapping attributes and associations to SS equivalent MOC
QciDscpMapping attributes**

| Attribute of IOC RNFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|--------------------|--|----------------------|-------------------|--------------------|
| id | id | string | M | M | - |
| qciDscpMappingList | qciDscpMappingList | genericEUTRANNRMAttributeTypes:: qciDscpMappingListType | M | M | M |

A.2.2.20 IOC EnergySavingProperties

Mapping from NRM IOC EnergySavingPropoerties attributes and associations to SS equivalent MOC ExternalID EnergySavingPropoerties attributes

| Attribute of IOC EnergySavingPropoerties in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|---------------------|---|-------------------|----------------|-----------------|
| energySavingState | energySavingState | genericEUTRANNRMAttributeTypes::EnergySavingStateEnumType | M | M | - |
| energySavingControl | energySavingControl | genericEUTRANNRMAttributeTypes::EnergySavingControlEnumType | CM | M | M |

A.2.2.21 IOC CellOutageCompensationInformation

| Attribute of IOC SONTargets in 3GPP TS 32.522 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|------------------------------|--|-------------------|----------------|-----------------|
| cOCStatus | cellOutageCompensationStatus | GenericSONPolicyNRMAAttributeTypes::cellOutageCompensationStatus | M | M | - |
| isCOAllowed | isCOAllowed | Boolean | M | M | M |

A.2.2.22 IOC EUtranCellINMCentralizedSON

Mapping from NRM IOC EUtranCellINMCentralizedSON attributes and associations to SS equivalent MOC EUtranCellINMCentralizedSON attributes

| Attribute of IOC ENBFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|---------------------------|---|-------------------|----------------|-----------------|
| a1ThresholdRsrp | a1ThresholdRsrp | unsignedShort | CM | M | M |
| a1ThresholdRsrq | a1ThresholdRsrq | unsignedShort | CM | M | M |
| a2ThresholdRsrp | a2ThresholdRsrp | unsignedShort | CM | M | M |
| a2ThresholdRsrq | a2ThresholdRsrq | unsignedShort | CM | M | M |
| a3Offset | a3Offset | short | CM | M | M |
| a4ThresholdRsrp | a4ThresholdRsrp | unsignedShort | CM | M | M |
| a4ThresholdRsrq | a4ThresholdRsrq | unsignedShort | CM | M | M |
| a5Threshold1Rsrp | a5Threshold1Rsrp | unsignedShort | CM | M | M |
| a5Threshold1Rsrq | a5Threshold1Rsrq | unsignedShort | CM | M | M |
| b1ThresholdUtraRscp | b1ThresholdUtraRscp | short | CM | M | M |
| b1ThresholdUtraEcN0 | b1ThresholdUtraEcN0 | unsignedShort | CM | M | M |
| b1ThresholdGeran | b1ThresholdGeran | unsignedShort | CM | M | M |
| b1ThresholdCdma2000 | b1ThresholdCdma2000 | unsignedShort | CM | M | M |
| b2Threshold1Rsrp | b2Threshold1Rsrp | unsignedShort | CM | M | M |
| b2Threshold1Rsrq | b2Threshold1Rsrq | unsignedShort | CM | M | M |
| b2Threshold2UtraRscp | b2Threshold2UtraRscp | short | CM | M | M |
| b2Threshold2UtraEcN0 | b2Threshold2UtraEcN0 | unsignedShort | CM | M | M |
| b2Threshold2Geran | b2Threshold2Geran | unsignedShort | CM | M | M |
| b2Threshold2Cdma2000 | b2Threshold2Cdma2000 | unsignedShort | CM | M | M |
| commonChannelPowerOffset | commonChannelPowerOffset | short | CM | M | M |
| configurationIndex | configurationIndex | unsignedShort | CM | M | M |
| contentionResolutionTimer | contentionResolutionTimer | genericEUTRANNRM AttributeTypes:: contentionResolutionTimerEnumType | CM | M | M |
| hysteresisEutraA1 | hysteresisEutraA1 | unsignedShort | CM | M | M |
| hysteresisEutraA2 | hysteresisEutraA2 | unsignedShort | CM | M | M |
| hysteresisEutraA3 | hysteresisEutraA3 | unsignedShort | CM | M | M |

| Attribute of IOC ENBFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|--|------------------------------------|---|-------------------|----------------|-----------------|
| 3 | | | | | |
| hysteresisEutraA4 | hysteresisEutraA4 | unsignedShort | CM | M | M |
| hysteresisEutraA5 | hysteresisEutraA5 | unsignedShort | CM | M | M |
| hysteresisIratB1 | hysteresisIratB1 | unsignedShort | CM | M | M |
| hysteresisIratB2 | hysteresisIratB2 | unsignedShort | CM | M | M |
| numberOfRaPreambles | numberOfRaPreambles | genericEUTRANRM AttributeTypes:: numberOfRaPreamblesEnumType | CM | M | M |
| preambleInitialReceivedTargetPower | preambleInitialReceivedTargetPower | genericEUTRANRM AttributeTypes:: preambleInitialReceivedTargetPowerEnumType | CM | M | M |
| preambleTransMax | preambleTransMax | genericEUTRANRM AttributeTypes:: preambleTransMaxEnumType | CM | M | M |
| pMax | pMax | short | CM | M | M |
| powerRampingStep | powerRampingStep | genericEUTRANRM AttributeTypes:: powerRampingStepEnumType | CM | M | M |
| qHyst | qHyst | genericEUTRANRM AttributeTypes:: qHystEnumType | CM | M | M |
| qOffsetUtra | qOffsetUtra | unsignedShort | CM | M | M |
| qOffsetGeran | qOffsetGeran | unsignedShort | CM | M | M |
| qOffsetCdma2000 | qOffsetCdma2000 | unsignedShort | CM | M | M |
| qQualMinUtra | qQualMinUtra | unsignedShort | CM | M | M |
| qRxLevMinEUtraSib1 | qRxLevMinEUtraSib1 | short | CM | M | M |
| qRxLevMinEUtraSib3 | qRxLevMinEUtraSib3 | short | CM | M | M |
| qRxLevMinGeran | qRxLevMinGeran | unsignedShort | CM | M | M |
| qRxLevMinUtra | qRxLevMinUtra | short | CM | M | M |
| responseWindowSize | responseWindowSize | genericEUTRANRM AttributeTypes:: responseWindowSizeEnumType | CM | M | M |
| rootSequenceIndex | rootSequenceIndex | unsignedShort | CM | M | M |

| Attribute of IOC ENBFunction in 3GPP TS 32.762 [4] | SS Attribute | SS Type | Support Qualifier | Read Qualifier | Write Qualifier |
|---|------------------------|---|-------------------|----------------|-----------------|
| x | | | | | |
| sIntraSearch | sIntraSearch | unsignedShort | CM | M | M |
| sizeOfRAPreambleGroupA | sizeOfRAPreambleGroupA | genericEUTRANRMAttributeTypes::sizeOfRAPreambleGroupAEnumType | CM | M | M |
| timeToTriggerEutraA1 | timeToTriggerEutraA1 | genericEUTRANRMAttributeTypes::timeToTriggerEutraEnumType | CM | M | M |
| timeToTriggerEutraA2 | timeToTriggerEutraA2 | genericEUTRANRMAttributeTypes::timeToTriggerEutraEnumType | CM | M | M |
| timeToTriggerEutraA3 | timeToTriggerEutraA3 | genericEUTRANRMAttributeTypes::timeToTriggerEutraEnumType | CM | M | M |
| timeToTriggerEutraA4 | timeToTriggerEutraA4 | genericEUTRANRMAttributeTypes::timeToTriggerEutraEnumType | CM | M | M |
| timeToTriggerEutraA5 | timeToTriggerEutraA5 | genericEUTRANRMAttributeTypes::timeToTriggerEutraEnumType | CM | M | M |
| timeToTriggerIratB1 | timeToTriggerIratB1 | genericEUTRANRMAttributeTypes::timeToTriggerEutraEnumType | CM | M | M |
| timeToTriggerIratB2 | timeToTriggerIratB2 | genericEUTRANRMAttributeTypes::timeToTriggerEutraEnumType | CM | M | M |
| tReselectionCdma2000 | tReselectionCdma2000 | unsignedShort | CM | M | M |
| tReselectionEutra | tReselectionEutra | unsignedShort | CM | M | M |
| tReselectionGeran | tReselectionGeran | unsignedShort | CM | M | M |
| tReselectionUtra | tReselectionUtra | unsignedShort | CM | M | M |
| tStoreUeContext | tStoreUeContext | unsignedShort | CM | M | M |
| Note: For all conditional qualifiers, see attribute constraints in 32.762 [4] | | | | | |

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 defines the MO classes for the E-UTRAN NRM IRP.

A.3.2 IDL specification "EUTranNetworkResourcesNRMDefs.idl"

```
//File:EUTranNetworkResourcesNRMDefs.idl
#ifndef _EUTRANNETWORKRESOURCESNRMDDFS_IDL_
#define _EUTRANNETWORKRESOURCESNRMDDFS_IDL_
#include "GenericNetworkResourcesNRMDefs.idl"
#include "EPCResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module EUTranNetworkResourcesNRMDefs
{
    /*
    * Definitions for MO class ENBFunction
    */
    interface ENBFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "ENBFunction";
        // Attribute Names
        //
        const string id= "id";
        const string eNBId = "eNBId";
        const string x2BlackList= "x2BlackList";
        const string x2WhiteList= "x2WhiteList";
        const string x2HOBlackList= "x2HOBlackList";
        const string x2IpAddressList= "x2IpAddressList";
        const string tceIDMappingInfoList= "tceIDMappingInfoList";

    };
    /*
    * Definitions for MO class RNFunction
    */
    interface RNFunction: ENBFunction
    {
        const string CLASS = "RNFunction";
        // Attribute Names
        //
        const string servingCell = "servingCell";
        const string candidateDeNBCells = "candidateDeNBCells";
    };
    /*
    * Definitions for MO class DeNBCapability
    */
    interface DeNBCapability: GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "DeNBCapability";
        // Attribute Names
        //
        const string id= "id";
        const string servedRN= "servedRN";
        const string maxNbrRNAllowed= "maxNbrRNAllowed";
    };
    /*
    * Definitions for MO class ExternalRNFunction
    */
    interface ExternalRNFunction: ExternalENBFunction
    {
        const string CLASS = "ExternalRNFunction";
        // Attribute Names
        //
    };
};
```

```

/*
/*
 * Definitions for MO class EUTranGenericCell
 */
interface EUTranGenericCell: GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "EUTranGenericCell";
    // Attribute Names
    //
    const string id = "id";
    const string cellLocalId = "cellLocalId";
    const string cellSize = "cellSize";
    const string plmnIdList = "plmnIdList";
    const string tac = "tac";
    const string pci = "pci";
    const string pciList = "pciList";
    const string operationalState = "operationalState";
    const string administrativeState = "administrativeState";
    const string availabilityStatus = "availabilityStatus";
    const string maximumTransmissionPower = "maximumTransmissionPower";
    const string referenceSignalPower = "referenceSignalPower";
    const string pb = "pb";
    const string partOfSectorPower = "partOfSectorPower";
    const string relatedTmaList = "relatedTmaList";
    const string relatedAntennaList = "relatedAntennaList";
    const string relatedSectorEquipment = "relatedSectorEquipment";
    const string allowedAccessClasses = "allowedAccessClasses";
    const string isChangeForEnergySavingAllowed = "isChangeForEnergySavingAllowed";
};

/*
 * Definitions for MO class ExternalEUTranGenericCell
 */
interface ExternalEUTranGenericCell: GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "ExternalEUTranGenericCell";
    // Attribute Names
    //
    const string id = "id";
    const string pci = "pci";
    const string plmnIdList = "plmnIdList";
    const string cellLocalId = "cellLocalId";
    const string eNBId = "eNBId";
};

/*
 * Definitions for MO class EUTranCellFDD
 */
interface EUTranCellFDD: EUTranGenericCell
{
    const string CLASS = "EUTranCellFDD";
    // Attribute Names
    //
    const string earfcnDl = "earfcnDl";
    const string earfcnUl = "earfcnUl";
};

/*
 * Definitions for MO class ExternalEUTranCellFDD
 */
interface ExternalEUTranCellFDD: ExternalEUTranGenericCell
{
    const string CLASS = "ExternalEUTranCellFDD";
    // Attribute Names
    //
    const string earfcnDl = "earfcnDl";
    const string earfcnUl = "earfcnUl";
};

/*
 * Definitions for MO class EUTranCellTDD
 */
interface EUTranCellTDD: EUTranGenericCell
{

```



```
    const string CLASS = "EUTranCellTDD";
    // Attribute Names
    //
    const string earfcn = "earfcn";
    const string sfAssignment = "sfAssignment";
    const string specialSfPatterns = "specialSfPatterns";
};

/*
 * Definitions for MO class ExternaleUtranCellTDD
 */
interface ExternaleUtranCellTDD: ExternaleUtranGenericCell
{
    const string CLASS = "ExternaleUtranCellTDD";
    // Attribute Names
    //
    const string earfcn = "earfcn";
};

/*
 * Definitions for MO class EUTranRelation
 */
interface EUTranRelation: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "EUTranRelation";
    // Attribute Names
    //
    const string id= "id";
    const string tCI = "tCI";
    const string isRemoveAllowed = "isRemoveAllowed";
    const string isHOAllowed = "isHOAllowed";
    const string adjacentCell = "adjacentCell";
    const string isICICInformationSendAllowed = "isICICInformationSendAllowed";
    const string isLBAllowed = "isLBAllowed";
    const string cellIndividualOffset = "cellIndividualOffset";
    const string qOffset = "qOffset";
};

/*
 * Definitions for MO class Link_ENB_ENB
 */
interface Link_ENB_ENB: GenericNetworkResourcesNRMDefs::Link
{
    const string CLASS = "Link_ENB_ENB";
    // Attribute Names
    //
};

/*
 * Definitions for MO class Cdma2000Relation
 */
interface Cdma2000Relation:GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "Cdma2000Relation";
    // Attribute Names
    //
    const string id= "id";
    const string adjacentSector = "adjacentSector";
};

/*
 * Definitions for MO class ExternaleNBFunction
 */
interface ExternaleNBFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "ExternaleNBFunction";
    // Attribute Names
    //
    const string id = "id";
    const string eNBId = "eNBId";
};
```

```
};

/*
 * Definitions for MO class MCEFunction
 */
interface MCEFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "MCEFunction";
    // Attribute Names
    //
    const string id= "id";
};

/*
 * Definitions for MO class Link_MCE_ENB
 */
interface Link_MCE_ENB: GenericNetworkResourcesNRMDefs::Link
{
    const string CLASS = "Link_MCE_ENB";
    // Attribute Names
    //
};

/*
 * Definitions for MO class Link_MCE_MME
 */
interface Link_MCE_MME: GenericNetworkResourcesNRMDefs::Link
{
    const string CLASS = "Link_MCE_MME";
    // Attribute Names
    //
};

/*
 * Definitions for MO class MBSFNArea
 */
interface MBSFNArea: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "MBSFNArea";
    // Attribute Names
    //
    const string id= "id";
    const string mbsfnAreaId= "mbsfnAreaId";
    const string cellIdList= "cellIdList";
};

/*
 * Definitions for MO class QciDscpMapping
 */
interface QciDscpMapping: GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "QciDscpMapping";
    // Attribute Names
    //
    const string id= "id";
    const string qciDscpMappingList = "qciDscpMappingList";
};

};

/*
 * Definitions for MO class EnergySavingProperties
 */
interface EnergySavingProperties: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "EnergySavingProperties";
    // Attribute Names
    //
    const string energySavingState= "energySavingState";
    const string energySavingControl= "energySavingControl";
};
```

```

};

/*
 * Definitions for MO class CellOutageCompensationInformation
 */
interface CellOutageCompensationInformation: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "CellOutageCompensationInformation";
    // Attribute Names
    //
    const string cellOutageCompensationStatus = "cellOutageCompensationStatus";
    const string isCOCAAllowed =
        "isCOCAAllowed";
};

/*
 * Definitions for MO class EUTranCellNMCentralizedSON
 */
interface EUTranCellNMCentralizedSON: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "EUTranCellNMCentralizedSON";
    // Attribute Names
    //
    const string a1ThresholdRsrp = "a1ThresholdRsrp";
    const string a1ThresholdRsrq = "a1ThresholdRsrq";
    const string a2ThresholdRsrp = "a2ThresholdRsrp";
    const string a2ThresholdRsrq = "a2ThresholdRsrq";
    const string a3Offset = "a3Offset";
    const string a4ThresholdRsrp = "a4ThresholdRsrp";
    const string a4ThresholdRsrq = "a4ThresholdRsrq";
    const string a5Threshold1Rsrp = "a5Threshold1Rsrp";
    const string a5Threshold1Rsrq = "a5Threshold1Rsrq";
    const string b1ThresholdUtraRscp = "b1ThresholdUtraRscp";
    const string b1ThresholdUtraEcN0 = "b1ThresholdUtraEcN0";
    const string b1ThresholdGeran = "b1ThresholdGeran";
    const string b1ThresholdCdma2000 = "b1ThresholdCdma2000";
    const string b2Threshold1Rsrp = "b2Threshold1Rsrp";
    const string b2Threshold1Rsrq = "b2Threshold1Rsrq";
    const string b2Threshold2UtraRscp = "b2Threshold2UtraRscp";
    const string b2Threshold2Geran = "b2Threshold2Geran";
    const string b2Threshold2Cdma2000 = "b2Threshold2Cdma2000";
    const string commonChannelPowerOffset = "commonChannelPowerOffset";
    const string configurationIndex = "configurationIndex";
    const string contentionResolutionTimer = "contentionResolutionTimer";
    const string hysteresisEutraA1 = "hysteresisEutraA1";
    const string hysteresisEutraA2 = "hysteresisEutraA2";
    const string hysteresisEutraA3 = "hysteresisEutraA3";
    const string hysteresisEutraA4 = "hysteresisEutraA4";
    const string hysteresisEutraA5 = "hysteresisEutraA5";
    const string hysteresisIratB1 = "hysteresisIratB1";
    const string hysteresisIratB2 = "hysteresisIratB2";
    const string numberOfRaPreambles = "numberOfRaPreambles";
    const string preambleInitialReceivedTargetPower = "preambleInitialReceivedTargetPower";
    const string preambleTransMax = "preambleTransMax";
    const string pMax = "pMax";
    const string powerRampingStep = "powerRampingStep";
    const string qHyst = "qHyst";
    const string qOffsetUtra = "qOffsetUtra";
    const string qOffsetGeran = "qOffsetGeran";
    const string qOffsetCdma2000 = "qOffsetCdma2000";
    const string qQualMinUtra = "qQualMinUtra";
    const string qRxLevMinEutraSib1 = "qRxLevMinEutraSib1";
    const string qRxLevMinEutraSib3 = "qRxLevMinEutraSib3";
    const string qRxLevMinGeran = "qRxLevMinGeran";
    const string qRxLevMinUtra = "qRxLevMinUtra";
    const string responseWindowSize = "responseWindowSize";
    const string rootSequenceIndex = "rootSequenceIndex";
    const string sIntraSearch = "sIntraSearch";
    const string sizeOfRAPreamblesGroupA = "sizeOfRAPreamblesGroupA";
    const string timeToTriggerEutraA1 = "timeToTriggerEutraA1";
    const string timeToTriggerEutraA2 = "timeToTriggerEutraA2";
    const string timeToTriggerEutraA3 = "timeToTriggerEutraA3";
    const string timeToTriggerEutraA4 = "timeToTriggerEutraA4";
    const string timeToTriggerEutraA5 = "timeToTriggerEutraA5";
    const string timeToTriggerIratB1 = "timeToTriggerIratB1";
    const string timeToTriggerIratB2 = "timeToTriggerIratB2";
};

```

```

    const string tReselectionCdma2000 = "tReselectionCdma2000";
    const string tReselectionEutra = "tReselectionEutra";
    const string tReselectionGeran = "tReselectionGeran";
    const string tReselectionUtra = "tReselectionUtra";
    const string tStoreUeContext = "tStoreUeContext";
};

module genericEUTRANRMAttributeTypes
{
    enum CellSizeEnumType
    {
        verysmall,
        small,
        medium,
        large
    };

    enum AllowedAccessClassesValues
    {
        EmergencyCall,
        ForPLMNUse,
        SecurityServices,
        PublicUtilities,
        EmergencyServices,
        PLMNStaff
    };
    typedef sequence < AllowedAccessClassesValues,6> AllowedAccessClasses

    struct PlmnIdType
    {
        short mcc;
        short mnc;
    };
    const short PLMNID_LIST_LENGTH = 6;
    typedef sequence<PlmnIdType > plmnIdListType;

    const short NO_OF_PCIS = 504;
    typedef sequence<short,NO_OF_PCIS> pciListType;

    typedef sequence<string> ipAddressListType;

    enum CellResvInfoType
    {
        reservedCell,
        nonReservedCell
    };

    struct QciDscpMappingType
    {
        short qci;
        short dscp;
    };

    typedef sequence<QciDscpMappingType> QciDscpMappingListType;

    struct EcgiType
    {
        short mcc;
        short mnc;
        unsignedlong eci
    };
    typedef sequence <EcgiType> EcgiListType;

    enum isEsCoveredByEnumType
    {
        no,
        partial,
        yes
    };

    enum yesNoType
    {
        no,
        yes
    };
};

```

```
enum energySavingStateEnumType
{
    isEnergySaving,
    isNotEnergySaving
};

enum energySavingControlEnumType
{
    toBeEnergySaving,
    toBeNotEnergySaving
};

struct TceIDMappingInfo
{
    short tceID;
    string tceIPAddr;
};
typedef sequence<TceIDMappingInfo> TceIDMappingInfoListType;

enum CellOutageCompensationState
{
    COCActivating,
    COCActive,
    COCDeactivating,
    COCDeactive
};

enum qOffsetEnumType
{
    dB-24,
    dB-22,
    dB-20,
    dB-18,
    dB-16,
    dB-14,
    dB-12,
    dB-10,
    dB-8,
    dB-6,
    dB-5,
    dB-4,
    dB-3,
    dB-2,
    dB-1,
    dB0,
    dB1,
    dB2,
    dB3,
    dB4,
    dB5,
    dB6,
    dB8,
    dB10,
    dB12,
    dB14,
    dB16,
    dB18,
    dB20,
    dB22,
    dB24
};

enum contentionResolutionTimerEnumType
{
    sf8,
    sf16,
    sf24,
    sf32,
    sf40,
    sf48,
    sf56,
    sf64
};

enum numberOfRaPreamblesEnumType
{
    n4,
```

```
n8,  
n12,  
n16,  
n20,  
n24,  
n28,  
n32,  
n36,  
n40,  
n44,  
n48,  
n52,  
n56,  
n60,  
n64  
};  
  
enum preambleInitialReceivedTargetPowerEnumType  
{  
    dBm-120,  
    dBm-118,  
    dBm-116,  
    dBm-114,  
    dBm-112,  
    dBm-110,  
    dBm-108,  
    dBm-106,  
    dBm-104,  
    dBm-102,  
    dBm-100,  
    dBm-98,  
    dBm-96,  
    dBm-94,  
    dBm-92,  
    dBm-90  
};  
  
enum preambleTransMaxEnumType  
{  
    n3,  
    n4,  
    n5,  
    n6,  
    n7,  
    n8,  
    n10,  
    n20,  
    n50,  
    n100,  
    n200  
};  
  
enum powerRampingStepEnumType  
{  
    dB0,  
    dB2,  
    dB4,  
    dB6  
};  
  
enum qHystEnumType  
{  
    dB0,  
    dB1,  
    dB2,  
    dB3,  
    dB4,  
    dB5,  
    dB6,  
    dB8,  
    dB10,  
    dB12,  
    dB14,  
    dB16,  
    dB18,  
    dB20,  
    dB22,  
    dB24
```

```
};

enum responseWindowSizeEnumType
{
    sf2,
    sf3,
    sf4,
    sf5,
    sf6,
    sf7,
    sf8,
    sf10
};

enum sizeOfRAPreambleGroupAEnumType
{
    n4,
    n8,
    n12,
    n16,
    n20,
    n24,
    n28,
    n32,
    n36,
    n40,
    n44,
    n48,
    n52,
    n56,
    n60,
};

enum timeToTriggerEutraEnumType
{
    ms0,
    ms40,
    ms64,
    ms80,
    ms100,
    ms128,
    ms160,
    ms256,
    ms320,
    ms480,
    ms512,
    ms640,
    ms1024,
    ms1280,
    ms2560,
    ms5120
};

typedef sequence<string> DnList;

struct CellOutageCompensationStatus
{
    CellOutageCompensationState cellOutageCompensationState;
    DnList errorList;
};

};

#endif // _EUTRANNETWORKRESOURCESNRMDEFS_IDL_
```

Annex B (normative): XML Definitions

This annex contains the XML Definitions for the E-UTRAN NRM IRP as it applies to Itf-N, in accordance with UTRAN NRM IRP IS definitions [4].

B.1 Architectural features

The overall architectural feature of E-UTRAN Network Resources IRP is specified in 3GPP TS 32.762 [4]. This clause specifies features that are specific to the Schema definitions.

The XML definitions of this document specify the schema for a configuration content.

When using the XML definitions for a configuration file transfer with the Bulk CM IRP, using either CORBA Solution Set of 3GPP TS 32.616 [7] or SOAP Solution Set of 3GPP TS 32.616 [7], the basic part of the XML file format definition is provided by 3GPP TS 32.616 [7]. The XML definitions of this document provide the schema for the configuration content to be included in such a configuration file.

When using the XML definitions with a SOAP Solution Set of any Interface IRP that perform operations on managed objects, for example the Basic CM IRP SOAP SS of 3GPP TS 32.606 [6], the XML definitions of this document provides the schema for the configuration content operated on by the interface IRP. Such configuration content can be name of managed object and, if applicable, IOC attributes.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a sub-element of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

Not present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.616 [7].

Annex B.3.3 of the present document defines the NRM-specific XML schema `eutranNrm.xsd` for the E-UTRAN Network Resources IRP NRM defined in 3GPP TS 32.762 [4].

XML schema `eutranNrm.xsd` explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [7].

B.3.2 Graphical Representation

Not present in the current version of this specification.

B.3.3 XML schema "eutranNrm.xsd"

```

<?xml version="1.0" encoding="UTF-8"?>
<!--
 3GPP TS 32.766 E-UTRAN Network Resource Model IRP
 XML schema definition
 eutranNrm.xsd
-->
<schema xmlns="http://www.w3.org/2001/XMLSchema"
xmlns:xn="http://www.3gpp.org/ftp/specs/archive/32_series/32.626#genericNrm"
xmlns:en="http://www.3gpp.org/ftp/specs/archive/32_series/32.766#eutranNrm"
xmlns:epc="http://www.3gpp.org/ftp/specs/archive/32_series/32.756#epcNrm"
xmlns:un="http://www.3gpp.org/ftp/specs/archive/32_series/32.646#utranNrm"
xmlns:gn="http://www.3gpp.org/ftp/specs/archive/32_series/32.656#geranNrm"
xmlns:sm="http://www.3gpp.org/ftp/specs/archive/32_series/32.676#stateManagementIRP"
xmlns:sp="http://www.3gpp.org/ftp/specs/archive/32_series/32.526#sonPolicyNrm"
targetNamespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.766#eutranNrm"
elementFormDefault="qualified">
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.626#genericNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.756#epcNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.646#utranNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.656#geranNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.676#stateManagementIRP"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.526#sonPolicyNrm"/>
  <complexType name="IpAddressList">
    <sequence>
      <element name="ipAddress" type="string" minOccurs="0" maxOccurs="unbounded"/>
    </sequence>
  </complexType>
  <simpleType name="EnbId">
    <restriction base="unsignedLong">
      <maxInclusive value="268435455"/>
    </restriction>
  </simpleType>
  <simpleType name="Eci">
    <restriction base="unsignedLong">
      <maxInclusive value="268435455"/>
    </restriction>
  </simpleType>
  <simpleType name="CellLocalId">
    <restriction base="unsignedShort">
      <maxInclusive value="255"/>
    </restriction>
  </simpleType>
  <simpleType name="cellSize">
    <restriction base="string">
      <enumeration value="verysmall"/>
      <enumeration value="small"/>
      <enumeration value="medium"/>
      <enumeration value="large"/>
    </restriction>
  </simpleType>
  <simpleType name="allowedAccessClassesElementType">
    <restriction base="string">
      <enumeration value="EmergencyCall"/>
      <enumeration value="ForPLMNUse"/>
      <enumeration value="SecurityServices"/>
      <enumeration value="PublicUtilities"/>
      <enumeration value="EmergencyServices"/>
      <enumeration value="PLMNStaff"/>
    </restriction>
  </simpleType>
  <complexType name="allowedAccessClassesType">
    <sequence minOccurs="0" maxOccurs="6">
      <element name="allowedAccessClassesElement" type="en:allowedAccessClassesElementType"/>
    </sequence>
  </complexType>
  <complexType name="PLMNId">
    <sequence>
      <element name="mcc" type="short"/>
      <element name="mnc" type="short"/>
    </sequence>
  </complexType>
  <complexType name="PLMNIdList">
    <sequence>
      <element name="pLMNId" type="en:PLMNId" maxOccurs="6"/>
    </sequence>
  </complexType>

```

```

    <!-- The first pLMNid of the pLMNidList is primary PLMN id -->
  </sequence>
</complexType>
<complexType name="EcgiList">
  <sequence>
    <element name="plmnId" type="en:PLMNid" minOccurs="0"/>
    <element name="eci" type="en:Eci" minOccurs="0"/>
  </sequence>
</complexType>
<simpleType name="Pci">
  <restriction base="unsignedShort">
    <maxInclusive value="503"/>
    <!-- Minimum value is 0, maximum value is 3x167+2=503 -->
  </restriction>
</simpleType>
<complexType name="PciList">
  <sequence>
    <element name="pci" type="en:Pci" maxOccurs="504"/>
  </sequence>
</complexType>
<simpleType name="cellResvInfoTyoe">
  <restriction base="string">
    <enumeration value="reservedCell"/>
    <enumeration value="nonReservedCell"/>
  </restriction>
</simpleType>
<simpleType name="mbsfnAreaIdType">
  <restriction base="unsignedLong">
    <maxInclusive value="255"/>
  </restriction>
</simpleType>
<complexType name="QciDscpMappingType">
  <sequence>
    <element name="qci" type="short"/>
    <element name="dscp" type="short"/>
  </sequence>
</complexType>
<complexType name="QciDscpMappingListType">
  <sequence>
    <element name="QciDscpMappingPair" type="en:QciDscpMappingType"/>
  </sequence>
</complexType>
<simpleType name="isEsCoveredByEnumType">
  <restriction base="string">
    <enumeration value="no"/>
    <enumeration value="partial"/>
    <enumeration value="yes"/>
  </restriction>
</simpleType>
<simpleType name="energySavingStateEnumType">
  <restriction base="string">
    <enumeration value="isEnergySaving"/>
    <enumeration value="isNotEnergySaving"/>
  </restriction>
</simpleType>
<simpleType name="energySavingControlEnumType">
  <restriction base="string">
    <enumeration value="toBeEnergySaving"/>
    <enumeration value="toBeNotEnergySaving"/>
  </restriction>
</simpleType>
<simpleType name="yesNoType">
  <restriction base="string">
    <enumeration value="yes"/>
    <enumeration value="no"/>
  </restriction>
</simpleType>
<simpleType name="QOffsetEnumType">
  <restriction base="string">
    <enumeration value="dB-24"/>
    <enumeration value="dB-22"/>
    <enumeration value="dB-20"/>
    <enumeration value="dB-18"/>
    <enumeration value="dB-16"/>
    <enumeration value="dB-14"/>
    <enumeration value="dB-12"/>
    <enumeration value="dB-10"/>
    <enumeration value="dB-8"/>
  </restriction>

```

```
<enumeration value="dB-6"/>
<enumeration value="dB-5"/>
<enumeration value="dB-4"/>
<enumeration value="dB-3"/>
<enumeration value="dB-2"/>
<enumeration value="dB-1"/>
<enumeration value="dB0"/>
<enumeration value="dB1"/>
<enumeration value="dB2"/>
<enumeration value="dB3"/>
<enumeration value="dB4"/>
<enumeration value="dB5"/>
<enumeration value="dB6"/>
<enumeration value="dB8"/>
<enumeration value="dB10"/>
<enumeration value="dB12"/>
<enumeration value="dB14"/>
<enumeration value="dB16"/>
<enumeration value="dB18"/>
<enumeration value="dB20"/>
<enumeration value="dB22"/>
<enumeration value="dB24"/>
</restriction>
</simpleType>
<simpleType name="ContentionResolutionTimerEnumType">
  <restriction base="string">
    <enumeration value="sf8"/>
    <enumeration value="sf16"/>
    <enumeration value="sf24"/>
    <enumeration value="sf32"/>
    <enumeration value="sf40"/>
    <enumeration value="sf48"/>
    <enumeration value="sf56"/>
    <enumeration value="sf64"/>
  </restriction>
</simpleType>
<simpleType name="NumberOfRaPreamblesEnumType">
  <restriction base="string">
    <enumeration value="n4"/>
    <enumeration value="n8"/>
    <enumeration value="n12"/>
    <enumeration value="n16"/>
    <enumeration value="n20"/>
    <enumeration value="n24"/>
    <enumeration value="n28"/>
    <enumeration value="n32"/>
    <enumeration value="n36"/>
    <enumeration value="n40"/>
    <enumeration value="n44"/>
    <enumeration value="n48"/>
    <enumeration value="n52"/>
    <enumeration value="n56"/>
    <enumeration value="n60"/>
    <enumeration value="n64"/>
  </restriction>
</simpleType>
<simpleType name="PreambleInitialReceivedTargetPowerEnumType">
  <restriction base="string">
    <enumeration value="dBm-120"/>
    <enumeration value="dBm-118"/>
    <enumeration value="dBm-116"/>
    <enumeration value="dBm-114"/>
    <enumeration value="dBm-112"/>
    <enumeration value="dBm-110"/>
    <enumeration value="dBm-108"/>
    <enumeration value="dBm-106"/>
    <enumeration value="dBm-104"/>
    <enumeration value="dBm-102"/>
    <enumeration value="dBm-100"/>
    <enumeration value="dBm-98"/>
    <enumeration value="dBm-96"/>
    <enumeration value="dBm-94"/>
    <enumeration value="dBm-92"/>
    <enumeration value="dBm-90"/>
  </restriction>
</simpleType>
<simpleType name="PreambleTransMaxEnumType">
  <restriction base="string">
```

```

    <enumeration value="n3"/>
    <enumeration value="n4"/>
    <enumeration value="n5"/>
    <enumeration value="n6"/>
    <enumeration value="n7"/>
    <enumeration value="n8"/>
    <enumeration value="n10"/>
    <enumeration value="n20"/>
    <enumeration value="n50"/>
    <enumeration value="n100"/>
    <enumeration value="n200"/>
  </restriction>
</simpleType>
<simpleType name="PowerRampingStepEnumType">
  <restriction base="string">
    <enumeration value="dB0"/>
    <enumeration value="dB2"/>
    <enumeration value="dB4"/>
    <enumeration value="dB6"/>
  </restriction>
</simpleType>
<simpleType name="QHystEnumType">
  <restriction base="string">
    <enumeration value="dB0"/>
    <enumeration value="dB1"/>
    <enumeration value="dB2"/>
    <enumeration value="dB3"/>
    <enumeration value="dB4"/>
    <enumeration value="dB5"/>
    <enumeration value="dB6"/>
    <enumeration value="dB8"/>
    <enumeration value="dB10"/>
    <enumeration value="dB12"/>
    <enumeration value="dB14"/>
    <enumeration value="dB16"/>
    <enumeration value="dB18"/>
    <enumeration value="dB20"/>
    <enumeration value="dB22"/>
    <enumeration value="dB24"/>
  </restriction>
</simpleType>
<simpleType name="ResponseWindowSizeEnumType">
  <restriction base="string">
    <enumeration value="sf2"/>
    <enumeration value="sf3"/>
    <enumeration value="sf4"/>
    <enumeration value="sf5"/>
    <enumeration value="sf6"/>
    <enumeration value="sf7"/>
    <enumeration value="sf8"/>
    <enumeration value="sf10"/>
  </restriction>
</simpleType>
<simpleType name="SizeOfRAPreambleGroupAEnumType">
  <restriction base="string">
    <enumeration value="n4"/>
    <enumeration value="n8"/>
    <enumeration value="n12"/>
    <enumeration value="n16"/>
    <enumeration value="n20"/>
    <enumeration value="n24"/>
    <enumeration value="n28"/>
    <enumeration value="n32"/>
    <enumeration value="n36"/>
    <enumeration value="n40"/>
    <enumeration value="n44"/>
    <enumeration value="n48"/>
    <enumeration value="n52"/>
    <enumeration value="n56"/>
    <enumeration value="n60"/>
  </restriction>
</simpleType>
<simpleType name="TimeToTriggerEUltraEnumType">
  <restriction base="string">
    <enumeration value="ms0"/>
    <enumeration value="ms40"/>
    <enumeration value="ms64"/>
    <enumeration value="ms80"/>
  </restriction>
</simpleType>

```

```

    <enumeration value="ms100"/>
    <enumeration value="ms128"/>
    <enumeration value="ms160"/>
    <enumeration value="ms256"/>
    <enumeration value="ms320"/>
    <enumeration value="ms480"/>
    <enumeration value="ms512"/>
    <enumeration value="ms640"/>
    <enumeration value="ms1024"/>
    <enumeration value="ms1280"/>
    <enumeration value="ms2560"/>
    <enumeration value="ms5120"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdRsrpRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="97"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdRsrqRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="34"/>
  </restriction>
</simpleType>
<simpleType name="OffsetRangeType">
  <restriction base="short">
    <minInclusive value="-30"/>
    <maxInclusive value="30"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdUtraRscpRangeType">
  <restriction base="short">
    <minInclusive value="-5"/>
    <maxInclusive value="91"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdUtraEcN0RangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="49"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdGeranRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdCDMA2000RangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="CommonChannelPowerOffsetRangeType">
  <restriction base="short">
    <minInclusive value="-350"/>
    <maxInclusive value="150"/>
  </restriction>
</simpleType>
<simpleType name="ConfigurationIndexRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="HysteresisRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="30"/>
  </restriction>
</simpleType>
<simpleType name="PMaxRangeType">
  <restriction base="short">
    <minInclusive value="-30"/>
    <maxInclusive value="33"/>
  </restriction>

```

```

</restriction>
</simpleType>
<simpleType name="QOffsetRangeType">
  <restriction base="short">
    <minInclusive value="-15"/>
    <maxInclusive value="15"/>
  </restriction>
</simpleType>
<simpleType name="QQualMinUtraRangeType">
  <restriction base="short">
    <minInclusive value="-24"/>
    <maxInclusive value="0"/>
  </restriction>
</simpleType>
<simpleType name="QRxLevMinEUtraRangeType">
  <restriction base="short">
    <minInclusive value="-77"/>
    <maxInclusive value="-22"/>
  </restriction>
</simpleType>
<simpleType name="QRxLevMinGeranRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="QRxLevMinUtraRangeType">
  <restriction base="short">
    <minInclusive value="-60"/>
    <maxInclusive value="-13"/>
  </restriction>
</simpleType>
<simpleType name="RootSequenceIndexRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="837"/>
  </restriction>
</simpleType>
<simpleType name="SIntraSearchRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="31"/>
  </restriction>
</simpleType>
<simpleType name="TReselectionRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="7"/>
  </restriction>
</simpleType>
<simpleType name="TStoreUeContextRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="1023"/>
  </restriction>
</simpleType>

<complexType name="TceIDMappingInfo">
  <sequence>
    <element name="tceID" type="short"/>
    <element name="tceIPAddr" type="string"/>
  </sequence>
</complexType>
<complexType name="TceIDMappingInfoList">
  <sequence>
    <element name="tceIDMappingInfo" type="en:TceIDMappingInfo" minOccurs="0"/>
  </sequence>
</complexType>
<simpleType name="cellOutageCompensationState">
  <restriction base="string">
    <enumeration value="cOCAActivating"/>
    <enumeration value="cOCAActive"/>
    <enumeration value="cOCDeactivating"/>
    <enumeration value="cOCDeactive"/>
  </restriction>
</simpleType>
<complexType name="cellOutageCompensationStatus">
  <sequence>

```

```

    <element name="cellOutageCompensationState" type="en:cellOutageCompensationState"/>
  <element name="errorList" type="xn:dnList"/>
</sequence>
</complexType>
<element name="CellOutageCompensationInformation">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes">
            <complexType>
              <all>
                <element name="cellOutageCompensationStatus"
                  type="en:cellOutageCompensationStatus"/>
                <element name="isCOCAAllowed" type="boolean"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="EUTranCellNMCentralizedSON">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes">
            <complexType>
              <all>
                <element name="a1ThresholdRsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                <element name="a1ThresholdRsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                <element name="a2ThresholdRsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                <element name="a2ThresholdRsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                <element name="a3Offset" type="en:OffsetRangeType" minOccurs="0"/>
                <element name="a4ThresholdRsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                <element name="a4ThresholdRsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                <element name="a5Threshold1Rsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                <element name="a5Threshold1Rsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>

                <element name="b1ThresholdUtraRscp" type="en:ThresholdUtraRscpRangeType"
minOccurs="0"/>

                <element name="b1ThresholdUtraEcN0" type="en:ThresholdUtraEcN0RangeType"
minOccurs="0"/>

                <element name="b1ThresholdGeran" type="en:ThresholdGeranRangeType" minOccurs="0"/>
                <element name="b1ThresholdCdma2000" type="en:ThresholdCDMA2000RangeType"
minOccurs="0"/>

                <element name="b2Threshold1Rsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                <element name="b2Threshold1Rsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                <element name="b2Threshold2UtraRscp" type="en:ThresholdUtraRscpRangeType"
minOccurs="0"/>

                <element name="b2Threshold2UtraEcN0" type="en:ThresholdUtraEcN0RangeType"
minOccurs="0"/>

                <element name="b2Threshold2Geran" type="en:ThresholdGeranRangeType"
minOccurs="0"/>

                <element name="b2Threshold2Cdma2000" type="en:ThresholdCDMA2000RangeType"
minOccurs="0"/>

                <element name="commonChannelPowerOffset"
type="en:CommonChannelPowerOffsetRangeType" minOccurs="0"/>
                <element name="configurationIndex" type="en:ConfigurationIndexRangeType"
minOccurs="0"/>

                <element name="contentionResolutionTimer"
type="en:ContentionResolutionTimerEnumType" minOccurs="0"/>
                <element name="hysteresisEutraA1" type="en:HysteresisRangeType" minOccurs="0"/>
                <element name="hysteresisEutraA2" type="en:HysteresisRangeType" minOccurs="0"/>
                <element name="hysteresisEutraA3" type="en:HysteresisRangeType" minOccurs="0"/>
                <element name="hysteresisEutraA4" type="en:HysteresisRangeType" minOccurs="0"/>
                <element name="hysteresisEutraA5" type="en:HysteresisRangeType" minOccurs="0"/>
                <element name="hysteresisIratB1" type="en:HysteresisRangeType" minOccurs="0"/>
                <element name="hysteresisIratB2" type="en:HysteresisRangeType" minOccurs="0"/>
                <element name="numberOfRaPreambles" type="en:NumberOfRaPreamblesEnumType"
minOccurs="0"/>

                <element name="preambleInitialReceivedTargetPower"
type="en:PreambleInitialReceivedTargetPowerEnumType" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```



```

minOccurs="0"/>
    <element name="preambleTransMax" type="en:PreambleTransMaxEnumType"
    <element name="pMax" type="en:PMaxRangeType" minOccurs="0"/>
    <element name="powerRampingStep" type="en:PowerRampingStepEnumType"
minOccurs="0"/>
    <element name="qHyst" type="en:PreambleInitialReceivedTargetPowerEnumType"
minOccurs="0"/>
    <element name="qOffsetUtra" type="en:QOffsetRangeType" minOccurs="0"/>
    <element name="qOffsetGeran" type="en:QOffsetRangeType" minOccurs="0"/>
    <element name="qOffsetCdma2000" type="en:QOffsetRangeType" minOccurs="0"/>
    <element name="qQualMinUtra" type="en:QQualMinUtraRangeType" minOccurs="0"/>
    <element name="qRxLevMinEUtraSib1" type="en:QRxLevMinEUtraRangeType"
minOccurs="0"/>
    <element name="qRxLevMinEUtraSib3" type="en:QRxLevMinEUtraRangeType"
minOccurs="0"/>
    <element name="qRxLevMinGeran" type="en:QRxLevMinGeranRangeType" minOccurs="0"/>
    <element name="qRxLevMinUtra" type="en:QRxLevMinUtraRangeType" minOccurs="0"/>
    <element name="responseWindowSize" type="en:ResponseWindowSizeEnumType"
minOccurs="0"/>
    <element name="rootSequenceIndex" type="en:RootSequenceIndexRangeType"
minOccurs="0"/>
    <element name="sIntraSearch" type="en:SIntraSearchRangeType" minOccurs="0"/>
    <element name="sizeOfRAPreamblesGroupA" type="en:SizeOfRAPreambleGroupAEnumType"
minOccurs="0"/>
    <element name="timeToTriggerEutraA1" type="en:TimeToTriggerEutraEnumType"
minOccurs="0"/>
    <element name="timeToTriggerEutraA2" type="en:TimeToTriggerEutraEnumType"
minOccurs="0"/>
    <element name="timeToTriggerEutraA3" type="en:TimeToTriggerEutraEnumType"
minOccurs="0"/>
    <element name="timeToTriggerEutraA4" type="en:TimeToTriggerEutraEnumType"
minOccurs="0"/>
    <element name="timeToTriggerEutraA5" type="en:TimeToTriggerEutraEnumType"
minOccurs="0"/>
    <element name="timeToTriggerIratB1" type="en:TimeToTriggerEutraEnumType"
minOccurs="0"/>
    <element name="timeToTriggerIratB2" type="en:TimeToTriggerEutraEnumType"
minOccurs="0"/>
    <element name="tReselectionCdma2000" type="en:TReselectionRangeType"
minOccurs="0"/>
    <element name="tReselectionEutra" type="en:TReselectionRangeType" minOccurs="0"/>
    <element name="tReselectionGeran" type="en:TReselectionRangeType" minOccurs="0"/>
    <element name="tReselectionUtra" type="en:TReselectionRangeType" minOccurs="0"/>
    <element name="tStoreUeContext" type="en:TStoreUeContextRangeType" minOccurs="0"/>
    </all>
  </complexType>
</element>
</sequence>
</extension>
</complexContent>
</complexType>
</element>
<element name="ENBFunction" substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string"/>
                <element name="enbId" type="en:EnbId" minOccurs="0"/>
                <element name="x2BlackList" type="xn:dnList" minOccurs="0"/>
                <element name="x2WhiteList" type="xn:dnList" minOccurs="0"/>
                <element name="x2H0BlackList" type="xn:dnList" minOccurs="0"/>
                <element name="x2IpAddressList" type="string" minOccurs="0"/>
                <element name="tceIDMappingInfoList" type="en:TceIDMappingInfoList"
minOccurs="0"/>
                <!-- linkList attribute is to be added when defined in the IS -->
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:EUTranCellFDD"/>
            <element ref="en:EUTranCellTDD"/>
            <element ref="epc:EP_RP_EPS"/>
            <element ref="en:ENBFunctionOptionallyContainedNrmClass"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>

```

```

        <element ref="en:DeNBCapability"/>
        <element ref="xn:VsDataContainer"/>
    </choice>
    <choice minOccurs="0" maxOccurs="1">
        <element ref="sp:ESPolicies"/>
    </choice>
</sequence>
</extension>
</complexContent>
</complexType>
</element>
<element name="RNFunction" substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
    <complexType>
        <complexContent>
            <extension base="xn:NrmClass">
                <sequence>
                    <element name="attributes" minOccurs="0">
                        <complexType>
                            <all>
                                <element name="userLabel" type="string"/>
                                <element name="servingCell" type="xn:dn"/>
                            </all>
                        </complexType>
                    </element>
                    <choice minOccurs="0" maxOccurs="unbounded">
                        <element ref="epc:EP_RP_EPS"/>
                        <element ref="en:RNFunctionOptionallyContainedNrmClass"/>
                        <element ref="xn:VsDataContainer"/>
                    </choice>
                </sequence>
            </extension>
        </complexContent>
    </complexType>
</element>
<element name="DeNBCapability">
    <complexType>
        <complexContent>
            <extension base="xn:NrmClass">
                <sequence>
                    <element name="attributes" minOccurs="0">
                        <complexType>
                            <all>
                                <element name="userLabel" type="string"/>
                                <element name="servedRN" type="xn:dnList" minOccurs="0"/>
                                <element name="maxNbrRNAllowed" type="unsignedShort"/>
                            </all>
                        </complexType>
                    </element>
                </sequence>
            </extension>
        </complexContent>
    </complexType>
</element>
<element name="ExternalRNFunction"
substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
    <complexType>
        <complexContent>
            <extension base="xn:NrmClass">
                <sequence>
                    <element name="attributes" minOccurs="0">
                        <complexType>
                            <all>
                                <element name="userLabel" type="string"/>
                                <element name="candidateDeNBCells" type="en:EcgiList" minOccurs="0"/>
                            </all>
                        </complexType>
                    </element>
                    <choice minOccurs="0" maxOccurs="unbounded">
                        <element ref="epc:EP_RP_EPS"/>
                        <element ref="en:ExternalRNFunctionOptionallyContainedNrmClass"/>
                        <element ref="xn:VsDataContainer"/>
                    </choice>
                </sequence>
            </extension>
        </complexContent>
    </complexType>
</element>
<element name="ExternalENBFunction" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">

```

```

<complexType>
  <complexContent>
    <extension base="xn:NrmClass">
      <sequence>
        <element name="attributes" minOccurs="0">
          <complexType>
            <all>
              <element name="userLabel" type="string"/>
              <element name="enbId" type="en:EnbId" minOccurs="0"/>
              <!-- Attributes are to be added when defined in the IS -->
            </all>
          </complexType>
        </element>
        <choice minOccurs="0" maxOccurs="unbounded">
          <element ref="en:ExternalEUTranCellFDD"/>
          <element ref="en:ExternalEUTranCellTDD"/>
          <element ref="en:ExternalENBFunctionOptionallyContainedNrmClass"/>
          <element ref="xn:VsDataContainer"/>
        </choice>
      </sequence>
    </extension>
  </complexContent>
</complexType>
</element>
<element name="EUTranCellFDD">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <!-- Inherited attributes from EUTranGenericCell-->
                <element name="userLabel" type="string"/>
                <element name="cellLocalId" type="en:CellLocalId"/>
                <element name="cellSize" type="en:cellSize"/>
                <element name="pLMNIdList" type="en:PLMNIdList"/>
                <element name="tac" type="long"/>
                <element name="pci" type="en:Pci"/>
                <element name="pciList" type="en:PciList" minOccurs="0"/>
                <element name="maximumTransmissionPower" type="short"/>
                <element name="partOfSectorPower" type="short" minOccurs="0"/>
                <element name="referenceSignalPower" type="short"/>
                <element name="pb" type="short"/>
                <element name="relatedTmaList" type="xn:dnList" minOccurs="0"/>
                <element name="relatedAntennaList" type="xn:dnList" minOccurs="0"/>
                <element name="relatedSectorEquipment" type="xn:dn" minOccurs="0"/>
                <element name="operationalState" type="sm:operationalStateType" minOccurs="0"/>
                <element name="administrativeState" type="sm:administrativeStateType"
                  minOccurs="0"/>
                <element name="availabilityStatus" type="sm:availabilityStatusType"
                  minOccurs="0"/>
                <element name="allowedAccessClasses" type="en:allowedAccessClassesType"/>
                <element name="cellResvInfo" type="en:cellResvInfoType" minOccurs="0"/>
                <element name="isChangeForEnergySavingAllowed"
                  type="en:yesNoType" minOccurs="0"/>
                <!-- End of inherited attributes from EUTranGenericCell -->
                <element name="earfcnDl" type="short"/>
                <element name="earfcnUl" type="short"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:EUTranRelation"/>
            <element ref="en:Cdma2000Relation"/>
            <element ref="gn:GsmRelation"/>
            <element ref="un:UtranRelation"/>
            <element ref="en:EUTranCellFDDOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0" maxOccurs="1">
            <element ref="en:EnergySavingProperties"/>
            <element ref="sp:ESPolicies"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>

```

```

</element>
<element name="ExternalEUTranCellFDD"
substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <!-- Inherited attributes from ExternalEUTranGenericCell-->
                <element name="userLabel" type="string"/>
                <element name="pci" type="en:Pci"/>
                <element name="pLMNidList" type="en:PLMNidList"/>
                <element name="cellLocalId" type="en:CellLocalId"/>
                <element name="enbId" type="en:EnbId" minOccurs="0"/>
                <!-- End of inherited attributes from ExternalEUTranGenericCell -->
                <element name="earfcnDl" type="short"/>
                <element name="earfcnUl" type="short"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:ExternalEUTranCellFDDOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0">
            <element ref="en:CellOutageCompensationInformation"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="EUTranCellTDD">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <!-- Inherited attributes from EUTranGenericCell-->
                <element name="userLabel" type="string"/>
                <element name="cellLocalId" type="en:CellLocalId"/>
                <element name="cellSize" type="en:cellSize"/>
                <element name="pLMNidList" type="en:PLMNidList"/>
                <element name="tac" type="long"/>
                <element name="pci" type="en:Pci" />
                <element name="pciList" type="en:PciList" minOccurs="0"/>
                <element name="maximumTransmissionPower" type="short"/>
                <element name="partOfSectorPower" type="short" minOccurs="0"/>
                <element name="referenceSignalPower" type="short"/>
                <element name="pb" type="short"/>
                <element name="relatedTmaList" type="xn:dnList" minOccurs="0"/>
                <element name="relatedAntennaList" type="xn:dnList" minOccurs="0"/>
                <element name="relatedSectorEquipment" type="xn:dn" minOccurs="0"/>
                <element name="operationalState" type="sm:operationalStateType" minOccurs="0"/>
                <element name="administrativeState" type="sm:administrativeStateType"
minOccurs="0"/>
                <element name="availabilityStatus" type="sm:availabilityStatusType"
minOccurs="0"/>
                <element name="allowedAccessClasses" type="en:allowedAccessClassesType"/>
                <element name="cellResvInfo" type="en:cellResvInfoType" minOccurs="0"/>
                <element name="isChangeForEnergySavingAllowed"
type="en:yesNoType" minOccurs="0"/>
                <!-- End of inherited attributes from EUTranGenericCell -->
                <element name="earfcn" type="short"/>
                <element name="sfAssignment" type="short"/>
                <element name="specialSfPatterns" type="short"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:EUTranRelation"/>
            <element ref="en:Cdma2000Relation"/>
            <element ref="gn:GsmRelation"/>
            <element ref="un:UtranRelation"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```

        <element ref="en:EUTranCellTDDOptionallyContainedNrmClass"/>
        <element ref="xn:VsDataContainer"/>
    </choice>
    <choice minOccurs="0" maxOccurs="1">
        <element ref="en:EnergySavingProperties"/>
        <element ref="sp:ESPolicies"/>
    </choice>
    <choice minOccurs="0">
        <element ref="en:CellOutageCompensationInformation"/>
    </choice>
</sequence>
</extension>
</complexContent>
</complexType>
</element>
<element name="ExternalEUTranCellTDD"
substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
    <complexType>
        <complexContent>
            <extension base="xn:NrmClass">
                <sequence>
                    <element name="attributes" minOccurs="0">
                        <complexType>
                            <all>
                                <!-- Inherited attributes from ExternalEUTranGenericCell-->
                                <element name="userLabel" type="string"/>
                                <element name="pci" type="en:Pci"/>
                                <element name="pLMNIdList" type="en:PLMNIdList"/>
                                <element name="cellLocalId" type="en:CellLocalId"/>
                                <element name="enbId" type="en:EnbId" minOccurs="0"/>
                                <!-- End of inherited attributes from ExternalEUTranGenericCell -->
                                <element name="earfcn" type="short"/>
                            </all>
                        </complexType>
                    </element>
                    <choice minOccurs="0" maxOccurs="unbounded">
                        <element ref="en:ExternalEUTranCellTDDOptionallyContainedNrmClass"/>
                        <element ref="xn:VsDataContainer"/>
                    </choice>
                </sequence>
            </extension>
        </complexContent>
    </complexType>
</element>
<element name="EUTranRelation">
    <complexType>
        <complexContent>
            <extension base="xn:NrmClass">
                <sequence>
                    <element name="attributes" minOccurs="0">
                        <complexType>
                            <all>
                                <element name="tCI" type="long" minOccurs="0"/>
                                <element name="isRemoveAllowed" type="boolean" minOccurs="0"/>
                                <element name="isHOAllowed" type="boolean" minOccurs="0"/>
                                <element name="isICICInformationSendAllowed" type="boolean" minOccurs="0"/>
                                <element name="isLBAAllowed" type="boolean" minOccurs="0"/>
                                <element name="adjacentCell" type="xn:dn"/>
                                <element name="isEsCoveredBy" type="en:isEsCoveredByEnumType" minOccurs="0"/>
                                <element name="cellIndividualOffset" type="en:QOffsetEnumType" minOccurs="0"/>
                                <element name="qOffset" type="en:QOffsetEnumType" minOccurs="0"/>
                            </all>
                        </complexType>
                    </element>
                    <choice minOccurs="0" maxOccurs="unbounded">
                        <element ref="en:EUTranRelationOptionallyContainedNrmClass"/>
                        <element ref="xn:VsDataContainer"/>
                        <element ref="en:EUTranRelationSon"/>
                    </choice>
                </sequence>
            </extension>
        </complexContent>
    </complexType>
</element>
<element name="Cdma2000Relation">
    <complexType>
        <complexContent>
            <extension base="xn:NrmClass">

```

```

<sequence>
  <element name="attributes" minOccurs="0">
    <complexType>
      <all>
        <element name="adjacentSector" type="xn:dn"/>
      </all>
    </complexType>
  </element>
  <choice minOccurs="0" maxOccurs="unbounded">
    <element ref="en:Cdma2000RelationOptionallyContainedNrmClass"/>
    <element ref="xn:VsDataContainer"/>
  </choice>
</sequence>
</extension>
</complexContent>
</complexType>
</element>
<element name="Link_ENB_ENB" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <!-- Inherited attributes from Link -->
                <element name="aEnd" type="xn:dn"/>
                <element name="linkType" type="xn:linkType" minOccurs="0"/>
                <element name="protocolName" type="string" minOccurs="0"/>
                <element name="protocolVersion" type="string" minOccurs="0"/>
                <element name="userLabel" type="string"/>
                <element name="zEnd" type="xn:dn"/>
                <!-- End of inherited attributes from Link -->
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:Link_ENB_ENBOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="MCEFunction" substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string" minOccurs="0"/>
                <!-- Attributes are to be added when defined in the IS -->
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:MCEFunctionOptionallyContainedNrmClass"/>
            <element ref="en:MBSFNArea"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="MBSFNArea" >
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="mbsfnAreaId" type="en:mbsfnAreaIdType" minOccurs="0"/>
                <element name="cellIdList" type="xn:dnList" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```

        </all>
      </complexType>
    </element>
    <choice minOccurs="0" maxOccurs="unbounded">
      <element ref="en:MBSFNAreaOptionallyContainedNrmClass"/>
      <element ref="xn:VsDataContainer"/>
    </choice>
  </sequence>
</extension>
</complexContent>
</complexType>
</element>
<element name="Link_MCE_ENB" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <!-- Inherited attributes from Link -->
                <element name="aEnd" type="xn:dn" minOccurs="0"/>
                <element name="linkType" type="xn:linkType" minOccurs="0"/>
                <element name="protocolName" type="string" minOccurs="0"/>
                <element name="protocolVersion" type="string" minOccurs="0"/>
                <element name="userLabel" type="string" minOccurs="0"/>
                <element name="zEnd" type="xn:dn" minOccurs="0"/>
                <!-- End of inherited attributes from Link -->
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:Link_MCE_ENBOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="Link_MCE_MME" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <!-- Inherited attributes from Link -->
                <element name="aEnd" type="xn:dn" minOccurs="0"/>
                <element name="linkType" type="xn:linkType" minOccurs="0"/>
                <element name="protocolName" type="string" minOccurs="0"/>
                <element name="protocolVersion" type="string" minOccurs="0"/>
                <element name="userLabel" type="string" minOccurs="0"/>
                <element name="zEnd" type="xn:dn" minOccurs="0"/>
                <!-- End of inherited attributes from Link -->
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:Link_MCE_MMEOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="QciDscpMapping"
  substitutionGroup="en:RNFunctionOptionallyContainedNrmClass"
>
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">

```

```

    <complexType>
      <all>
        <element name="userLabel" type="string"/>
        <element name="QciDscpMappingList" type="en:QciDscpMappingListType"/>
      </all>
    </complexType>
  </element>
  <choice minOccurs="0" maxOccurs="unbounded">
    <element ref="xn:VsDataContainer"/>
  </choice>
</sequence>
</extension>
</complexContent>
</complexType>
</element>

<element name="EnergySavingProperties">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="energySavingState" type="en:energySavingStateEnumType"/>
                <element name="energySavingControl" type="en:energySavingControlEnumType"
                  minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<!-- The element definition for EP_RP_EPS is available through
the epcNrm.xsd (3GPP TS 32.756), by using epc:EP_RP_EPS -->
<element name="ENBFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="ExternalENBFunctionOptionallyContainedNrmClass" type="xn:NrmClass"
abstract="true"/>
<element name="EUTranCellFDDOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="ExternalEUTranCellFDDOptionallyContainedNrmClass" type="xn:NrmClass"
abstract="true"/>
<element name="EUTranCellTDDOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="ExternalEUTranCellTDDOptionallyContainedNrmClass" type="xn:NrmClass"
abstract="true"/>
<element name="EUTranRelationOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="Cdma2000RelationOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="Link_ENB_ENBOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="MCEFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="Link_MCE_ENBOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="Link_MCE_MMEOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="MBSFNAreaOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="RNFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
<element name="ExternalRNFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
</schema>

```


Annex C (informative): Change history

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|---|--------|--------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 05-2010 | SA-48 | SP-100281 | -- | -- | Presentation to SA for information and approval | --- | 1.0.0 |
| 06-2010 | SA-48 | -- | -- | -- | Publication | 1.0.0 | 10.0.0 |
| 09-2010 | SA-49 | SP-100489 | 001 | -- | Addition of eNBId and adjustment of cellIdentity | 10.0.0 | 10.1.0 |
| 09-2010 | SA-49 | SP-100489 | 002 | -- | Add IOC MCEFunction and MBSFNArea | 10.0.0 | 10.1.0 |
| 09-2010 | SA-49 | SP-100487 | 003 | -- | Align with IS - Remove cellType | 10.0.0 | 10.1.0 |
| 09-2010 | SA-49 | SP-100488 | 004 | -- | Align with IS - Add attributes for association roles for Radio Equipment view | 10.0.0 | 10.1.0 |
| 09-2010 | SA-49 | SP-100489 | 005 | -- | Correction of EUTRAN NRM IRP XML Definitions | 10.0.0 | 10.1.0 |
| 12-2010 | SA-50 | SP-100833 | 006 | 1 | Correcting the PLMNID definition of XML schema - Align with 23.003 and 32.762 IS | 10.1.0 | 10.2.0 |
| 12-2010 | SA-50 | SP-100833 | 007 | 1 | Adding Relay and Donor eNodeB NRM SS - Align with RAN2 TS 36.300 | 10.1.0 | 10.2.0 |
| 12-2010 | SA-50 | SP-100833 | 008 | 1 | Add an attribute to SS EUTranGenericCell to set allowed access class per cell | 10.1.0 | 10.2.0 |
| 03-2011 | SA-51 | SP-110095 | 009 | 2 | Add candidateDeNBCells attribute to RNFunction in E-UTRAN Network Resource Model IRP Solution Set definitions | 10.2.0 | 10.3.0 |
| 03-2011 | SA-51 | SP-110095 | 010 | 3 | Add QciDscpMapping IOC | 10.2.0 | 10.3.0 |
| 03-2011 | SA-51 | SP-110100 | 013 | 3 | Add Energy Saving Management (ESM) items for Itf-N - Align with 32.762 E-UTRAN NRM IRP IS and 32.551 ESM Concepts and requirements | 10.2.0 | 10.3.0 |
| 03-2011 | SA-51 | SP-110100 | 013 | 4 | Add Energy Saving Management (ESM) items for Itf-N - Align with 32.762, 32.551 NOTE: MCC modification of "toBeNotEnergySaving" instead of "NotToBeEnergySaving" to align with 32.762 | 10.2.0 | 10.3.0 |
| 03-2011 | SA-51 | SP-110096 | 016 | 1 | Removing SectorEquipmentFunction - Align with EUTRAN NRM IS | 10.2.0 | 10.3.0 |
| 03-2011 | SA-51 | SP-110095 | 018 | 1 | Align with 32.762 - Correct Relay and Donor eNodeB model in E-UTRAN Network Resource Model IRP | 10.2.0 | 10.3.0 |
| 03-2011 | SA-51 | SP-110102 | 020 | 1 | Adding TCE address and TCE ID mapping information to ENBFunction | 10.2.0 | 10.3.0 |
| 03-2011 | SA-51 | SP-110097 | 021 | 1 | Add a new object class to hold information about Cell Outage Compensation (COC) and report COC activities - Align with 32.762 | 10.2.0 | 10.3.0 |
| 06-2011 | SA-52 | SP-110285 | 023 | - | Fix syntax faults in eUTRAN NRM IRP | 10.3.0 | 10.4.0 |
| 06-2011 | SA-52 | SP-110284 | 025 | - | Introduction of cellIndividualOffset in EUTranRelation | 10.3.0 | 10.4.0 |
| 06-2011 | SA-52 | SP-110365 | 026 | - | Add stage 3 for new IOC EUTranCellINMCentralizedSON named by EUTranGenericCell and add attributes to EUTranRelation IOC | 10.3.0 | 10.4.0 |
| 09-2011 | SA-53 | SP-110526 | 027 | 1 | Corrections on some data type definitions | 10.4.0 | 10.5.0 |
| 09-2011 | SA-53 | SP-110537 | 029 | 1 | Adding TCE address and TCE ID mapping information to ENBFunction | 10.4.0 | 10.5.0 |

History

| Document history | | |
|-------------------------|--------------|-------------|
| V10.3.0 | April 2011 | Publication |
| V10.4.0 | June 2011 | Publication |
| V10.5.0 | October 2011 | Publication |
| | | |
| | | |