

ETSI TS 133 511 V16.7.0 (2021-08)



**5G;  
Security Assurance Specification (SCAS)  
for the next generation Node B (gNodeB)  
network product class  
(3GPP TS 33.511 version 16.7.0 Release 16)**



---

**Reference**

RTS/TSGS-0333511vg70

---

**Keywords**

5G,SECURITY

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope .....	6
2 References .....	6
3 Definitions of terms and abbreviations.....	6
3.1 Terms.....	6
3.2 Abbreviations .....	6
4 gNodeB-specific security requirements and related test cases.....	7
4.1 Introduction .....	7
4.2 gNodeB-specific security functional adaptations of requirements and related test cases.....	7
4.2.1 Introduction.....	7
4.2.2 Security functional requirements on the gNodeB deriving from 3GPP specifications and related test cases.....	7
4.2.2.1 Security functional requirements on the gNodeB deriving from 3GPP specifications – TS 33.501 [2].....	7
4.2.2.1.1 Integrity protection of RRC-signalling .....	7
4.2.2.1.2 Integrity protection of user data between the UE and the gNB .....	8
4.2.2.1.3 VOID .....	8
4.2.2.1.4 RRC integrity check failure.....	8
4.2.2.1.5 UP integrity check failure.....	9
4.2.2.1.6 Ciphering of RRC-signalling.....	10
4.2.2.1.7 Ciphering of user data between the UE and the gNB .....	10
4.2.2.1.8 Replay protection of user data between the UE and the gNB.....	11
4.2.2.1.9 Replay protection of RRC-signalling .....	12
4.2.2.1.10 Ciphering of user data based on the security policy sent by the SMF .....	12
4.2.2.1.11 Integrity of user data based on the security policy sent by the SMF .....	13
4.2.2.1.12 AS algorithms selection.....	14
4.2.2.1.13 Key refresh at the gNB .....	15
4.2.2.1.14 Bidding down prevention in Xn-handovers.....	15
4.2.2.1.15 AS protection algorithm selection in gNB change .....	16
4.2.2.1.16 Control plane data confidentiality protection over N2/Xn interface.....	16
4.2.2.1.17 Control plane data integrity protection over N2/Xn interface .....	16
4.2.2.1.18 Key update at the gNB on dual connectivity .....	16
4.2.3 Technical Baseline .....	17
4.2.3.1 Introduction.....	17
4.2.3.2 Protecting data and information.....	17
4.2.3.2.1 Protecting data and information – general .....	17
4.2.3.2.2 Protecting data and information – unauthorized viewing .....	17
4.2.3.2.3 Protecting data and information in storage .....	17
4.2.3.2.4 Protecting data and information in transfer.....	17
4.2.3.2.5 Logging access to personal data .....	18
4.2.3.3 Protecting availability and integrity.....	18
4.2.3.4 Authentication and authorization.....	18
4.2.3.4.1 Authentication attributes.....	18
4.2.3.5 Protecting sessions .....	18
4.2.3.6 Logging .....	18
4.2.4 Operating systems.....	18
4.2.5 Web servers .....	18
4.2.6 Network devices .....	18
4.2.6.1 Protection of data and information.....	18
4.2.6.2 Protecting availability and integrity .....	18
4.2.6.2.1 Packet filtering.....	18

4.2.6.2.2	Interface robustness requirements .....	18
4.2.6.2.3	GTP-C Filtering .....	19
4.2.6.2.4	GTP-U Filtering .....	19
4.2.7	Void .....	19
4.3	gNodeB-specific adaptations of hardening requirements and related test cases. ....	19
4.3.1	Introduction.....	19
4.3.2	Technical Baseline .....	19
4.3.3	Operating Systems .....	19
4.3.4	Web Servers.....	19
4.3.5	Network Devices .....	19
4.3.6	Network Functions in service-based architecture .....	19
4.4	gNodeB-specific adaptations of basic vulnerability testing requirements and related test cases .....	19
<b>Annex A (informative): Change history .....</b>		<b>20</b>
History .....		21

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document contains objectives, requirements and test cases that are specific to the gNB network product class. It refers to the Catalogue of General Security Assurance Requirements and formulates specific adaptations of the requirements and test cases given there, as well as specifying requirements and test cases unique to the gNB network product class.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 33.501 (Release 15): "Security architecture and procedures for 5G system".
- [3] 3GPP TS 33.117: "Catalogue of general security assurance requirements".
- [4] 3GPP TS 33.216: "Security Assurance Specification (SCAS) for the evolved Node B (eNB) network product class".
- [5] 3GPP TR 33.926: "Security Assurance Specification (SCAS) threats and critical assets in 3GPP network product classes".
- [6] 3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification".

---

# 3 Definitions of terms and abbreviations

## 3.1 Terms

For the purposes of the present document, the terms given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

## 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

5GC	5G Core Network
AMF	Access and Mobility Management Function
gNB	NR Node B
NG	Next Generation
NG-RAN	5G Radio Access Network
SMF	Session Management Function

## 4 gNodeB-specific security requirements and related test cases

### 4.1 Introduction

gNB specific security requirements include both requirements derived from gNB-specific security functional requirements as well as security requirements derived from threats specific to gNB as described in TR 33.926 [5]. Generic security requirements and test cases common to other network product classes have been captured in TS 33.117 [3] and are not repeated in the present document.

### 4.2 gNodeB-specific security functional adaptations of requirements and related test cases

#### 4.2.1 Introduction

Present clause contains gNB-specific security functional adaptations of requirements and related test cases.

#### 4.2.2 Security functional requirements on the gNodeB deriving from 3GPP specifications and related test cases

##### 4.2.2.1 Security functional requirements on the gNodeB deriving from 3GPP specifications – TS 33.501 [2]

###### 4.2.2.1.1 Integrity protection of RRC-signalling

*Requirement Name:* Integrity protection of RRC-signalling

*Requirement Reference:* TS 33.501 [2], clause 5.3.3

*Requirement Description:* "The gNB shall support integrity protection of RRC-signalling over the NG RAN air interface" as specified in TS 33.501 [2], clause 5.3.3.

*Threat References:* TR 33.926 [5], clause D.2.2.2 – Control plane data integrity protection.

*Test Case:*

**Test Name:** TC\_CP\_DATA\_INT\_RRC-SIGN\_gNB

**Purpose:** To verify that the RRC-signalling data sent between UE and gNB over the NG RAN air interface are integrity protected.

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments. UE may be simulated.
- Tester shall have access to the integrity algorithm and the integrity protection keys.
- The tester can capture the message via the NG RAN air interface, or can capture the message at the UE.

**Execution Steps:**

1. The NIA0 is disabled at UE and gNB.
2. gNB sends AS SMC message to the UE, and UE responses AS SMP.
3. Check any RRC message sent by gNB after sending AS SMC and before UE enters CM-Idle state is integrity protected.

**Expected Results:**

Any RRC-signalling over the NG RAN air interface is integrity protected after gNB sending AS SMC.

**Expected format of evidence:**

Evidence suitable for the interface, e.g. Screenshot containing the operational results.

**4.2.2.1.2 Integrity protection of user data between the UE and the gNB**

*Requirement Name:* Integrity protection of user data between the UE and the gNB.

*Requirement Reference:* TS 33.501 [2], clause 5.3.3

*Requirement Description:* "The gNB shall support integrity protection of user data packets over the NG RAN air interface" as specified in TS 33.501 [2], clause 5.3.3.

NOTE: This requirement does not apply to the gNB that is used as a secondary node connecting to the EPC.

*Threat References:* TR 33.926 [5], clause D.2.2.4 – User plane data integrity protection.

**Test Case:**

**Test Name:** TC-UP-DATA-INT\_gNB

**Purpose:** To verify that the user data packets are integrity protected over the NG RAN air interface.

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments. UE may be simulated.
- Tester shall enable the user plane integrity protection and ensure NIA0 is not used.
- Tester shall have knowledge of integrity algorithm and integrity protection keys.
- The tester can capture the message via the NG RAN air interface, or can capture the message at the UE.

**Execution Steps:**

1. The NIA0 is disabled at UE and gNB.
2. gNB sends RRCConnectionReconfiguration with integrity protection indication "on".
3. Check any User data sent by gNB after sending RRCConnectionReconfiguration and before UE enters CM-Idle state is Integrity protected.

**Expected Results:**

Any user plane packets sent between UE and gNB over the NG RAN air interface after gNB sending RRCConnectionReconfiguration is integrity protected.

**Expected format of evidence:**

Evidence suitable for the interface e.g. Screenshot containing the operational results.

**4.2.2.1.3 VOID****4.2.2.1.4 RRC integrity check failure**

*Requirement Name:* RRC integrity check failure

*Requirement Reference:* TS 33.501 [2], clause 6.5.1

*Requirement Description:* "The RRC integrity checks shall be performed both in the ME and the gNB. In case failed integrity check (i.e. faulty or missing MAC-I) is detected after the start of integrity protection, the concerned message shall be discarded. This can happen on the gNB side or on the ME side." as specified in TS 33.501 [2], clause 6.5.1.

*Threat References:* TR 33.926 [4], clause D.2.2.2, Control plane data integrity protection

*Test Case:*

**Purpose:**

Verify that RRC integrity check failure is handled correctly by the gNB.

**Pre-Conditions:**

Test environment with a UE. The UE may be simulated. RRC integrity protection is activated at the gNB.

**Execution Steps**

- 1a) The UE sends a RRC message to the gNB without MAC-I; or
- 1b) The UE sends a RRC message to the gNB with a wrong MAC-I.
- 2b) The gNB verifies the integrity of the RRC message from the UE.

**Expected Results:**

The RRC message is discarded by the gNB after step 1a) or after step 2b).

**Expected format of evidence:**

Sample copies of the log files.

#### 4.2.2.1.5 UP integrity check failure

*Requirement Name:* UP integrity check failure

*Requirement Reference:* TS 33.501 [2], clause 6.6.4

*Requirement Description:* "If the gNB or the UE receives a PDCP PDU which fails integrity check with faulty or missing MAC-I after the start of integrity protection, the PDU shall be discarded." as specified in TS 33.501 [2], clause 6.6.4.

*Threat References:* TR 33.926 [4], clause D.2.2.4, User plane data integrity protection

*Test Case:*

**Purpose:**

Verify that UP integrity check failure is handled correctly by the gNB.

**Pre-Conditions:**

Test environment with a UE. The UE may be simulated. UP integrity protection is activated at the gNB.

**Execution Steps**

- 1a) The UE sends a PDCP PDU to the gNB without MAC-I; or
- 1b) The UE sends a PDCP PDU to the gNB with a wrong MAC-I.
- 2b) The gNB verifies the integrity of the PDCP PDU from the UE.

**Expected Results:**

The PDCP PDU is discarded by the gNB after step 1a) or after step 2b).

**Expected format of evidence:**

Evidence suitable for the interface e.g. Screenshot containing the operational results.

#### 4.2.2.1.6 Cipherring of RRC-signalling

*Requirement Name:* Cipherring of RRC-signalling

*Requirement Reference:* TS 33.501 [2], clause 5.3.2

*Requirement Description:* "The gNB shall support cipherring of RRC-signalling over the NG RAN air interface" as specified in TS 33.501 [2], clause 5.3.2.

*Threat References:* TR 33.926 [5], clause D.2.2.1 – Control plane data confidentiality protection.

*Test Case:*

**Test Name:** TC-CP-DATA-CIP-RRC-SIGN\_gNB

**Purpose:** To verify that the RRC-signalling data sent between UE and gNB over the NG RAN air interface are confidentiality protected.

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments. The UE may be simulated.
- The tester shall have access to the NG RAN air interface or can capture the message at the UE.

**Execution Steps:**

1. The UE sends a Registraton Request to the AMF.
  2. The AMF sends a KgNB and the UE security capability to the gNB.
  3. The gNB selects an algorithm and sends AS SMC to the UE.
  4. The gNB receive AS SMP from the UE.
- Expected Results:**  
Control plane packets sent to the UE after the gNB sends AS SMC is ciphpered.

**Expected format of evidence:**

Evidence suitable for the interface, e.g. Screenshot containing the operational results.

#### 4.2.2.1.7 Cipherring of user data between the UE and the gNB

*Requirement Name:* Cipherring of user data between the UE and the gNB

*Requirement Reference:* TS 33.501 [2], clause 5.3.2

*Requirement Description:* "The gNB shall provide cipherring of user data packets between the UE and the gNB on NG RAN air interface" as specified in TS 33.501 [2], clause 5.3.2.

*Threat References:* TR 33.926 [5], clause D.2.2.3 – User plane data confidentiality protection at gNB

*Test Case:*

**Test Name:** TC-UP-DATA-CIP\_gNB

**Purpose:** To verify that the user data packets are confidentiality protected over the NG RAN air interface.

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments. The UE may be simulated.
- The tester shall have access to the NG RAN air interface or can capture the message at the UE.

**Execution Steps:**

1. The UE sends PDU session establishment Request to the SMF.
2. The SMF sends a UP security policy with UP cipherring required or preferred to the gNB.

3. The gNB sends RRCConnectionReconfiguration with ciphering protection indication "on".
4. Check any user data sent by the gNB after sending RRCConnectionReconfiguration and before the UE enters into CM-Idle state.

**Expected Results:**

The user plane packets sent to the UE after the gNB sends RRCConnectionReconfiguration is confidentiality protected.

**Expected format of evidence:**

Evidence suitable for the interface e.g. Screenshot containing the operational results.

#### 4.2.2.1.8 Replay protection of user data between the UE and the gNB

*Requirement Name:* Replay protection of user data between the UE and the gNB.

*Requirement Reference:* TS 33.501 [2], clause 5.3.3

*Requirement Description:* "the gNB shall support integrity protection and replay protection of user data between the UE and the gNB" as specified in TS 33.501 [2], clause 5.3.3.

*Threat References:* TR 33.926 [5], clause D.2.2.4 – User plane data integrity protection.

**Test Case:**

**Test Name:** TC-UP-DATA-REPLAY\_gNB

**Purpose:** To verify that the user data packets are replay protected over the NG RAN air interface.

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments. The UE may be simulated.
- The tester shall have access to the NG RAN air interface.
- The tester shall active the user plane integrity protection of the RRC-signalling packets.

**Execution Steps:**

1. The tester shall capture the user plane data sent between UE and gNB using any network analyser over the NG RAN air interface.
2. Tester shall filter user plane data packets sent between UE and gNB.
3. Tester shall replay the captured user plane packets or shall use any packet crafting tool to create a user plane packet similar to the captured user plane packet and replay to the gNB.
4. Tester shall check whether the replayed user plane packets were processed by the gNB by capturing over NG RAN air interface to see if any corresponding response message is received from the gNB.
5. Tester shall confirm that gNB provides replay protection by dropping/ignoring the replayed packet if no corresponding response is received from the gNB to the replayed packet.
6. Tester shall verify from the result that if the replayed user plane packets are not accepted by gNB, the NG RAN air interface is replay protected.

**Expected Results:**

The user plane packets sent between the UE and gNB over the NG air interface is replay protected.

**Expected format of evidence:**

Evidence suitable for the interface, e.g. Screenshot containing the operational results.

#### 4.2.2.1.9 Replay protection of RRC-signalling

*Requirement Name:* Replay protection of RRC-signalling.

*Requirement Reference:* TS 33.501 [2], clause 5.3.3

*Requirement Description:* "The gNB shall support integrity protection and replay protection of RRC-signalling " as specified in TS 33.501 [2], clause 5.3.3.

*Threat References:* TR 33.926 [5], clause D.2.2.2 – Control plane data integrity protection.

*Test Case:*

**Test Name:** TC-UP-DATA-RRC-REPLAY\_gNB

**Purpose:** To verify the replay protection of RRC-signalling between UE and gNB over the NG RAN air interface.

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments.
- Tester shall have knowledge of the integrity algorithm and the corresponding protection keys.
- The tester shall have access to the NG RANs air interface.
- The tester shall active the user plane integrity protection of the user data packets.

**Execution Steps:**

1. The tester shall capture the data sent between UE and the gNB using any network analyser over the NG RAN air interface.
2. Tester shall filter RRC signalling packets.
3. Tester shall check for the RRC SQN of the filtered RRC signalling packets and shall use any packet crafting tool to create RRC signalling packets similar to the captured packets or the tester shall replay the captured RRC uplink packet to the gNB to perform the replay attack over gNB.
4. Tester shall check whether the replayed RRC signalling packets were processed by the gNB or not, by capturing over NG RAN air interface to see if any corresponding response message is received from the gNB.
5. Tester shall confirm that gNB provides replay protection by dropping/ignoring the replayed packet if no corresponding response is sent by the gNB to the replayed packet.

**Expected Results:**

The RRC signalling over the NG RAN air interface is replay protected.

**Expected format of evidence:**

Evidence suitable for the interface, e.g. Screenshot containing the operational results.

#### 4.2.2.1.10 Cipherng of user data based on the security policy sent by the SMF

*Requirement Name:* Cipherng of user data based on the security policy sent by the SMF

*Requirement Reference:* TS 33.501 [2], clause 5.3.2

*Requirement Description:* "The gNB shall activate cipherng of user data based on the security policy sent by the SMF" as specified in TS 33.501 [2], clause 5.3.2.

*Threat References:* TR 33.926 [5], clause D.2.2.8 – Security Policy Enforcement.

*Test Case:*

**Test Name:** TC-UP-DATA-CIP-SMF

**Purpose:** To verify that the user data packets are confidentiality protected based on the security policy sent by the SMF via AMF

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments. The UE and the 5GC may be simulated.
- The tester shall have access to the NG RAN air interface.
- The tester shall have knowledge of the RRC and UP ciphering algorithm and protection keys.
- RRC ciphering is already activated at the gNB.

**Execution Steps:**

1. The tester triggers PDU session establishment procedure by sending PDU session establishment request message.
2. Tester shall trigger the SMF to send the UP security policy with ciphering protection "required" or "not needed" to the gNB.
3. The tester shall capture the RRC connection reconfiguration procedure between gNB to UE over NG RAN air interface. And filter the RRC connection reconfiguration message sent by gNB to UE.
4. The tester shall decrypt the RRC connection Reconfiguration message and retrieve the UP ciphering protection indication presenting in the decrypted message.
5. The tester shall verify if the UP security policy received at gNB is same as the UP ciphering protection indication notified by the gNB to the UE in the RRC connection Reconfiguration message.
6. Tester shall capture the RRC connection Reconfiguration complete message sent between UE and gNB.
- 6a. Tester shall capture the user plane data sent between UE and gNB using any network analyser.
7. Tester shall check that the captured UP data is activated/de-activated according to the UP security policy.

**Expected Results:**

When the received UP cipher protection indication is set to "required", the captured user plane data appear to be garbled (i.e. no longer plaintext) and the user plane packets are confidentiality protected based on the UP security policy sent by the SMF.

When the received UP cipher protection indication is set to "not needed", the captured user plane data appear to be plaintext and the user plane packets are not confidentiality protected based on the UP security policy sent by the SMF.

**Expected format of evidence:**

Evidence suitable for the interface, e.g. Screenshot containing the operational results.

#### 4.2.2.1.11 Integrity of user data based on the security policy sent by the SMF

*Requirement Name:* Integrity of user data based on the security policy sent by the SMF

*Requirement Reference:* TS 33.501 [2], clause 5.3.2

*Requirement Description:* "The gNB shall provide integrity protection of user data based on the security policy sent by the SMF" as specified in TS 33.501 [2], clause 5.3.2.

*Threat References:* TR 33.926 [5], clause D.2.2.8 – Security Policy Enforcement.

**Test Case:**

**Test Name:** TC-UP-DATA-INT-SMF

**Purpose:** To verify that the user data packets are integrity protected based on the security policy sent by the SMF.

**Pre-Condition:**

- The gNB network product shall be connected in emulated/real network environments. The UE and the 5GC may be simulated.
- The tester shall have access to the NG RAN air interface.
- The tester shall have knowledge of the integrity algorithm and protection keys.
- RRC integrity and cipher are already activated at the gNB.

**Execution Steps:**

1. The tester triggers PDU session establishment procedure by sending PDU session establishment request message.
2. Tester shall trigger the SMF to send the UP security policy with integrity protection is "required" or "not needed" to the gNB.
3. The tester shall capture the RRC connection reconfiguration message sent by gNB to UE over NG RAN air interface.
4. The tester shall decrypt the RRC connection reconfiguration message and retrieve the UP integrity protection indication presenting in the decrypted message.
5. Tester shall check whether UP integrity is enabled /disabled to verify if the UP security policy received at gNB is same as the UP integrity protection indication notified by the gNB to the UE in the RRC connection reconfiguration message.
6. Tester shall capture the user plane data sent between UE and gNB using any network analyser.
7. The tester shall check whether the user plane data packet contains a message authentication code.

**Expected Results:**

When the received UP integrity protection is set to "required", the user plane data packet contains a message authentication code and the user plane packets are integrity protected based on the security policy sent by the SMF.

When the received UP integrity protection is set to "not needed", the user plane data packet message authentication code is not present and the user plane packets are not integrity protected based on the security policy sent by the SMF.

**Expected format of evidence:**

Evidence suitable for the interface, e.g. Screenshot containing the operational results.

**4.2.2.1.12 AS algorithms selection**

*Requirement Name:* AS algorithms selection

*Requirement Reference:* TS 33.501 [2], clause 6.7.3.0 and clause 5.11.2.

*Requirement Description:* "The serving network shall select the algorithms to use dependent on: the UE security capabilities of the UE, the configured allowed list of security capabilities of the currently serving network entity." as specified in TS 33.501 [2], clause 5.11.2".

"Each gNB shall be configured via network management with lists of algorithms which are allowed for usage. There shall be one list for integrity algorithms, and one for ciphering algorithms. These lists shall be ordered according to a priority decided by the operator." as specified in TS 33.501 [2], clause 6.7.3.0.

*Threat References:* TR 33.926 [5], D.2.2.5 – AS algorithm selection and use

*Test Case:* the test case in subclause 4.2.2.1.5 of TS 33.216 [4]

#### 4.2.2.1.13 Key refresh at the gNB

*Requirement Name:* Key refresh at the gNB

*Requirement Reference:* TS 33.501 [2], clause 6.9.4.1; TS 38.331 [6], clause 5.3.1.2

*Requirement Description:* "Key refresh shall be possible for  $K_{gNB}$ ,  $K_{RRC-enc}$ ,  $K_{RRC-int}$ ,  $K_{UP-int}$ , and  $K_{UP-enc}$  and shall be initiated by the gNB when a PDCP COUNTs are about to be re-used with the same Radio Bearer identity and with the same  $K_{gNB}$ ." as specified in TS 33.501 [2], clause 6.9.4.1.

"The network is responsible for avoiding reuse of the COUNT with the same RB identity and with the same key, e.g. due to the transfer of large volumes of data, release and establishment of new RBs, and multiple termination point changes for RLC-UM bearers. In order to avoid such re-use, the network may e.g. use different RB identities for RB establishments, change the AS security key, or an RRC\_CONNECTED to RRC\_IDLE/RRC\_INACTIVE and then to RRC\_CONNECTED transition." as specified in TS 38.331 [6], clause 5.3.1.2.

*Threat References:* TR 33.926 [5], clause D.2.2.7 Key Reuse

*Test Case :*

**Test Name:** TC\_GNB\_KEY\_REFRESH\_DRB\_ID

**Purpose:**

Verify that the gNB performs  $K_{gNB}$  refresh when DRB-IDs are about to be reused under the following conditions:

- the successive Radio Bearer establishment uses the same RB identity while the PDCP COUNT is reset to 0, or
- the PDCP COUNT is reset to 0 but the RB identity is increased after multiple calls and wraps around.

**Pre-Conditions:**

The UE, AMF and SMF may be simulated.

**Execution Steps**

- 1) The gNB sends the AS Security Mode Command message to the UE.
- 2) The UE responds with the AS Security Mode Complete message.
- 3) A DRB is set up.
- 4) DRB is set up and torn down for multiple times within one active radio connection without the UE going to idle (e.g. by the UE making multiple IMS calls, or by the SMF requesting PDU session modification and deactivation via the AMF), until the DRB ID is reused.

**Expected Results:**

Before DRB ID reuse, the gNB takes a new  $K_{gNB}$  into use by e.g. triggering an intra-cell handover or triggering a transition from RRC\_CONNECTED to RRC\_IDLE or RRC\_INACTIVE and then back to RRC\_CONNECTED.

**Expected format of evidence:**

Part of log that shows all the DRB identities and the intra-cell handover or the transition from RRC\_CONNECTED to RRC\_IDLE or RRC\_INACTIVE and then back to RRC\_CONNECTED. This part can be presented, for example, as a screenshot.

#### 4.2.2.1.14 Bidding down prevention in Xn-handovers

*Requirement Name:* Bidding Down Prevention

*Requirement Reference:* TS 33.501 [2], clause 6.7.3.1

*Requirement Description:* "In the Path-Switch message, the target gNB shall send the UE's 5G security capabilities, UP security policy with corresponding PDU session ID received from the source gNB to the AMF." as specified in TS 33.501 [2], clause 6.7.3.1."

*Threat References:* TR 33.926 [4], clause D.2.2.6 Bidding Down on Xn-Handover

*Test Case:* the test case in subclause 4.2.2.1.10 of TS 33.216 [4]

#### 4.2.2.1.15 AS protection algorithm selection in gNB change

*Requirement Name:* AS protection algorithm selection in gNB change.

*Requirement Reference:* TS 33.501 [2], clauses 6.7.3.1 and 6.7.3.2

*Requirement Description:* "The target gNB shall select the algorithm with highest priority from the UE's 5G security capabilities according to the locally configured prioritized list of algorithms (this applies for both integrity and ciphering algorithms). The chosen algorithms shall be indicated to the UE in the Handover Command message if the target gNB selects different algorithms compared to the source gNB " as specified in TS 33.501 [2], clause 6.7.3.1, and clause 6.7.3.2.

*Threat References:* TR 33.926 [5], D.2.2.5 – AS algorithm selection and use

*Test Case:* the test case in subclause 4.2.2.1.11 of TS 33.216 [4]

#### 4.2.2.1.16 Control plane data confidentiality protection over N2/Xn interface

*Requirement Name:* Control plane data confidentiality protection over N2/Xn interface

*Requirement Reference:* TS 33.501 [2], clauses 9.2 and 9.4

*Requirement Description:* "The transport of control plane data over N2 shall be integrity, confidentiality and replay-protected." "The transport of control plane data and user data over Xn shall be integrity, confidentiality and replay-protected." as specified in TS 33.501 [2], clauses 9.2 and 9.4.

*Threat References:* TR 33.926 [5], clause D.2.2.1 – Control plane data confidentiality protection.

*Test Case:* the test case in subclause 4.2.2.1.1 of TS 33.216 [4]

#### 4.2.2.1.17 Control plane data integrity protection over N2/Xn interface

*Requirement Name:* Control plane data integrity protection over N2/Xn interface

*Requirement Reference:* TS 33.501[2], clauses 9.2 and 9.4

*Requirement Description:* "The transport of control plane data over N2 shall be integrity, confidentiality and replay-protected." "The transport of control plane data and user data over Xn shall be integrity, confidentiality and replay-protected." as specified in TS 33.501 [2], clauses 9.2 and 9.4.

*Threat References:* TR 33.926 [5], clause D.2.2.2 – Control plane data integrity protection.

*Test Case:* the test case in subclause 4.2.2.1.2 of TS 33.216 [4].

#### 4.2.2.1.18 Key update at the gNB on dual connectivity

*Requirement Name:* Key update at the gNB on dual connectivity

*Requirement Reference:* TS 33.501 [2], clause 6.10.2.1; clause 6.10.2.2.1.

*Requirement Description:* "When executing the procedure for adding subsequent radio bearer(s) to the same SN, the MN shall, for each new radio bearer, assign a radio bearer identity that has not previously been used since the last  $K_{SN}$  change. If the MN cannot allocate an unused radio bearer identity for a new radio bearer in the SN, due to radio bearer identity space exhaustion, the MN shall increment the SN Counter and compute a fresh  $K_{SN}$ , and then shall perform a SN Modification procedure to update the  $K_{SN}$ " as specified in TS 33.501 [2], clause 6.10.2.1.

"The SN shall request the Master Node to update the  $K_{SN}$  over the Xn-C, when uplink and/or downlink PDCP COUNTs are about to wrap around for any of the SCG DRBs or SCG SRB" as specified in TS 33.501 [2], clause 6.10.2.2.1.

NOTE: The following testcases are only tested when the NR-NR DC, NE-DC and EN-DC scenarios are deployed.

*Threat References:* TR 33.926 [5], clause D.2.2.7 Key Reuse

*Test Case :*

**Test Name:** TC\_GNB\_DC\_KEY\_UPDATE\_DRB\_ID

**Purpose:**

Verify that the gNB under test acting as a Master Node (MN) performs  $K_{SN}$  update when DRB-IDs are about to be reused.

**Pre-Conditions:**

- Test environment with a gNB or ng-eNB acting as the Secondary Node (SN), which may be simulated
- Test environment with a UE, SMF and AMF, which may be simulated

**Execution Steps**

1. The gNB under test establishes RRC connection and AS security context with the UE.
2. The gNB under test establishes security context between the UE and the SN for the given AS security context shared between the gNB under test and the UE; and generates a  $K_{SN}$  sent to the SN.
3. A SCG bearer is set up between the UE and the SN.
4. The gNB under test is triggered to execute the SN Modification procedure to provide additional available DRB IDs to be used for SN terminated bearers (e.g. by the UE making multiple IMS calls, or by the SMF requesting PDU session modification and deactivation via the AMF), until the DRB IDs are reused,

**Expected Results:**

- Before DRB ID reuse, the gNB under test generates a new  $K_{SN}$  and sends it via the SN Modification Request message to the SN.

**Expected format of evidence:**

Evidence suitable for the interface, e.g. text representation of the captured SN Modification Request message.

## 4.2.3 Technical Baseline

### 4.2.3.1 Introduction

The present clause provides baseline technical requirements.

### 4.2.3.2 Protecting data and information

#### 4.2.3.2.1 Protecting data and information – general

There are no gNB-specific additions to clause 4.2.3.2.1 of TS 33.117 [3].

#### 4.2.3.2.2 Protecting data and information – unauthorized viewing

There are no gNB-specific additions to clause 4.2.3.2.2 of TS 33.117 [3].

#### 4.2.3.2.3 Protecting data and information in storage

There are no gNB-specific additions to clause 4.2.3.2.3 of TS 33.117 [3].

#### 4.2.3.2.4 Protecting data and information in transfer

There are no gNB-specific additions to clause 4.2.3.2.4 of TS 33.117 [3].

#### 4.2.3.2.5 Logging access to personal data

The requirement and testcase in clause 4.2.3.2.5 of TS 33.117 [3] are not applicable to the gNB network products.

#### 4.2.3.3 Protecting availability and integrity

There are no gNB-specific additions to clause 4.2.3.3 of TS 33.117 [3].

#### 4.2.3.4 Authentication and authorization

##### 4.2.3.4.1 Authentication attributes

gNB-specific adaptation to clause 4.2.3.4.2.1 of TS 33.117 [2] is:

Dual-factor authentication by combining several authentication options as noted in clause 4.2.3.4.2.1 of TS 33.117 [2] for higher level of security is not applicable to the gNB.

Apart from the above exception, there are no other gNB-specific adaptations to clause 4.2.3.4.2 of TS 33.117 [3].

#### 4.2.3.5 Protecting sessions

There are no gNB-specific additions to clause 4.2.3.5 of TS 33.117 [3].

#### 4.2.3.6 Logging

There are no gNB-specific additions to clause 4.2.3.6 of TS 33.117 [3].

### 4.2.4 Operating systems

The gNB-specific additions to clause 4.2.4 of TS 33.117 [3] are:

For the requirement defined in clause 4.2.4.1.1.2 Handling of ICMP of TS 33.117[3]:

- Echo Reply can be sent by default.
- In case of remote base station auto deployment, Router Advertisement can be processed. Apart from the above exceptions, there are no gNB-specific additions to clause 4.2.4 of TS 33.117 [3].

#### 4.2.5 Web servers

There are no gNB-specific additions to clause 4.2.5 of TS 33.117 [3].

#### 4.2.6 Network devices

##### 4.2.6.1 Protection of data and information

There are no gNB-specific additions to clause 4.2.6 of TS 33.117 [3].

##### 4.2.6.2 Protecting availability and integrity

###### 4.2.6.2.1 Packet filtering

There are no gNB-specific additions to clause 4.2.6.2.1 of TS 33.117 [3].

###### 4.2.6.2.2 Interface robustness requirements

There are no gNB-specific additions to clause 4.2.6.2.2 of TS 33.117 [3].

#### 4.2.6.2.3 GTP-C Filtering

The requirement and testcase in clause 4.2.6.2.3 of TS 33.117 [3] is not applicable to gNB network products.

#### 4.2.6.2.4 GTP-U Filtering

There are no gNB-specific additions to clause 4.2.6.2.4 of TS 33.117 [3].

### 4.2.7 Void

## 4.3 gNodeB-specific adaptations of hardening requirements and related test cases.

### 4.3.1 Introduction

The present clause contains gNB-specific adaptations of hardening requirements and related test cases.

### 4.3.2 Technical Baseline

There are no gNB-specific additions to clause 4.3.2 of TS 33.117 [3].

### 4.3.3 Operating Systems

There are no gNB-specific additions to clause 4.3.3 of TS 33.117 [3].

### 4.3.4 Web Servers

There are no gNB-specific additions to clause 4.3.4 of TS 33.117 [3].

### 4.3.5 Network Devices

There are no gNB-specific additions to clause 4.3.5 of TS 33.117 [3].

### 4.3.6 Network Functions in service-based architecture

The requirements and test cases in clause 4.3.6 of TS 33.117 [3] are not applicable to the gNB network products.

## 4.4 gNodeB-specific adaptations of basic vulnerability testing requirements and related test cases

There are no gNB-specific additions to clause 4.4 of TS 33.117 [3].

## Annex A (informative): Change history

Change history							
Date	Meeting	TDoc	CR	R ev	Cat	Subject/Comment	New version
2019-06	SA#84					Upgrade to change control version	16.0.0
2019-09	SA#85	SP-190688	0001	-	F	Add abbreviation and correct references	16.1.0
2019-09	SA#85	SP-190688	0002	1	F	Editorial corrections on the threat references of some test cases	16.1.0
2019-09	SA#85	SP-190688	0003	1	F	Update requirements and test cases for gNB SCAS	16.1.0
2019-09	SA#85	SP-190688	0005	-	F	Correction to test case requirement reference	16.1.0
2019-12	SA#86	SP-191138	0006	-	F	Adding the expected evidence	16.2.0
2019-12	SA#86	SP-191138	0007	1	F	Update testcases for gNB SCAS	16.2.0
2019-12	SA#86	SP-191138	0008	-	F	Fix the reference numbers	16.2.0
2019-12	SA#86	SP-191138	0010	1	F	Corrections for clean-up and alignment	16.2.0
2020-03	SA#87E	SP-200136	0011	1	B	Complete the test cases of key refresh at the gNB	16.3.0
2020-03	SA#87E	SP-200136	0012	-	B	A new test case for key update at the gNB on dual connectivity	16.3.0
2020-07	SA#88E	SP-200358	0013	1	F	Update testcase in gNB SCAS	16.4.0
2020-07	SA#88E	SP-200358	0014	1	F	Remove mismatched threat references and test steps	16.4.0
2020-09	SA#89E	SP-200703	0015	-	F	gNB-specific adaptation to account protection by authentication attribute	16.5.0
2021-03	SA#91e	SP-210117	0019	1	F	gNB Cipher Security Policy Verification	16.6.0
2021-03	SA#91e	SP-210117	0020	1	F	gNB Integrity Security Policy Verification	16.6.0
2021-06	SA#92e	SP-210446	0021	-	F	Editorial correction in clause 4.2.2.1.5	16.7.0
2021-06	SA#92e	SP-210446	0023	1	F	Update conditions of testcases	16.7.0

---

# History

<b>Document history</b>		
V16.4.0	August 2020	Publication
V16.5.0	November 2020	Publication
V16.6.0	April 2021	Publication
V16.7.0	August 2021	Publication