

ETSI TS 136 523-2 V8.2.0 (2009-06)

Technical Specification

**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA) and
Evolved Packet Core (EPC);
User Equipment (UE) conformance specification;
Part 2: ICS
(3GPP TS 36.523-2 version 8.2.0 Release 8)**



Reference

RTS/TSGR-0536523-2v820

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	6
3.1 Definitions	6
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Recommended Test Case Applicability	7
Annex A (normative): ICS proforma for E-UTRA/EPC Generation User Equipment.....	25
A.1 Guidance for completing the ICS proforma	25
A.1.1 Purposes and structure	25
A.1.2 Abbreviations and conventions	25
A.1.3 Instructions for completing the ICS proforma	26
A.2 Identification of the User Equipment	26
A.2.1 Date of the statement	26
A.2.2 User Equipment Under Test (UEUT) identification	26
A.2.3 Product supplier	26
A.2.4 Client	27
A.2.5 ICS contact person	27
A.3 Identification of the protocol	28
A.4 ICS proforma tables.....	28
A.4.1 UE Implementation Types	28
A.4.2 UE Service Capabilities	28
A.4.2.1 3GPP Standardised UE Service Capabilities.....	28
A.4.2.1.1 Bearer Services	28
A.4.3 Baseline Implementation Capabilities	28
A.4.3.1 RF Baseline Implementation Capabilities.....	29
A.4.4 Additional information	29
A.4.5 Feature group indicators	30
Annex B (informative): Change history	34
History	36

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (ICS).

The present document is part 2 of a multi-part conformance test specification for User Equipment (UE).

3GPP TS 36.523-1 [19]: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".

3GPP TS 36.523-2: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification; Part 2: Implementation Conformance Statement (ICS) proforma specification". (the present document)

3GPP TS 36.523-3 [20]: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification; Part 3: Abstract Test Suite (ATS)".

1 Scope

The present document provides the Implementation Conformance Statement (ICS) proforma for 3rd Generation User Equipment (UE), in compliance with the relevant EPS (E-UTRA/EPC) requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-1 [24] and ISO/IEC 9646-7 [25].

The present document also specifies a recommended applicability statement for the test cases included in TS 36.523-1 [19]. These applicability statements are based on the features implemented in the UE.

Special conformance testing functions can be found in TS 36.509 [6] and the common test environments are included in 3GPP TS 36.508 [18].

The present document is valid for UE complying with EPS (E-UTRA/EPC) and implemented according to 3GPP releases starting from Release 8 up to the Release indicated on the cover page of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.
 - For a Release 8 UE, references to 3GPP documents are to version 8.x.y, when available.

Editor's Note: The Reference list is incomplete and some references are still to UMTS specs.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.003: "Numbering, Addressing and Identification".
- [3] 3GPP TS 23.122: "Non-Access-Stratum functions related to Mobile Station (MS) in idle mode".
- [4] 3GPP TS 24.008: "Mobile Radio Interface Layer 3 specification; Core Network Protocols; Stage 3".
- [5] 3GPP TS 34.108: "Common Test Environments for User Equipment (UE) Conformance Testing".
- [6] 3GPP TS 36.509: " Special conformance testing functions for User Equipment " .
- [7] 3GPP TS 34.123-1: "User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".
- [8] 3GPP TS 34.123-2: "User Equipment (UE) conformance specification; Part 2: Implementation Conformance Statement (ICS) proforma specification".
- [9] 3GPP TS 34.123-3: "User Equipment (UE) conformance specification; Part 3: Abstract Test Suites (ATS)".
- [10] 3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2".
- [11] 3GPP TS 36.302: "Services provided by the physical layer for E-UTRA".
- [12] 3GPP TS 36.304: "Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE) Procedures in idle mode " .

- [13] 3GPP TS 36.306: "Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE) Radio Access capabilities".
- [14] 3GPP TS 36.321: "Evolved Universal Terrestrial Radio Access (E-UTRA) Medium Access Control (MAC) protocol specification".
- [15] 3GPP TS 36.322: "Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Link Control (RLC) protocol specification".
- [16] 3GPP TS 36.323: "Evolved Universal Terrestrial Radio Access (E-UTRA) Packet Data Convergence Protocol (PDCP) specification".
- [17] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Resource Control (RRC) Protocol Specification".
- [18] 3GPP TS 36.508: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); Common Test Environments for User Equipment (UE) Conformance Testing".
- [19] 3GPP TS 36.523-1: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".
- [20] 3GPP TS 36.523-3: " Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification; Part 3: Abstract Test Suites (ATS)".
- [21] 3GPP TR 24.801: "3GPP System Architecture Evolution; CT WG1 Aspects".
- [22] 3GPP TS 23.401: "3GPP System Architecture Evolution; GPRS enhancements for E-UTRAN access".
- [23] 3GPP TS 51.010-1: "Mobile Station (MS) conformance specification; Part 1: Conformance specification".
- [24] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [25] ISO/IEC 9646-7: "Information technology - Open systems interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [26] 3GPP2 C.S0024-A-v3.0: "cdma2000 High Rate Packet Data Air Interface Specification".
- [27] 3GPP2 C.S0002-A: "Physical Layer Standard for cdma2000 Spread Spectrum Systems – Release A".

3 Definitions, symbols and abbreviations

For the purposes of the present document, the following terms, definitions, symbols and abbreviations apply:

- such given in TR 21.905[1]
- such given in ISO/IEC 9646-1 [24] and ISO/IEC 9646-7 [25]

NOTE: Some terms and abbreviations defined in [24] and [25] are explicitly included below with small modification to reflect the terminology used in 3GPP.

3.1 Definitions

Implementation Conformance Statement (ICS): A statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented.

ICS proforma: A document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS.

Implementation eXtra Information for Testing (IXIT): A statement made by a supplier or implementer of an UEUT which contains or references all of the information (in addition to that given in the ICS) related to the UEUT and its testing environment, which will enable the test laboratory to run an appropriate test suite against the UEUT.

IXIT proforma: A document, in the form of a questionnaire, which when completed for an UEUT becomes an IXIT.

Protocol Implementation Conformance Statement (PICS): An ICS for an implementation or system claimed to conform to a given protocol specification.

Protocol Implementation eXtra Information for Testing (PIXIT): An IXIT related to testing for conformance to a given protocol specification.

static conformance review: A review of the extent to which the static conformance requirements are claimed to be supported by the UEUT, by comparing the answers in the ICS(s) with the static conformance requirements expressed in the relevant specification(s).

3.2 Symbols

No specific symbols have been identified so far.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ENB	Evolved Node B
FFS	For Further Study
ICS	Implementation Conformance Statement
IXIT	Implementation eXtra Information for Testing
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
SCS	System Conformance Statement
TC	Test Case
UEUT	User Equipment Under Test

4 Recommended Test Case Applicability

The applicability of each individual test is identified in Table 4-1. This is just a recommendation based on the purpose for which the test case was written.

The applicability of every test is formally expressed by the use of Boolean expression that are based on parameters (ICS) included in annex A of the present document.

Additional information related to the Test Case (TC), e.g. affecting its dynamic behaviour or its execution may be provided as well

The columns in Table 1 have the following meaning:

Clause

The clause column indicates the clause number in TS 36.523-1 [19] that contains the test body.

Title

The title column describes the name of the test and contains the clause title of the clause in TS 36.523-1 [19] that contains the test body.

Release

The release column indicates the earliest release from which each the test case is applicable.

Applicability - Condition

The following notations are used for the applicability column:

R	recommended - the test case is recommended
O	optional – the test case is optional
N/A	not applicable - in the given context, the test case is not recommended.
Ci	conditional - the test is recommended ("R") or not ("N/A") depending on the support of other items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." is used to avoid ambiguities.

NOTE: The conditions are defined in Table 4-1a.

Applicability - Comments

This column contains a verbal description of the condition.

Additional Information - Specific ICS

This column contains the mnemonics of ICS(s) affecting the dynamic behaviour of the TC.

Additional Information - Specific IXIT

This column contains the mnemonics of IXIT(s) affecting the dynamic behaviour of the TC.

NOTE 1: More columns may be added in the future if appropriate e.g. Number of test executions, etc.

NOTE 2: To meet the validation requirements from certification bodies then there is a need to uniquely reference the FDD and TDD branch of common FDD and TDD test cases. The FDD and TDD branches of common FDD and TDD test cases can be referenced by amending a "FDD" or "TDD" suffix to the test case clause number. For example for AM RLC test case 7.2.3.13 the FDD and TDD branches can be identified by "7.2.3.13 FDD" and "7.2.3.13 TDD".

Table 4-1: Applicability of tests and additional information for testing

Clause	TC Title	Release	Applicability		Additional Information	
			Condition	Comment	Specific ICS	Specific IXIT
	IDLE MODE					
6.1.1.1	PLMN selection of RPLMN, HPLMN/EHPLMN, UPLMN and OPLMN: Automatic mode	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.2	Cell selection, Qrxlevmin	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.3	Cell selection (intra frequency intra E-UTRAN) when the serving cell becomes non-suitable ($S < 0$, barred)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.4	Cell reselection	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.5	Cell reselection for inter-band operation	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.6	Cell reselection using Qhyst, Qoffset and Treselection	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.7	Cell reselection: Equivalent PLMN	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.8	Cell reselection using cell status and cell reservations (access control class 0-9)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.9	Cell reselection using cell status and cell reservations (access control class 11-15)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.11	Inter-frequency cell reselection	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.1.2.15	Inter-frequency cell reselection according to cell reselection priority provided by SIBs	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
6.2.2.1	Inter-RAT cell Selection / from E-UTRA RRC_IDLE to UTRA_Idle, serving cell becomes non-suitable ($S_{ServingCell} < 0$, barred)	Rel-8	C01	UEs supporting E-UTRA and UTRA	pc_eFDD	
					pc_eTDD	
6.2.2.2	Inter-RAT cell Selection / from E-UTRA RRC_IDLE to GSM_Idle/GPRS Packet_idle, serving cell becomes non-suitable ($S_{ServingCell} < 0$, barred)	Rel-8	C05	UEs supporting E-UTRA and GSM	pc_eFDD	
					pc_eTDD	
6.2.2.3	Inter-RAT Cell selection / from E-UTRA RRC_IDLE to HRPD Idle, when the serving cell becomes non-suitable ($S_{ServingCell} < 0$)	Rel-8	C06	UEs supporting E-UTRA and HRPD	pc_eFDD	
					pc_eTDD	
6.2.3.1	Inter-RAT Cell Reselection / from E-UTRA RRC_IDLE to GSM_Idle/GPRS Packet_Idle	Rel-8	C05	UEs supporting E-UTRA and GSM	pc_eFDD	

6.2.3.2	Inter-RAT Cell Reselection / from GSM_Idle/GPRS Packet_Idle to E-UTRA	Rel-8	C05	UEs supporting E-UTRA and GSM	pc_eTDD	
					pc_eFDD	
					pc_eTDD	
6.2.3.5	Inter-RAT Cell reselection / from E-UTRA RRC_IDLE to UTRA_Idle	Rel-8	C01	UEs supporting E-UTRA and UTRA	pc_eFDD	
					pc_eTDD	
6.2.3.7	Inter-RAT Cell Reselection: from E-UTRA RRC_IDLE to HRPD Idle – When HRPD cell is higher reselection priority than E-UTRA	Rel-8	C06	UEs supporting E-UTRA and HRPD	pc_eFDD	
					pc_eTDD	
6.2.3.8	Inter-RAT Cell Reselection: from E-UTRA RRC_IDLE to HRPD Idle – When HRPD is lower reselection priority than E-UTRA	Rel-8	C06	UEs supporting E-UTRA and HRPD	pc_eFDD	
					pc_eTDD	
6.3.6	Ignoring CSG cells in cell selection/reselection when Allowed CSG list is empty or not supported	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
	LAYER 2					
7.1.1.1	CCCH mapped to UL SCH/ DL-SCH / Invalid LCID (Logical Channel ID)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.1.2	DTCH or DCCH mapped to UL SCH/ DL-SCH / Invalid LCID (Logical Channel ID)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.1	Correct Selection of RACH parameters / Random Access Preamble and PRACH resource explicitly signalled to the UE by RRC [Non Contention Based Random Access Procedure	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.2	Correct Selection of RACH parameters / Random Access Preamble and PRACH resource explicitly signalled to the UE in PDCCH Order [Non Contention Based Random Access Procedure]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.3	Correct Selection of RACH parameters, selected by MAC itself [Contention Based Random Access Procedure]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.4	Random Access Procedure: Successful	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.5	Random Access Procedure: MAC PDU containing multiple RARs	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.6	Maintenance of Uplink Time Alignment	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.7	MAC-Contention Resolution[Temporary C-RNTI]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.8	MAC-Contention Resolution[C-RNTI]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.2.9	MAC-Backoff Indicator	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	

7.1.3.1	Correct handling of DL assignment / dynamic case	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.3.2	Correct handling of DL assignment / semi persistent case [Conf Req:]	Rel-8	C18	UEs supporting E-UTRA and Feature Group Indicator 3	pc_eFDD	
					pc_eTDD	
7.1.3.3	MAC PDU header handling	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.3.4	Correct HARQ process handling [DCCH /DTCH]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.3.5	Correct HARQ process handling [CCCH]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.3.6	Correct HARQ process handling [BCCH]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.3.7	MAC-Padding	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.3.9	MAC reset	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.1	Correct handling of UL assignment / dynamic case	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.2	Correct handling of UL assignment / semi persistent case	Rel-8	C18	UEs supporting E-UTRA and Feature Group Indicator 3	pc_eFDD	
					pc_eTDD	
7.1.4.3	Logical channel prioritization handling	Rel-8	C19	UEs supporting E-UTRA and Feature Group Indicator 6	pc_eFDD	
					pc_eTDD	
7.1.4.4	Correct Handling of MAC control information [Scheduling Requests/ PUCCH]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.5	Correct Handling of MAC control information [Scheduling Requests/Random Access Procedure]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.6	Correct Handling of MAC control information [Buffer Status/ UL data arrives in the UE Tx buffer / Regular BSR]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.7	Correct Handling of MAC control information [Buffer Status/ UL resources are allocated/ Padding BSR]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.8	Correct Handling of MAC control information [Buffer Status/ Periodic BSR Timer expires]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.10	MAC-Padding	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.11	Correct HARQ process handling	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.12	MAC reset	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.13	MAC PDU header handling	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.14	Correct HARQ process handling: TTI Bundling	Rel-8	C09	UEs supporting E-UTRA and Feature Group Indicator 3	pc_eFDD	
					pc_eTDD	

7.1.4.15	UE Power HeadRoom Reporting [Periodic reporting]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.4.16	UE Power HeadRoom Reporting [DL_Pathloss change reporting]	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.6.1	DRX Operation / (short cycle not configured) /Parameters configured by RRC (radio resource configuration)	Rel-8	C08	UEs supporting E-UTRA and Feature Group 5.	pc_eFDD	
					pc_eTDD	
7.1.6.2	DRX Operation / Parameters (short cycle not configured) / DRX command MAC control element reception	Rel-8	C08	UEs supporting E-UTRA and Feature Group 5.	pc_eFDD	
					pc_eTDD	
7.1.7.1.1	DL-SCH Transport Block Size selection / DCI format 1 / RA type 0	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.7.1.2	DL-SCH Transport Block Size selection / DCI format 1 / RA type 1	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.7.1.3	DL-SCH Transport Block Size selection / DCI format 1A / RA type 2 / Localised VRB	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.7.1.4	DL-SCH Transport Block Size selection / DCI format 1A / RA type 2 / Distributed VRB	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.1.7.2.1	UL-SCH Transport Block Size selection / DCI format 0	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.2.2.1	UM RLC / Segmentation and Reassembly / 5-bit SN / "Framing Info Field"	Rel-8	C15	UEs supporting E-UTRA and Feature Group Indicator 3 and Feature Group Indicator 7	pc_eFDD	
					pc_eTDD	
7.2.2.2	UM RLC / Segmentation and Reassembly / 10-bit SN / "Framing Info Field"	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eFDD	
					pc_eTDD	
7.2.2.3	UM RLC / Reassembly / 5-bit SN / LI value > PDU size	Rel-8	C15	UEs supporting E-UTRA and Feature Group Indicator 3 and Feature Group Indicator 7	pc_eFDD	
					pc_eTDD	
7.2.2.4	UM RLC/ Reassembly / 10-bit SN / LI value > PDU size	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eFDD	
					pc_eTDD	
7.2.2.5.1	UM RLC / 5-bit SN / Correct use of Sequence Numbering	Rel-8	C15	UEs supporting E-UTRA and Feature Group Indicator 3 and Feature Group Indicator 7	pc_eFDD	
					pc_eTDD	
7.2.2.5.2	UM RLC / 10-bit SN / Correct use of Sequence Numbering	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eFDD	
					pc_eTDD	
7.2.2.6	UM RLC / Concatenation, Segmentation and Reassembly	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eFDD	
					pc_eTDD	
7.2.2.7	UM RLC / In sequence delivery of upper layers PDUs without residual loss of RLC PDUs / Maximum re-ordering delay below <i>t-Reordering</i>	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eFDD	

7.2.2.8	UM RLC/ In sequence delivery of upper layer PDUs without residual loss of RLC PDUs/ Maximum re-ordering delay exceeds <i>t-Reordering</i>	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eTDD	
					pc_eFDD	
7.2.2.9	UM RLC/ In sequence delivery of upper layer PDUs with residual loss of RLC PDUs/ Maximum re-ordering delay exceeds <i>t-Reordering</i>	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eTDD	
					pc_eFDD	
7.2.2.10	UM RLC / Duplicated detection of RLC PDUs	Rel-8	C16	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eTDD	
					pc_eFDD	
7.2.2.11	UM RLC / RLC re-establishment procedure	Rel-8	Cyy	UEs supporting E-UTRA and Feature Group Indicator 7	pc_eTDD	
					pc_eFDD	
7.2.3.1	AM RLC / Concatenation and Reassembly	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.2	AM RLC / Segmentation and Reassembly / No PDU segmentation	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.3	AM RLC / Segmentation and Reassembly / "Framing Info Field"	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.4	AM RLC / Segmentation and Reassembly / Different numbers of Length Indicators	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.5	AM RLC / Reassembly / LI value > PDU size	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.6	AM RLC / Correct use of Sequence Numbering	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.7	AM RLC / Control of Transmit Window	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.8	AM RLC / Control of Receive Window	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.9	AM RLC / Polling for status	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.10	AM RLC / Receiver Status Triggers	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.12	AM RLC / Operation of the RLC reestablishment procedure / UE Terminated	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.13	AM RLC / Reconfiguration of RLC parameters by upper layers	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.14	AM RLC / In sequence delivery of upper layers PDUs	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.15	AM RLC / Re-ordering of RLC PDU segments	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
7.2.3.16	AM RLC / Re-transmission of RLC PDU without re-segmentation	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	

7.2.3.17	AM RLC / Re-segmentation RLC PDU / SO, FI, LSF	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.2.3.18	AM RLC / Reassembly / AMD PDU reassembly from AMD PDU segments; Segmentation Offset and Last Segment Flag fields	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.2.3.19	Void					
7.2.3.20	AM RLC / Duplicate detection of RLC PDUs	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.2.3.21	AM RLC / RLC re-establishment at RRC Connection reconfiguration including <i>mobilityControlInfo</i> IE	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.1.1	Maintenance of PDCP sequence numbers (user plane, RLC AM)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.1.2	Maintenance of PDCP sequence numbers (user plane, RLC UM, short PDCP SN (7 bits))	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.1.3	Maintenance of PDCP sequence numbers (user plane, RLC UM, long PDCP SN (12 bits))	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.3.1	Ciphering and Deciphering: Correct functionality of EPS AS encryption algorithms (SNOW 3G)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.3.2	Ciphering and Deciphering: Correct functionality of EPS UP encryption algorithms (SNOW 3G)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.3.3	Ciphering and Deciphering: Correct functionality of EPS AS encryption algorithms (AES)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.3.4	Ciphering and Deciphering: Correct functionality of EPS UP encryption algorithms (AES)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.4.1	Integrity protection: Correct functionality of EPS AS integrity algorithms (SNOW3G)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.4.2	Integrity protection: Correct functionality of EPS AS integrity algorithms (AES)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.5.1	Void					
7.3.5.2	PDCP handover / Lossless handover / PDCP Sequence Number maintenance	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.5.3	PDCP handover / Non-lossless handover / PDCP Sequence Number maintenance	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.5.4	PDCP handover / Lossless handover / PDCP status report to convey the information on missing or acknowledged PDCP SDUs at handover	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
7.3.5.5	PDCP handover / In-order delivery and duplicate	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	

	elimination in the downlink					
7.3.6.1	PDCP Discard	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
					pc_eTDD	
8	RADIO RESOURCE CONTROL					
8.1.1.1	RRC / Paging for Connection in idle mode	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.1.2	RRC / Paging for notification of BCCH modification in idle mode	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.1.3	RRC / Paging for Connection in idle mode (multiple paging records)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.1.4	RRC / Paging for Connection in idle mode (Shared Network environment)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.2.1	RRC Connection Establishment: Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.2.2	RRC Connection Establishment in RRC Idle state: Reject with wait time	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.2.3	RRC Connection Establishment in RRC Idle state: return to idle state after T300 timeout	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.2.5	RRC Connection Establishment: 0% access probability for MO calls, no restriction for MO signalling	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.2.7	RRC Connection Establishment: 0% access probability for AC 0..9, AC 10 is barred, AC 11..15 are not barred, access for UE with access class in the range 11..15 is allowed.	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.2.8	RRC Connection Establishment: range of access barring time	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.2.10	RRC Connection Establishment during Cell reselection: Failure	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.3.1	RRC / RRC Connection Release: Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.3.3	RRC Connection Release: UE stays on same cell	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.3.4	RRC Connection Release: redirection to another E-UTRA frequency	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.3.5	RRC Connection Release: success (with priority information)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.1.3.6	RRC Connection Release: redirection from E-UTRAN to UTRAN	Rel-8	C01	UEs supporting E-UTRA and UTRA	pc_eFDD	
					pc_eTDD	

8.1.3.9	RRC Connection Release: redirection from E-UTRAN to CDMA2000-HRPD	Rel-8	C06	UEs supporting E-UTRA and HRPD	pc_eFDD	
					pc_eTDD	
8.1.3.10	RRC Connection Release: redirection from E-UTRAN to CDMA2000-1xRTT	Rel-8	C07	UEs supporting E-UTRA and 1xRTT	pc_eFDD	
					pc_eTDD	
8.2.1.1	RRC Connection Reconfiguration / Radio Bearer Establishment for transition from RRC_Idle to RRC_CONNECTED: Success (Default bearer, early bearer establishment)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.1.2	RRC Connection Reconfiguration / Radio Bearer Establishment for transition from RRC_IDLE to RRC_CONNECTED: Failure (Default bearer)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.1.3	RRC Connection Reconfiguration / Radio Bearer Establishment: Success (Dedicated bearer)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.1.4	RRC Connection Reconfiguration / Radio Bearer Establishment: Failure (Dedicated bearer)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.1.7	RRC Connection Reconfiguration / Radio Bearer Establishment: Success (SRB2)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.2.1	RRC Connection Reconfiguration / Radio Resource Reconfiguration: Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.2.2	RRC Connection Reconfiguration / SRB/DRB Reconfiguration: Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.3.1	RRC Connection Reconfiguration / Radio Bearer Release: Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.4.1	RRC Connection Reconfiguration / Handover: Success (Dedicated preamble)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.4.2	RRC Connection Reconfiguration / Handover: Success (Common preamble)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.4.3	RRC Connection Reconfiguration / Handover: success (intra-cell, security reconfiguration)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.4.5	RRC Connection Reconfiguration / Handover (full configuration)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.4.6	RRC Connection Reconfiguration / Handover (inter-frequency)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.4.7	RRC Connection Reconfiguration / Handover: Failure (Re-establishment successful)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.2.4.9	RRC Connection Reconfiguration / Handover (Inter-band	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	

	blind handover): Success					
8.3.1.1	Measurement configuration control and reporting/ intra E-UTRAN measurements: event A1	Rel-8	C09	UEs supporting E-UTRA and Feature Group Indicator 16	pc_eTDD	
					pc_eFDD	
8.3.1.2	Measurement configuration control and reporting/ intra E-UTRAN measurements: event A2	Rel-8	C09	UEs supporting E-UTRA and Feature Group Indicator 16	pc_eTDD	
					pc_eFDD	
8.3.1.3	Measurement configuration control and reporting / intra E-UTRAN measurements: 2 simultaneous events A3 (intra and inter frequency measurements)	Rel-8	C10	UEs supporting E-UTRA and Feature Group Indicator 25	pc_eTDD	
					pc_eFDD	
8.3.1.4	Measurement configuration control and reporting / intra E-UTRAN measurements: Periodic reporting (intra and inter frequency measurements)	Rel-8	C11	UEs supporting E-UTRA and Feature Group Indicator 16 and Feature Group Indicator 25	pc_eTDD	
					pc_eFDD	
8.3.1.5	Measurement configuration control and reporting / intra E-UTRAN measurements: 2 simultaneous event A3 (intra frequency measurements)	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
8.3.1.6	Measurement configuration control and reporting / intra E-UTRAN measurements: 2 simultaneous events A2 and A3 (Inter frequency measurements)	Rel-8	C10	UEs supporting E-UTRA and Feature Group Indicator 25	pc_eTDD	
					pc_eFDD	
8.3.1.7	Measurement configuration control and reporting/ intra E-UTRAN measurements: blacklisting	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
8.3.1.8	Measurement configuration control and reporting / intra E-UTRAN measurements: handover (IE measurement configuration present)	Rel-8	C09	UEs supporting E-UTRA and Feature Group Indicator 16	pc_eTDD	
					pc_eFDD	
8.3.1.9	Measurement configuration control and reporting / intra E-UTRAN measurements: intra-frequency handover (IE measurement configuration not present)	Rel-8	C11	UEs supporting E-UTRA and Feature Group Indicator 16 and Feature Group Indicator 25	pc_eTDD	
					pc_eFDD	
8.3.1.10	Measurement configuration control and reporting / intra E-UTRAN measurements: inter-frequency handover (IE measurement configuration not present)	Rel-8	C12	UEs supporting E-UTRA and Feature Group Indicator 13 and Feature Group Indicator 16 and Feature Group Indicator 25	pc_eTDD	
					pc_eFDD	
8.3.2.3	Measurement configuration control and reporting / inter RAT measurements: event B2 (measurement of UTRAN cells)	Rel-8	C13	UEs supporting E-UTRA and UTRA and Feature Group Indicator 16 and Feature Group Indicator 22	pc_eTDD	
					pc_eFDD	
8.3.2.4	Measurement configuration control and reporting / inter RAT measurements: Periodic reporting (measurement of UTRAN cells)	Rel-8	C13	UEs supporting E-UTRA and UTRA and Feature Group Indicator 16 and Feature Group Indicator 22	pc_eTDD	
					pc_eFDD	

8.3.2.6	Measurement configuration control and reporting / inter RAT measurements: Simultaneous A2 and two B2 (measurements of E-UTRAN, UTRAN and GERAN cells)	Rel-8	C17	UEs supporting E-UTRA, UTRAN, GERAN and Feature Group Indicators 22 and 23	pc_eTDD	
					pc_eFDD	
8.3.2.7	Measurement configuration control and reporting / inter RAT measurements: event B2 (measurement of HRPD cells)	Rel-8	C06	UEs supporting E-UTRA and HRPD	pc_eTDD	
					pc_eFDD	
8.3.2.8	Measurement configuration control and reporting / inter RAT measurements: periodic reporting (measurement of HRPD cells)	Rel-8	C06	UEs supporting E-UTRA and HRPD	pc_eFDD	
					pc_eFDD	
8.3.2.9	Measurement configuration control and reporting / inter RAT measurements: event B2 (measurement of 1xRTT cells)	Rel-8	C07	UEs supporting E-UTRA and 1xRTT	pc_eFDD	
					pc_eTDD	
8.3.3.1	Measurement configuration control and reporting / SON / ANR: CGI reporting of E-UTRAN cell	Rel-8	C14	UEs supporting E-UTRA and Feature Group Indicator 5 and Feature Group Indicator 17	pc_eFDD	
					pc_eTDD	
8.4.1.8	CS fallback caused by addition of CS service / from E-UTRA(Data) to UTRA(PS+CS)	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
8.5.1.1	RRC Connection Re-establishment: Success (after Radio Link Failure)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.5.1.2	RRC Connection Re-establishment: End of procedure after T301 expiry (after Radio Link Failure)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.5.1.3	RRC Connection Re-establishment: Failure: T311 Expiry (after Radio Link Failure)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.5.1.4	RRC Connection Re-establishment: Failure: Reject (after Radio Link Failure)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
8.5.1.5	Radio Link Recovery while T310 is running	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9	EPS MOBILITY MANAGEMENT PROCEDURE					
9.1.1.1	GUTI reallocation procedure	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.1.1.2	GUTI reallocation procedure, no TA list	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.1.2.1	Authentication accepted	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.1.2.2	Authentication not accepted by the network, GUTI used, identification procedure and authentication restart	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.1.2.3	Authentication not accepted by the network, GUTI used, authentication reject and re-authentication	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	

9.1.2.4	Authentication not accepted by the UE, MAC code failure	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.1.2.5	Authentication not accepted by the UE, SQN failure	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.1.3.1	NAS security mode command accepted by the UE	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.1.3.2	NAS security mode command not accepted by the UE	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.1.1.1	Attach Procedure / Success (valid GUTI)	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.2	Attach Procedure / Success / With IMSI, GUTI reallocation	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.1.1.5	Attach Procedure / Success / ATTACH ACCEPT message includes the PDN address assigned to the UE	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.7	Attach Procedure / Success / list of equivalent PLMNs in the ATTACH ACCEPT message	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.1.1.9	ATTACH / rejected / IMSI invalid	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.10	ATTACH / rejected / illegal ME	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.11	ATTACH / rejected / EPS services and non-EPS services not allowed	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.12	ATTACH / rejected / GPRS services not allowed	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.13	ATTACH / rejected / PLMN not allowed	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.14	Attach / rejected / tracking area not allowed	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.15	Attach / rejected / roaming not allowed in this tracking area	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.17	Attach / rejected / no suitable cells in tracking area	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.19	ATTACH / Abnormal case / Failure due to non integrity protection	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.24	Attach / Abnormal case / Change of cell into a new tracking area	Rel-8	C04	UEs supporting E-UTRA and not CS fallback capable	pc_eFDD	
					pc_eTDD	
9.2.1.1.25	Attach / Abnormal case / Mobile originated detach required	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	

9.2.1.2.1	Combined attach procedure / Success / EPS and non-EPS services	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.1.2.2	Combined attach procedure / Success / EPS services only / IMSI unknown in HSS	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.1.2.3	Combined attach procedure / Success / EPS services only / MSC temporarily unreachable	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.1.2.4	Combined attach procedure / Success / EPS services only / CS domain not available	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.1.2.6	Combined attach / rejected / Illegal ME	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.1.2.8	Combined attach / rejected / EPS services not allowed	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.1.2.9	Combined attach / rejected / PLMN not allowed	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.1.2.10	Combined attach / rejected / Tracking area not allowed	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.2.1.1	UE initiated detach / UE switched off	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
9.2.2.1.2	UE initiated detach / USIM removed from the UE	Rel-8	C03	UEs supporting E-UTRA and USIM removal without power down	pc_eTDD, pc_USIM_Removal	
					pc_eFDD, pc_USIM_Removal	
9.2.2.1.6	UE initiated detach / Abnormal case / local detach after 5 attempts due to no network response	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
9.2.2.2.1	NW initiated detach / re-attach required	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
9.2.2.2.2	NW initiated detach / IMSI detach	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eTDD	
					pc_eFDD	
9.2.3.1.1	Normal tracking area update / accepted	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
9.2.3.1.2	Normal tracking area update / accepted / 'Active' flag set	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
9.2.3.1.4	Normal tracking area update / list of equivalent PLMNs in the TRACKING AREA UPDATE ACCEPT message	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	
9.2.3.1.5	Periodic tracking area update / accepted	Rel-8	R	UEs supporting E-UTRA	pc_eTDD	
					pc_eFDD	

9.2.3.1.8	UE receives an indication that the RRC connection was released with cause "load balancing TAU required"	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.1.10	Normal tracking area update / rejected / IMSI invalid	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.1.11	Normal tracking area update / rejected / illegal ME	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.1.12	Normal tracking area update / rejected / EPS service not allowed	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.1.13	Normal tracking area update / rejected / UE identity cannot be derived by the network	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.1.14	Normal tracking area update / rejected / UE implicitly detached	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.1.15	Normal tracking area update / rejected / PLMN not allowed	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.1.16	Normal tracking area update / rejected / tracking area not allowed	Rei-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.2.3.2.1	Combined tracking area update successful	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.2.3.2.3	Combined tracking area update / successful for EPS services only / MSC temporarily not reachable	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.2.3.2.6	Combined tracking area update / rejected / Illegal ME	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.2.3.2.10	Combined tracking area update / rejected / UE implicitly detached	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.2.3.2.12	Combined tracking area update / rejected / Tracking area not allowed	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.2.3.2.15	Combined tracking area update / rejected / Tracking area not allowed	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.3.1.1	Service Request / initiated by UE for user data	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.3.1.2	Service Request / initiated by UE for uplink signalling	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.3.1.3	Service Request / Mobile originating CS fallback	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.3.1.4	Service Request / Rejected / IMSI invalid	Rel-8	C02	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.3.1.7a	Service Request / Rejected / UE implicitly detached	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	

9.3.2.1	Paging procedure	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.3.2.2	Paging for CS fallback / Idle mode	Rel-8	C02	UEs supporting E-UTRA and UEs supporting CSfallback	pc_eFDD	
					pc_eTDD	
9.4.1	Integrity protection: Correct functionality of EPS NAS integrity algorithms (SNOW3G)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.4.2	Integrity protection: Correct functionality of EPS NAS integrity algorithms (AES)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.4.3	Ciphering and Deciphering: Correct functionality of EPS NAS encryption algorithms (SNOW3G)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
9.4.4	Ciphering and Deciphering: Correct functionality of EPS NAS encryption algorithms (AES)	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10	EPS Session Management					
10.2.1	Dedicated EPS bearer context activation / Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.3.1	EPS bearer context modification / Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.4.1	EPS bearer context deactivation / Success	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.5.1	UE requested PDN connectivity accepted by the network	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.5.2	UE requested PDN connectivity accepted by the network / No PDN address allocated	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.5.3	UE requested PDN connectivity not accepted	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.6.1	UE requested PDN disconnect procedure accepted by the network	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.6.2	UE requested PDN disconnect procedure not accepted by the network	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
10.7.1	UE requested bearer resource modification accepted by the network / new EPS bearer context	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	
					pc_eTDD	
12	E-UTRA Radio Bearer Tests					
12.2	Data transfer of E-UTRA radio bearer combinations – one layer DL spatial multiplexing	Rel-8	R	UEs supporting E-UTRA	pc_eFDD	

Table 4-1a: Applicability of tests Conditions

C01	IF [8]A.1/1 OR [8]A.1/2 THEN R ELSE N/A
C02	IF ([8]A.1/1 OR [8]A.1/2 OR [8]A.1/4) AND [8]A.3/1 AND A.4.2.1.1-1/1 THEN R ELSE N/A
C03	IF A.4.4-1/1 THEN R ELSE N/A
C04	IF (NOT A.4.2.1.1-1/1) THEN R ELSE N/A
C05	IF [8]A.1/4 THEN R ELSE N/A
C06	IF A.4.1-1/3 THEN R ELSE N/A
C07	IF A.4.1-1/4 THEN R ELSE N/A
C08	IF A.4.5-1/5 THEN R ELSE N/A
C09	IF A.4.5-1/16 THEN R ELSE N/A
C10	IF A.4.5-1/25 THEN R ELSE N/A
C11	IF A.4.5-1/16 AND A.4.5-1/25 THEN R ELSE N/A
C12	IF A.4.5-1/13 AND A.4.5-1/16 AND A.4.5-1/25 THEN R ELSE N/A
C13	IF [8]A.1/1 AND A.4.5-1/16 AND A.4.5-1/22 THEN R ELSE N/A
C14	IF A.4.5-1/5 AND A.4.5-1/17 THEN R ELSE N/A
C15	IF A.4.5-1/3 AND A.4.5-1/7 THEN R ELSE N/A
C16	IF A.4.5-1/7 THEN R ELSE N/A
C17	IF [8]A.1/1 AND [8]A.1/4 AND A.4.5-1/22 AND A.4.5-1/23 THEN R ELSE N/A
C18	IF A.4.5-1/3 THEN R ELSE N/A
C19	IF A.4.5-1/6 THEN R ELSE N/A

Annex A (normative): ICS proforma for E-UTRA/EPC Generation User Equipment

Notwithstanding the provisions of the copyright clause related to the text of the present document, The Organizational Partners of 3GPP grant that users of the present document may freely reproduce the ICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed ICS.
--

A.1 Guidance for completing the ICS proforma

A.1.1 Purposes and structure

The purpose of this ICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in relevant specifications may provide information about the implementation in a standardised manner.

The ICS proforma is subdivided into clauses for the following categories of information:

- instructions for completing the ICS proforma;
- identification of the implementation;
- identification of the protocol;
- ICS proforma tables (for example: UE implementation types, Teleservices, etc).

A.1.2 Abbreviations and conventions

The ICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [25].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Reference column

The reference column gives reference to the relevant 3GPP core specifications.

Release column

The release column indicates the earliest release from which the capability or option is relevant.

Mnemonic column

The Mnemonic column contains mnemonic identifiers for each item.

Comments column

This column is left blank for particular use by the reader of the present document.

References to items

For each possible item answer (answer in the support column) within the ICS proforma there exists a unique reference, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns shall be discriminated by letters (a, b, etc.), respectively.

A.1.3 Instructions for completing the ICS proforma

The supplier of the implementation may complete the ICS proforma in each of the spaces provided. More detailed instructions are given at the beginning of the different clauses of the ICS proforma.

A.2 Identification of the User Equipment

Identification of the User Equipment should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the ICS should be named as the contact person.

A.2.1 Date of the statement

.....

A.2.2 User Equipment Under Test (UEUT) identification

UEUT name:

.....
.....

Hardware configuration:

.....
.....
.....

Software configuration:

.....
.....
.....

A.2.3 Product supplier

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

A.2.4 Client

Name:

.....

Address:

.....

.....

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

A.2.5 ICS contact person

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

A.3 Identification of the protocol

This ICS proforma applies to the 3GPP standards listed in the normative references clause of the present document.

A.4 ICS proforma tables

A.4.1 UE Implementation Types

Table A.4.1-1: UE Radio Technologies

Item	UE Radio Technologies	Ref.	Release	Mnemonic	Comments
1	E-UTRA FDD	36.101	Rel-8	pc_eFDD	
2	E-UTRA TDD	36.101	Rel-8	pc_eTDD	
3	HRPD	C.S0024-A	Rel-8	pc_HRPD	
4	1xRTT	C.S0002-A	Rel-8	pc_1xRTT	

A.4.2 UE Service Capabilities

A.4.2.1 3GPP Standardised UE Service Capabilities

A.4.2.1.1 Bearer Services

Table A.4.2.1.1-1: Definition of Bearer Services

Item	Definition of Bearer Services	Ref.	Release	Mnemonic	Comments
1	CS fallback	24.301	Rel-8	pc_CSfallback	

A.4.3 Baseline Implementation Capabilities

Table A.4.3-1: Supported protocols

Item	Supported protocols	Ref.	Release	Mnemonic	Comments
1	EPS Mobility Management	24.301, 5	Rel-8		
2	EPS Session Management	24.301, 6	Rel-8		
3	Radio Resource Control	36.331	Rel-8		
4	Packet Data Convergence Protocol	36.323	Rel-8		
5	Radio Link Control	36.322	Rel-8		
6	Medium Access Control	36.321	Rel-8		
7	Physical Layer	36.201	Rel-8		

Table A.4.3-2: Special Conformance Testing Functions

Item	Special Conformance Testing Functions	Ref.	Release	Comments
1	UE test loop	36.509	Rel-8	
2	Max UE test loop UL RLC SDU size 65535 bits	36.509	Rel-8	

A.4.3.1 RF Baseline Implementation Capabilities

Table A.4.3.1-1: FDD RF Baseline Implementation Capabilities

Item	FDD (DS) RF Baseline Implementation Capabilities	Ref.	Release	Mnemonic	Comments
1	Frequency band: 1920-1 980, 2110-2170 MHz	36.101, 5.1	R8	pc_eBand1_Supp	Band 1
2	Frequency band: 1850-1910, 1930-1 990 MHz	36.101, 5.1	R8	pc_eBand2_Supp	Band 2
3	Frequency band: 1710-1785, 1805-1880 MHz	36.101, 5.1	R8	pc_eBand3_Supp	Band 3
4	Frequency band: 1710-1755, 2110-2155 MHz	36.101, 5.1	R8	pc_eBand4_Supp	Band 4
5	Frequency band: 824 – 849, 869-894 MHz	36.101, 5.1	R8	pc_eBand5_Supp	Band 5
6	Frequency band: 830-840, 875-885 MHz	36.101, 5.1	R8	pc_eBand6_Supp	Band 6
7	Frequency band: 2500-2570, 2620-2690 MHz	36.101, 5.1	R8	pc_eBand7_Supp	Band 7
8	Frequency band: 880–915, 925–960 MHz	36.101, 5.1	R8	pc_eBand8_Supp	Band 8
9	Frequency band: 1749.9-1784.9, 1844.9-1879.9 MHz	36.101, 5.1	R8	pc_eBand9_Supp	Band 9
10	Frequency band: 1710-1770, 2110-2170 MHz	36.101, 5.1	R8	pc_eBand10_Supp	Band 10
11	Frequency band: 1427.9-1452.9, 1475.9-1500.9 MHz	36.101, 5.1	R8	pc_eBand11_Supp	Band 11
12	Frequency band: 698-716, 728-746 MHz	36.101, 5.1	R8	pc_eBand12_Supp	Band 12
13	Frequency band: 777–787, 746–756 MHz	36.101, 5.1	R8	pc_eBand13_Supp	Band 13
14	Frequency band: 788-798, 758-768 MHz	36.101, 5.1	R8	pc_eBand14_Supp	Band 14
15	Reserved				
16	Reserved				
17	Frequency band: 704716, 734-746 MHz	36.101, 5.1	R8	pc_eBand17_Supp	Band 17
18	Frequency band: 815-830, 860-875 MHz	36.101, 5.1	R8	pc_eBand18_Supp	Band 18
19	Frequency band: 830–845, 875–890 MHz	36.101, 5.1	R8	pc_eBand19_Supp	Band 19

A.4.4 Additional information

Table A.4.4-1: Additional information

Item	Additional information	Ref.	Release	Mnemonic	Comments
1	Support of USIM removal without power down		Rel-8	pc_USIM_Removal	
2	Support of Allowed CSG list	36.331 Annex B.2	Rel-8	pc_Allowed_CSG_List	

A.4.5 Feature group indicators

Table A.4.5-1: Feature group indicators

Item	Additional information	Ref.	Release	Mnemonic	Comments
1	Support of <ul style="list-style-type: none"> - Intra-subframe frequency hopping for PUSCH scheduled by UL grant - Extended cyclic prefix with $\Delta f = 7.5\text{kHz}$ for DL resource block - DCI format 3a (TPC commands for PUCCH and PUSCH with single bit power adjustments) - Multi-user MIMO for PDSCH - Aperiodic CQI/PMI/RI reporting on PUSCH: Mode 2-0 – UE selected subband CQI without PMI - Aperiodic CQI/PMI/RI reporting on PUSCH: Mode 2-2 – UE selected subband CQI with multiple PMI 	36.331, Annex B.1	Rel-8	pc_FeatrGrp_1	Corresponding to the Index of Indicator, the leftmost binary bit 1 Set to true if supporting all functionalities in the feature group
2	Support of <ul style="list-style-type: none"> - Simultaneous CQI and ACK/NACK on PUCCH, i.e. PUCCH format 2a and 2b - Absolute TPC command for PUSCH - Resource allocation type 1 for PDSCH - Periodic CQI/PMI/RI reporting on PUCCH: Mode 2-0 – UE selected subband CQI without PMI - Periodic CQI/PMI/RI reporting on PUCCH: Mode 2-1 – UE selected subband CQI with single PMI 	36.331, Annex B.1	Rel-8	pc_FeatrGrp_2	Corresponding to the Index of Indicator, the leftmost binary bit 2 Set to true if supporting all functionalities in the feature group
3	Support of <ul style="list-style-type: none"> - Semi-persistent scheduling - TTI bundling - 5bit RLC UM SN - 7bit PDCP SN 	36.331, Annex B.1	Rel-8	pc_FeatrGrp_3	Corresponding to the Index of Indicator, the leftmost binary bit 3 Set to true if supporting all functionalities in the feature group
4	Support of <ul style="list-style-type: none"> - Short DRX cycle 	36.331, Annex B.1	Rel-8	pc_FeatrGrp_4	Corresponding to the Index of Indicator, the leftmost binary bit 4 Set to true if supporting all functionalities in the feature group
5	Support of <ul style="list-style-type: none"> - Long DRX cycle - DRX command MAC control element 	36.331, Annex B.1	Rel-8	pc_FeatrGrp_5	Corresponding to the Index of Indicator, the leftmost binary bit 5 Set to true if supporting all functionalities in the feature group

6	Support of - Piroritized bit rate	36.331, Annex B.1	Rel-8	pc_FeatrGrp_6	Corresponding to the Index of Indicator, the leftmost binary bit 6 Set to true if supporting all functionalities in the feature group
7	Support of - RLC UM	36.331, Annex B.1	Rel-8	pc_FeatrGrp_7	Corresponding to the Index of Indicator, the leftmost binary bit 7 Set to true if supporting all functionalities in the feature group
8	Support of - EUTRA RRC_CONNECTED to UTRA CELL_DCH PS handover	36.331, Annex B.1	Rel-8	pc_FeatrGrp_8	Corresponding to the Index of Indicator, the leftmost binary bit 8 Set to true if supporting all functionalities in the feature group
9	Support of - EUTRA RRC_CONNECTED to GERAN GSM_Dedicated handover	36.331	Rel-8	pc_FeatrGrp_9	Corresponding to the Index of Indicator, the leftmost binary bit 9 Set to true if supporting all functionalities in the feature group
10	Support of - EUTRA RRC_CONNECTED to GERAN (Packet_Idle) by Cell Change Order - EUTRA RRC_CONNECTED to GERAN (Packet_Idle) by Cell Change Order with NACC (Network Assisted Cell Change)	36.331, Annex B.1	Rel-8	pc_FeatrGrp_10	Corresponding to the Index of Indicator, the leftmost binary bit 10 Set to true if supporting all functionalities in the feature group
11	Support of - EUTRA RRC_CONNECTED to 1xRTT CS Active handover	36.331, Annex B.1	Rel-8	pc_FeatrGrp_11	Corresponding to the Index of Indicator, the leftmost binary bit 11 Set to true if supporting all functionalities in the feature group
12	Support of - EUTRA RRC_CONNECTED to HRPD Active handover	36.331, Annex B.1	Rel-8	pc_FeatrGrp_12	Corresponding to the Index of Indicator, the leftmost binary bit 12 Set to true if supporting all functionalities in the feature group

13	Support of - Inter-frequency handover -	36.331, Annex B.1	Rel-8	pc_FeatrGrp_13	Corresponding to the Index of Indicator, the leftmost binary bit 13 Set to true if supporting all functionalities in the feature group
14	Support of - Measurement reporting event: Event A4 – Neighbour > threshold - Measurement reporting event: Event A5 – Serving < threshold1 & Neighbour > threshold2	36.331, Annex B.1	Rel-8	pc_FeatrGrp_14	Corresponding to the Index of Indicator, the leftmost binary bit 14 Set to true if supporting all functionalities in the feature group
15	Support of - Measurement reporting event: Event B1 – Neighbour > threshold	36.331, Annex B.1	Rel-8	pc_FeatrGrp_15	Corresponding to the Index of Indicator, the leftmost binary bit 15 Set to true if supporting all functionalities in the feature group
16	Support of - Periodical measurement reporting for non-ANR related measurements	36.331, Annex B.1	Rel-8	pc_FeatrGrp_16	Corresponding to the Index of Indicator, the leftmost binary bit 16 Set to true if supporting all functionalities in the feature group
17	Support of - Periodical measurement reporting for SON / ANR - ANR related intra-frequency measurement reporting events	36.331, Annex B.1	Rel-8	pc_FeatrGrp_17	Corresponding to the Index of Indicator, the leftmost binary bit 17 Set to true if supporting all functionalities in the feature group
18	Support of - ANR related inter-frequency measurement reporting events	36.331, Annex B.1	Rel-8	pc_FeatrGrp_18	Corresponding to the Index of Indicator, the leftmost binary bit 18 Set to true if supporting all functionalities in the feature group
19	Support of - ANR related inter-RAT measurement reporting events	36.331, Annex B.1	Rel-8	pc_FeatrGrp_19	Corresponding to the Index of Indicator, the leftmost binary bit 19 Set to true if supporting all functionalities in the feature group

20	Support of - RB combination: SRB1 and SRB2 for DCCH + 1x AM DRB + 1x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 2x AM DRB + 1x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 2x AM DRB + 2x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 3x AM DRB + 1x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 3x AM DRB + 2x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 4x AM DRB + 1x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 4x AM DRB + 2x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 5x AM DRB + 3x UM DRB - RB combination: SRB1 and SRB2 for DCCH + 8x AM DRB	36.331, Annex B.1	Rel-8	pc_FeatrGrp_20	Corresponding to the Index of Indicator, the leftmost binary bit 20 Set to true if supporting all functionalities in the feature group
21	Support of - Predefined intra-subframe frequency hopping for PUSCH with $N_{sb} > 1$ - Predefined inter-subframe frequency hopping for PUSCH with $N_{sb} > 1$	36.331, Annex B.1	Rel-8	pc_FeatrGrp_21	Corresponding to the Index of Indicator, the leftmost binary bit 21 Set to true if supporting all functionalities in the feature group
22	Support of - UTRAN measurements and reporting in E-UTRA connected mode	36.331, Annex B.1	Rel-8	pc_FeatrGrp_22	Corresponding to the Index of Indicator, the leftmost binary bit 22 Set to true if supporting all functionalities in the feature group
23	Support of - GERAN measurements and reporting in E-UTRA connected mode	36.331, Annex B.1	Rel-8	pc_FeatrGrp_23	Corresponding to the Index of Indicator, the leftmost binary bit 23 Set to true if supporting all functionalities in the feature group
24	Support of - cdma2000 measurements and reporting in E-UTRA connected mode	36.331, Annex B.1	Rel-8	pc_FeatrGrp_24	Corresponding to the Index of Indicator, the leftmost binary bit 24 Set to true if supporting all functionalities in the feature group
25	Support of - Inter-frequency measurements and reporting in E-UTRA connected mode	36.331, Annex B.1	Rel-8	pc_FeatrGrp_25	Corresponding to the Index of Indicator, the leftmost binary bit 25 Set to true if supporting all functionalities in the feature group

Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2007-11	-	-	-	-	Initial version		0.0.1
2008-02	-	-	-	-	Addition applicability 6 new LTE RRC test cases.	0.0.1	0.1.0
2008-04	-	-	-	-	Editorial corrections	0.1.0	0.1.1
2008-05	-	-	-	-	Extend the Applicability table scope with additional information for testing which may include: - relevant per TC Specific PICS statements - relevant per TC Specific PIXIT statements Updated TC applicability with contributions to RAN5#39	0.1.1	0.2.0
2008-06	-	-	-	-	- Added TCs agreed at RAN5#39bis - Updating TCs names, numbers, removed TCs deleted from the TC list - Editorial update	0.2.0	0.3.0
2008-09	RP-41	RP-080595	-	-	Submitted for information. Update in accordance with RAN5#40 (Editorial update and input from R5-083453, R5-083517, R5-083654)	0.3.0	1.0.0
2008-09	post RAN5#40	-	-	-	Update to reflect the agreed during the RAN5#40 extended e-mail agreement input: - All agreed new TCs added - One modified TCs title reflected	1.0.0	1.0.1
2008-10	post RAN5#40 bis	-	-	-	- Added new agreed at RAN5#40bis TCs - Removed TCs that are removed from the LTE/SAE WP (R5-084008) - Added TCs that exist as 80% completed in the LTE/SAE WP (R5-084008) but do not exist in 36.523-2 - Modified agreed RAN5#40bis new TC numbers - Updated TCs titles to match those in the LTE/SAE WP (R5-084008)	1.0.1	1.1.0
2008-11	Post RAN5#41	-	-	-	R5-085361: - New TCs added to applicability table - TCs titles updated - TC 9.2.2.1.2 removed from applicability table - Table for provision of test loops added - Editorial changes	1.1.0	2.0.0
2008-12	RAN#42	RP-080860			Approval of version 2.0.0 at RAN#42, then put to version 8.0.0.	2.0.0	8.0.0
2008-01					Editorial corrections.	8.0.0	8.0.1
2009-03	RAN#43	R5-090101	0001	-	Removal of reference to 11-bit Length Indicator in E-UTRA RLC test cases	8.0.1	8.1.0
2009-03	RAN#43	R5-090292	0002	1	Applicability of new E-UTRA PDCP test case - 7.3.5.4	8.0.1	8.1.0
2009-03	RAN#43	R5-090569	0003	-	Updating applicability table with input relevant to agreed at RAN5#41bis 36.523-1 CRs	8.0.1	8.1.0
2009-03	RAN#43	R5-090668	0004	-	Batch 1B - Applicability of new E-UTRA PDCP test cases	8.0.1	8.1.0
2009-03	RAN#43	R5-090737	0005	-	Update of Applicability table for EPS mobility management test cases	8.0.1	8.1.0
2009-03	RAN#43	R5-090738	0006	-	Batch 1: Applicability for new MAC test cases 7.1.3.9 & 7.1.4.12	8.0.1	8.1.0
2009-03	RAN#43	R5-090751	0007	-	Addition of Applicability new LTE test cases	8.0.1	8.1.0
2009-05	RAN#44	R5-092056	0008	-	GCF Priority 2 - Adding TC 9.1.2.5 to applicability	8.1.0	8.2.0
2009-05	RAN#44	R5-092091	0009	-	GCF Priority 2 - Addition of applicability statement for E-UTRAN test case 6.1.2.7 for Cell reselection: Equivalent PLMN	8.1.0	8.2.0
2009-05	RAN#44	R5-092116	0010	-	GCF Priority 1 - Applicability of new E-UTRA MAC test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092117	0011	-	GCF Priority 1 - Proposal to remove E-UTRA RLC test case 7.2.3.19 (Part 2)	8.1.0	8.2.0
2009-05	RAN#44	R5-092207	0012	-	GCF Priority 2 - Addition of applicability for new EMM test case	8.1.0	8.2.0
2009-05	RAN#44	R5-092215	0013	-	GCF Priority 2 - Addition of applicability for new idle mode and RRC test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092254	0014	-	Update of Applicability table for agreed EMM test cases in RAN5#42bis	8.1.0	8.2.0
2009-05	RAN#44	R5-092255	0015	-	GCF Priority 2 - Applicability for new idle mode test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092279	0016	-	Addition of Applicability New LTE Test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092404	0017	-	GCF priority 2: Applicability statements for the new MAC DRX test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092407	0018	-	GCF Priority 2 - Addition of applicability for UM RLC test case 7.2.2.11	8.1.0	8.2.0
2009-05	RAN#44	R5-092415	0019	-	GCF Priority 2: Applicability of new EMM test cases	8.1.0	8.2.0

2009-05	RAN#44	R5-092416	0020	GCF Priority 2: Applicability of new Cell Selection test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092424	0021	Addition of LTE Operating Band Capabilities for FDD Mode Test frequencies	8.1.0	8.2.0
2009-05	RAN#44	R5-092432	0022	GCF Priority 2 - Addition of Applicability statement for MAC test case 7.1.4.14	8.1.0	8.2.0
2009-05	RAN#44	R5-092433	0023	GCF Priority 2: Applicability of new Cell Reselection test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092448	0024	Update of Applicability for Feature Group Indicators	8.1.0	8.2.0
2009-05	RAN#44	R5-092450	0025	GCF Priority 1 - Update of applicability for RRC part 3 test cases based on Feature Group Indicators	8.1.0	8.2.0
2009-05	RAN#44	R5-092508	0026	Missing applicability of EMM/ESM test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092509	0027	Applicability of new EMM & ESM test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092586	0028	GCF Priority 1 - Update of applicability for RLC test cases	8.1.0	8.2.0
2009-05	RAN#44	R5-092769	0029	GCF Priority 2 - Applicability of new RRC test case 8.3.2.6	8.1.0	8.2.0
2009-05	RAN#44	R5-092770	0030	GCF Priority 2 - Update of applicability for MAC test cases based on Feature Group Indicators	8.1.0	8.2.0
2009-05	RAN#44	R5-092783	0031	Addition of applicability for new idle mode CSG test cases	8.1.0	8.2.0

History

Document history		
V8.0.1	January 2009	Publication
V8.1.0	April 2009	Publication
V8.2.0	June 2009	Publication