

ETSI TS 155 243 V19.0.0 (2025-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Specification of the GIA4 integrity algorithm
for General Packet Radio Service (GPRS);
Design conformance test data
(3GPP TS 55.243 version 19.0.0 Release 19)**



ReferenceRTS/TSGS-0355243vj00

KeywordsGSM, SECURITY

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 Introductory information	5
4.1 Introduction	5
4.2 Notation.....	5
4.2.1 Radix.....	5
4.2.2 Conventions	6
4.2.3 Bit/Byte ordering	6
4.3 List of variables.....	6
5 Conformance data	7
Annex A (informative): Change history	8
History	9

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document has been prepared by the 3GPP Task Force, and gives a detailed specification of the 3GPP integrity algorithm GIA4.

The present document is the third of three, which between them form the entire specification of the 3GPP Integrity Algorithm GIA4:

- 3GPP TS 55.241: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Specification of the GIA4 integrity algorithms for GPRS; GIA4 specification".
- 3GPP TS 55.242: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Specification of the GIA4 integrity algorithms for GPRS; Implementers' test data".
- **3GPP TS 55.243: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Specification of the GIA4 integrity algorithms for GPRS; Design conformance test data".**

1 Scope

The present document defines the Design conformance test data for the 3GPP integrity algorithm GIA4.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

[2] 3GPP TS 55.241: "Specification of the GIA4 encryption algorithms for GPRS; GIA4 specification".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

4 Introductory information

4.1 Introduction

The integrity algorithm GIA4 computes a 32-bit MAC (Message Authentication Code) of a given input message using integrity key KI128. The approach adopted uses KASUMI [2] in a form of CBC-MAC mode.

4.2 Notation

4.2.1 Radix

The prefix "0x" is used to indicate hexadecimal numbers.

4.2.2 Conventions

The assignment operator "=", is used as in several programming languages. So the following:

$$\langle \text{variable} \rangle = \langle \text{expression} \rangle$$

means that $\langle \text{variable} \rangle$ assumes the value that $\langle \text{expression} \rangle$ had before the assignment took place. For instance:

$$x = x + y + 3$$

means:

(new value of x) becomes (old value of x) + (old value of y) + 3.

4.2.3 Bit/Byte ordering

All data variables in the present document are presented with the most significant bit (or byte) on the left hand side and the least significant bit (or byte) on the right hand side. Where a variable is broken down into a number of sub-strings, the left most (most significant) sub-string is numbered 0, the next most significant is numbered 1 and so on through to the least significant.

For example an n -bit MESSAGE is subdivided into 64-bit substrings $MB_0, MB_1 \dots MB_i$ so for the following message:

0x0123456789ABCDEFEDCBA987654321086545381AB594FC28786404C50A37...

$MB_0 = 0x0123456789ABCDEF$

$MB_1 = 0xFEDCBA9876543210$

$MB_2 = 0x86545381AB594FC2$

$MB_3 = 0x8786404C50A37...$

In binary this would be:

0000000100100011010001010110011110001001101010111100110111101111111110...

with

$MB_0 = 0000000100100011010001010110011110001001101010111100110111101111$

$MB_1 = 1111111011011100101110101001100001110110010101000011001000010000$

$MB_2 = 10000110010101000101001110000001101010110010100111111000010$

$MB_3 = 1000011110000110010000000100110001010000101000110111...$

4.3 List of variables

A, B are 64-bit registers that are used within the function to hold intermediate values.

BLOCKS an integer variable indicating the number of successive applications of KASUMI that need to be performed.

CONSTANT-F a 32-bit parameter which is constant for any given FRAMETYPE input.

DIRECTION a 1-bit input indicating the direction of transmission (uplink or downlink).

FRAMETYPE an 8-bit input to the function indicating the type of frame to be protected.

INPUT-I a 32-bit time variant input to the function.

KI128 the 128-bit integrity key.

KM a 128-bit constant that is used to modify a key.

M an input to the function which specifies the number of octets of message to be MAC'd (1-65536).

MAC the 32-bit message authentication code (MAC) produced by the function.

MESSAGE the input octet stream of length M octets that is to be processed by the function.

PS is the input padded string processed by the function.

5 Conformance data

This clause only available under licence.

See <http://www.etsi.org/about/what-we-do/security-algorithms-and-codes/cellular-algorithm-licences>.

Annex A (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-03	SA#75	SP-170089				Presented for approval	2.0.0
2017-03	SA#75					Upgrade to change control version	13.0.0
2017-03	SA#75	-	-	-		Promotion to Release 14 without technical change	14.0.0
2018-06	-	-	-	-	-	Update to Rel-15 version (MCC)	15.0.0
2020-07	-	-	-	-	-	Update to Rel-16 version (MCC)	16.0.0
2022-03	-	-	-	-	-	Update to Rel-17 version (MCC)	17.0.0
2024-03	-	-	-	-	-	Update to Rel-18 version (MCC)	18.0.0
2025-10	-	-	-	-	-	Update to Rel-19 version (MCC)	19.0.0

History

Document history		
V19.0.0	October 2025	Publication